



the future is safer with altro

Altro Walkway[™] 20




Our popular, hard-wearing safety flooring with modern and traditional looks in 44 colors

2mm
thick

6'7"
width

66'
length


sheet
format



Swan

VMi2012P LRV: 75


WR291 / AM01



Winter

VMi2053 LRV: 61


WR105 / AM01



Blizzard

VMi2055 LRV: 44


WR79 / AM191



Streetlight

VMi2005P LRV: 45


WR287 / AM79



Cloud

VM2014 LRV: 41


WR79 / AM191



Temple

VM2009P LRV: 27


WR261 / AM81



Rock

VMi2004P LRV: 23


WR84 / AM84



Fog

VM20153 LRV: 27


WR81 / AM81



Dolphin

VM2010 LRV: 21


WR86 / AM86



Whale

VMi2054 LRV: 20


WR86 / AM86



Nickel - Matches AQI Tern

VMi2019P LRV: 29


WR81 / AM81



Pavement

VMi2007P LRV: 14

WR83 / AM83



Runway

VM2006P LRV: 9

WR72 / AM



Midnight

VM20421 LRV: 11


WR72 / AM72



Black

VM20892 LRV: 6

WR100 / AM100



Nightfall

VMi2056 LRV: 10

WR72 / AM72



Pitch

VM2020P LRV: 5


WR277 / AM100



Coal

VMi2058 LRV: 6


WR100 / AM100



Tarragon

VMi2052 LRV: 26


WR52 / AM52



Skyline

VM20332 LRV: 24


WR52 / AM52



Fresco

VMi2017P LRV: 31


WR309 / AM309



Stream

VM2001P LRV: 22


WR288 / AM71



Blue

VM20412 LRV: 22


WR71 / AM71



River

VMi2057 LRV: 22


WR71 / AM71



Mallard

VMi2013P LRV: 13

WR302 / AM302



Minster

VM2018P **LRV: 40**
WR289 / AM265




Arena

VM2019P **LRV: 41**
WR297 / AM20




Bisque - Matches AQI Curlew

VM2021P **LRV: 50**
WR364 / AM335




Sand

VM2051 **LRV: 40**
WR20 / AM20




Tan - Matches AQI Sandpiper

VM2018P **LRV: 41**
WR362 / AM20




Rodeo

VM2020P **LRV: 27**
WR363 / AM265




Bone

VM20215 **LRV: 37**
WR20 / AM20




Biscuit

VM20907 **LRV: 30**
WR146 / AM20




Monument

VM2008P **LRV: 23**
WR305 / AM239




Tundra

VM20910 **LRV: 17**
WR153 / AM239



Savannah

VM2050 **LRV: 19**
WR153 / AM239




Signal

VM2016P **LRV: 13**
WR300 / AM42




Forge

VM2015P **LRV: 9**
WR248 / AM238




Tango

VM2031 **LRV: 14**
WR42 / AM42




Silk

VM2003P **LRV: 10**
WR310 / AM35




Lupin

VM2059 **LRV: 17**
WR286 / AM286



Roof Garden

VM2000P **LRV: 23**
WR262 / AM154



Gecko

VM2002P **LRV: 18**
WR308 / AM308

Typical applications

General purpose

Slip resistance

Static coefficient of friction		ASTM D2047	.78 dry, .80 wet
Ramp test		DIN 51130	R10
TRRL pendulum test		BS 7976	36+

Specifications

Thickness	2.0mm .08"		
Roll dimensions	6'7" x 66' 2.0m x 20m		
Weight	4.79 lbs./yd ² 2.6 kg/m ²		
Wear layer	Altro Walkway 20 2.0mm, homogeneous construction		
Cleaning technology		Altro Easyclean Maxis PUR	
Warranty		10 years	
Static load limit		ASTM F970	1000 psi
Sound insulation		ISO 140-8	20 5dB
Fire and smoke performance		CAN/ULC - S102.2 ASTM E648 ASTM E662	Tested Class I < 450
VOC emissions		CA 01350 FloorScore	Pass Certified
Bio-based content		This product is manufactured with bio-based content.	
Recycled content		VM20 contains 10% per-consumer & 10% post-consumer recycled content.	
Composition	Aluminum trioxide and colored quartz aggregate throughout thickness. Silicon carbide also present on traditional "sparkly" hues. Altro Easyclean Maxis PUR incorporated for exceptional cleanability.		
Backing	Non-woven polyester/cellulose glass fiber reinforcement scrim. Altro XpressLay has embossed PVC backing.		
Installation and maintenance	Altro flooring must be installed by a professional flooring installer that has attended an Altro training clinic. Installation procedures available at altrofloors.com/downloads , training clinic information at altrofloors.com/training . Proper care of Altro flooring is critical. Please consult our cleaning procedures available at altrofloors.com/downloads . Failure to install, heat weld, and/or maintain correctly could void the warranty.		
Staining	Certain chemicals may cause staining of vinyl flooring. Traffic stains may be caused by asphalt and rubber products, like rubber mats. Please conduct stain test before installation.		

Altro, the future is safer with Altro, Altro Walkway 20 and Altro Easyclean Maxis PUR are all trademarks of Altro Limited. Folder content was correct at time of print. Altro reserves the right to change any detail. Please consult your sales representative for the latest product information.
© Copyright Altro USA 2016


LEED facts

LEED v4



This product may help contribute to the following credits:

Walkway 20 total qualifying credits **8**

	Materials and resources Contains recycled content	1
	Materials and resources Rapidly renewable bio-based content	1
	Materials and resources Environmental product declaration (EPD)	1
	Materials and resources Health product declaration (HPD)	1
	Environmental quality Low emitting materials, flooring CA 01350	3
	Environmental quality Low emitting materials, adhesives	1

For our full sustainability story as well as LEED, low-VOC, EPD and HPD certificates visit altrofloors.com/sustainability



Color shown: Biscuit VM20907

