



the future is safer with altro

Altro Whiterock cleaning and maintenance guide

Initial Cleaning

Once all panels and joints are installed, remove the protective film and clean all surfaces down with an antistatic solution, or anti-static wipes. This is required as the panel may have static build up, and any dust in the atmosphere will adhere to the surface of the panel.

Regular Cleaning

- Altro Whiterock can be cleaned with a diluted soap/detergent solution, such Altro Whiterock PVC wall cleaner (for stubborn stains) or AltroClean 44 (degreaser).
- When cleaning the Altro Whiterock surface, we recommend the temperature of water does not exceed 140°F (60°C).
- Pressure cleaning with hot water may be used with the pressure nozzle, a minimum of 2 feet (600mm) away from the surface.
- To reduce the buildup of static, cleaning the panels with an anti-static solution or anti-static wipes is recommended.
- Some cleaning agents may adversely affect Altro Whiterock. See Altro's chemical resistance chart for reactions to common chemicals at www.altro.com.
- Do not use materials containing abrasives or solvents.



P/N: **ALW A859/325**
Altro Whiterock PVC Cleaner



P/N: **ASF 44 Cleaner**
Altro Clean 44 - 5 Liters
1.3 Gallons



P/N: **ALW A809/05**
Whiterock Anti-Static Agent
5 Liters



P/N: **ALW A863**
Altro Whiterock Anti-Static Wipes
80/Unit