



## Altro Wood Acoustic

Realistic wood visuals with enhanced underfoot comfort and sound reduction

















Blchd. Bamboo Acoustic WSMA3797 WR463 / AM392 LRV 42



Farmhouse Oak Acoustic WSMA3781 WR338 / AM27 LRV 38



Castle Oak Acoustic WR335 / AM335



WSMA3798



Antiq. Walnut Acoustic WR341 / AM160





Mellow Maple Acoustic WR352 / AM352





Sovereign Oak Acoustic WR468 / AM62

WSMA37102



## **Altro Wood Acoustic**

Wood-look sheet vinyl with enhanced comfort and sound reduction

Slip resistance				
Static coefficient of friction	.79 <b>D</b> .94 <b>W</b>	ASTM D2047	.79 dry, .94 wet	
Ramp test	$R_{10}$	DIN 51130	R10	
TRRL pendulum test	PTV ≥36	BS 7976	36+	

Specifications				
Thickness	3.9mm			
Roll dimensions	6'7" x 66'   2.0m x 20m			
Weight	5.34 lbs/yd <sup>2</sup>   2.9 kg/m <sup>2</sup>			
Wear layer	.7mm			
Cleaning technology	office EASYCLEAN*	Altro Easyclean		
Warranty	10 year product warranty	10 years		
Static load limit	A	ASTM F970	500 psi	
Sound insulation	(((?)	ISO 140-8	19dB	
		IIC rating	54	
Fire and smoke performance		CAN/ULC - S102.2 ASTM E648 ASTM E662	Tested Class I < 450	
VOC emissions	VOC	CA 01350 FloorScore	Pass Certified	
Bio-based content	bio-based content	Manufactured with 24% rapidly renewable bio-based content.		
Composition	Heterogeneous PVC with glass fiber reinforcement scrim between the film print and backing.  Altro Easyclean incorporated into top layer for exceptional cleanability.			
Backing	Blown PVC backing.			
Installation and maintenance	Altro flooring must be installed by a professional flooring installer that has attended an Altro training clinic. Installation procedures available at altrofloors.com/downloads, training clinic information at altrofloors.com/training. Proper care of Altro flooring is critical. Please consult our cleaning procedures available at altrofloors.com/downloads. Failure to install, heat weld, and/or maintain correctly could void the warranty.			
Staining	Certain chemicals may cause staining of vinyl flooring. Traffic stains may be caused by asphalt and rubber products, like rubber mats. Please conduct stain test before installation.			

**LEED facts** This product may help contribute to the following credits LEED v4 Altro Wood Acoustic Materials and resources 1 Renewable bio-based content Materials and resources 1 Environmental product declaration Materials and resources 1 Health product declaration Environmental quality 3 Low emitting materials, flooring Environmental quality 1 Low emitting materials, adhesives

Discover more of our sustainability story and credentials at altro.com/sustainability

Follow us



© Copyright Altro USA 2017

Altro, Altro Wood Acoustic and Altro Easyclean are all trademarks of Altro Limited. Folder content was correct at time of print. Altro reserves the right to change any detail. Please consult your sales representative for the latest product information.