



Client:

Project:

Type:

Order Code:

Quantity:

AL Fade 6 Pro is simple, fader based wall-mount DMX controller designed for single color or multi-color LED lighting products. It features a six channel DMX output, six user programmable presets (static color or moving sequence), and a master dimmer function. An IR remote control is included for wireless control up to 30'.

SPECIFICATIONS

DMX Output	6 channels
DMX Input	6 channels, overrides dimmer levels for programming
Interface	Dimmable faders and preset buttons
Multiple Locations	Not available for AL Fade 6 Pro
Adjustable Start Address	Available via back panel dip switches
Operating Voltage	12-24VDC, 500mA (power adapter included - 6W, 12VDC, 100-240VAC input)
Mounting	Single gang electrical box (not included)
Finish	White
Material	Aluminum housing, glass panel
Ambient Operating Temperature	32° F to 104° F (0° C to 40° C)
IP Rating	IP20, dry location
Fixture Connectors	Screw terminal block, direct hardwire
Warranty	2 Years, limited
Weight	0.3 lbs (140g)
Dimensions	L: 4.72" W: 2.99" D: 0.6" (120 x 76 x 15.3mm)
Certifications	CE


ORDER CODES

ALF6PU: AL Fade 6 Pro (North American Version)

ALF6PE: AL Fade 6 Pro (European Version)

INCLUDED COMPONENTS

Power Supplies



APS-6-12

Power Supply for AL Fade 6 Pro
100-240VAC, 500mA, 12VDC, 6W
cULus component, CE approved

DIMENSIONS

