

DynaGraze Interior SO

Client:	
Project:	
Туре:	
Order Code:	
Quantity:	



The **DynaGraze Interior SO** is a high power, white LED, indoor linear graze fixture. Available in 1' and 4' sections, it offers smooth linear dimming with ELV and 100-1% with most commercially available TRIAC dimmers . Featuring class-leading output, robust housing, and several color temperature options, it is the perfect option for any structure that calls for indoor linear grazing.


SPECIFICATIONS

Color Temperature	2,700K, 3000K, 3500K, 4000K
Beam Angle	15°, 40°, 15° x 60°, 30° x 60°, 60° (Via LSF Only)
Max Fixture Runs	50' @ 120VAC / 100' @ 240VAC+
Power Consumption	12w (1') / 48w (4'), Optional 5W per foot ASHRAE Compliant
Total Lumens	572 (1') @ 3000k
Efficacy (lm/W)	48 @ 3000K
CRI	85 @ 3000K
Lumen Maintenace	70% @ 50,000 Hours
Finish	Anodized Brushed Aluminum
Housing	Aluminum; Frosted Polycarbonate Lens
Operating Temperature	-4°F to 113°F (-20°C to 45°C)
Operating Voltage	90-135VAC / 200-300VAC
Dimming	TRIAC or ELV
Fixture Connectors	Integral, 3 Pin Male & Female Connector
Rating	IP 20, Dry Location
Warranty	5 Years
Weight	1' 0.7 lbs (0.3 kg) 4' 2.6 lbs (1.2 kg)
Dimensions	W 1.5" x H 2.0" x L 12"/ 48" (39 mm x 52 mm x 305 mm / 1,220 mm)
Certifications	(Ti) CC





DIMENSIONS








DynaGraze Interior SO

Client:	
Project:	
Туре:	
Order Code:	
Quantity:	

ORDER CODES



RELATED COMPONENTS

CA-CAF-03050	Start Cable for DynaGraze Interior 10'
CA-CAL-00305	Link Cable for DynaGraze Interior 1'
CA-CAL-00150	Link Cable for DynaGraze Interior 5'
CA-CAL-00310	Link Cable for DynaGraze Interior 10'
DGDLV12	DynaGraze SO Interior Louver 1'
DGDLV48	DynaGraze SO Interior Louver 4'

WIRING

50' (120V) / 100' (240V+) Maximum in any combination of 1' & 4' sections

