

Flex Drywall Channel



Client:

Project:

Type:

Order Code:

Quantity:




The **Flex Drywall Channel** is a two-piece system, with anodized aluminum channel, designed for clean lines of LED installation in drywall or drywall ceiling. Add the channel with or without a flange to the mounting section for a simple, clean LED strip.

Compatible with:
Flex II Interior
Flex III Interior

Specifications

Length	3.28' (1m), Cut to length as needed
Material	Double Anodized Aluminum, Polycarbonate Lenses
IP Rating	IP22, Dry Location
Area Temperature	32° F - 104° F (0° C - 40° C)
Warranty	3 Years
Mounting	via Surface Spring Accessory
Weight	0.84 lbs. (0.38 kg)
Dimensions	L: 39.3" (1m) W: 2.6" (6.6cm) H: 1.12" (2.84cm)

Dimensions



Flex Drywall Channel

Order Code

FLK DWM: Flex Drywall Mount Extrusion, 1m (3.28')

use in conjunction with one of the two units below:

FLK DWC: Flex Drywall Channel Internal Extrusion, 1m (3.28')

FLK DWF: Flex Drywall Channel Internal Extrusion, with Flange, 1m (3.28')

Related Components

FLK DWM CLIP: Drywall Mounting Clip




FLK DWM EC: Drywall Mount End Cap



FLK DCL: Drywall Clear Lens



FLK DFL: Drywall Frosted Lens



FLK DWC SS: Drywall Channel Surface Spring

