

ACCLAIM LIGHTING

X-PD-150 II

Junction Box

Operation Manual



DESCRIPTIONS:

X-PD-150 II is a junction box with built-in 24VDC/6.5A PSU, features DMX input and power/signal output. It consists of the below versions for user selection:

X-PD-150 II-UL, with UL plug power input and UL socket for power thru, 5-pin power/data socket.

X-PD-150 II-VDE, with VDE plug power input and VDE socket for power thru, 5-pin power/data socket.

X-PD-150 II-BS, with BS plug power input and BS socket for power thru, 5-pin power/data socket.

FEATURES:

- Built-in 24VDC / 6.5A switching power supply unit
- 1 DMX input and 3 Power/data output
- Multiple AC input voltage (selectable)
- 150W (12pcs of X-Panel, 12pcs of X-Curtain 1000, 5pcs of X-Curtain 2000)

TECHNICAL SPECIFICATIONS:

POWER INPUT	110-120VAC(3.2A) / 220-240VAC(1.6A), 50/60Hz.
POWER OUTPUT	+24VDC, 6.5A Max.
INPUT	3-pin VDE/UL/BS plug and XLR male socket
OUTPUT	3pcs 5-pin IP67 water proof power / data socket
FUSE	T3.15A 250V 5x20mm
POWER THROUGH	VDE/UL/BS female socket
POWER SUPPLY	100-240VAC I/P, 24VDC O/P, 150W;
HOUSING	Sheet metal with powder finishing
IP RATING	IP20
CONNECTION	5-pin IP67 waterproof connector
LISTING	CE certified
OPERATION TEMPERATURE	-10 degC to +50 degC
STORAGE TEMPERATURE	-20 degC to +70 degC
DIMENSION	297.5(L) x 154(W) x 75(H)mm
WEIGHT	2.35Kg

PHYSICAL DIMENSIONS:

