## **ONE OR TWO LAMP STRIP (SLIMLINE)**



## 3-9/16" (90mm)

## PRODUCT HIGHLIGHTS

- Premium housing crimped along sides for extra rigidity and straight alignment
- Accepts optional plug-in wiring feature for continuous row installation
- Alignment couplers furnished for continuous row installation
- Channel cover equipped with quarterturn, captive fasteners for easy access to ballast compartment

**CONSTRUCTION** - Fixture housing, lampholder brackets, end sections and channel cover constructed of codegauge, die-formed steel.

ELECTRICAL - All devices UL/CUL listed.
Suitable for damp locations. Damp location emergency pack must be specified separately. Ballasts are energy-saving solid-state electronic. Ballasts and lampholders replaceable without removing from ceiling. Discrete voltage must be specified for emergency pack options when wired with flex.

FINISH - All metal parts painted after fabrication following treatment with phosphate rust inhibitor. Finish coating of housing reflecting surfaces is with white, high reflectance (minimum 92%) polyester powder.

PHOTOMETRICS - Please visit our web site at <a href="https://www.lsi-industries.com">www.lsi-industries.com</a> for detailed photometric data.



ARRA
Funding Compliant

## ORDERING INFORMATION

TYPICAL ORDER EXAMPLE: \$ 2 59 \$\$010 F UE

Prefix	Lamps	Lamp Type	Ballasts	Options	Voltage
S	1 2	T8 Lamps 59 - 59W 96"  T8 H0 Lamps 44 - 44W 48" H0 86 - 86W 96" H0  Note: For tandem configurations suffix number above with "-2"	SSO - T8 Electronic SSOHL- T8 High Ballast Factor SSOHLR- T8 Program Start High Ballast Factor SSO10 - T8 <10% THD Instant Start	F - Fusing EM - Emergency Pack EMDL - Emergency Pack - Damp Location PM - Prewired Plug-in Assembly (specify circuitry.See Options/Accessories Section) CEE - CEE Approved Components installed	120 - 120V 277 - 277V 347 - 347V UE - Universal Electronic (120-277V)

ACCESSORY ORDERING INFORMATION (Accessories are field installed)						
Description	Order Number	Description	Order Number			
Wire Guard - 4 foot (For 8' add "2"WG per fixture)	WG 240	Symmetrical Reflector (specify unit)	F20 2 96			
Clamp Hanger	CH12	Asymmetrical Reflector (specify unit)	AR 2 4			
Chain Hanger Set (36" length)	CHS	(For Symmetrical Reflector use Wire Guard)	IWG F202			



\_\_\_ Fixture Type \_\_\_\_\_\_