PRODUCT HIGHLIGHTS

- Rounded Lens for unique appearance.
- Flexible lens allows for easy access to service lamps or ballast.
- · Available in 4' and 8' housing lengths.
- Ballast cover held in place with quarter turn fasteners for easy access.
- Small size allows for installation in small spaces.

CONSTRUCTION - Fixture housing, lampholder brackets, and sections and reflector constructed of code-gauge dieformed steel.

SHIELDING - Clear Acrylic Lens, .125 thick with 20% DR blend.

ELECTRICAL - All devices UL/CUL listed. Suitable for damp locations. Damp location emergency pack must be specified separately. Ballasts are solid-state electronic. Ballasts and


solid-state electronic. Ballasts and lampholders replaceable without removing from ceiling. Discrete voltage must be specified for emergency pack options when wired with flex.

FINISH - All metal parts painted after fabrication following treatment with phosphate rust inhibitor. Finish coating of housing reflecting surfaces is with white, high reflectance (minimum 92%) polyester powder.

PHOTOMETRICS - Please visit our web site at <u>www.lsi-industries.com</u> for detailed photometric data.



DIMENSIONS







ORDERING INFORMATION

TYPICAL ORDER EXAMPLE: DW 2 32 SSO10 CLR F UE

Prefix	Lamps	Lamp Type	Ballasts	Shielding	Options	Voltage
DW	1 2 3	28 - 28W 45" T5 32 - 32W 48" T8 54 - 54W 45" T5HO Note: For tandem configurations suffix above number with "-2"	SSSR - T5 Programmed Start SS5D - T5 Dimming (specify type) SS5H0 - T5H0 SS0D - T8 Dimming (specify type) SSOL - T8 Low Watt SSOHL- T8 High Ballast Factor SSOHL- T8 Program Start High Ballast Factor SSOR - T8 Programmed Start SSO10 - T8 <10% THD Instant Start (For dual ballasts add "2" Example: SSO2)	WHT - White Acrylic Lens	EM - Emergency Pack EM14 - Emergency Pack - 1400 lumens	120 - 120V 277 - 277V 347 - 347V UE - Universal Electronic (120-277V)