

CARE & MAINTENANCE ■

KI Stack Seating

May, 2016

Care and maintenance instructions for the following KI stack chairs:

<i>Dōni</i>	<i>Perry</i>	<i>Torsion</i>
<i>Dorsal</i>	<i>Piretti Stack</i>	<i>Torsion Air</i>
<i>Grazie</i>	<i>Rapture</i>	<i>Torsion on the Go!</i>
<i>Maestro</i>	<i>Strive</i>	<i>Versa</i>
<i>Matrix</i>		



GENERAL CLEANING

KI stack seating requires minimal maintenance. It requires no more care than any other fine seating. Proper care and careful use are the best methods of maintaining the appearance, finish, and function of any product. Periodic light cleaning is all that is necessary. Stains and spots may require more cleaning attention (see below).

PLASTIC/POLY PARTS

Sunnyside Plastic Cleaner is ideal for light cleaning. Buffing with this product restores luster to smooth services. Its anti-static properties help repel dust and dirt. High quality wax, such as Johnson's "Glo-Coat" or "Simonize", restores luster and protects the finish. Follow container directions and apply with a soft cloth and buff thoroughly. For chewing gum and similar stubborn spots, remove with cigarette lighter fluid. Wipe dry immediately.

POWDER-COATED FRAMES

It is recommended that frames be kept dry and away from water, rain, ice, snow, and salt. To clean frames, use warm water and mild soap, then dry thoroughly. Wax or furniture polish may be applied after cleaning.

FABRIC UPHOLSTERY

Be sure to vacuum upholstery frequently and thoroughly. Use a foam-type cleaner such as Johnson Wax "Glory" or Earl Grissmer Co. "Blue Lustre" for general cleaning. For more stubborn spots and stains, use Texie Chemical Co's "K2r". Always follow the manufacturer's directions. Do not use dry-cleaning agents on upholstery.

ARMS

If your chair has arms, the fasteners attaching the arms to the underside of the seat should be periodically tightened.

LAMINATE TABLET ARMS

To clean the laminate, use a mild solution of water and detergent on a soft cloth. (Pine cleaner and warm water works well.) Wipe clean with a dry cloth. Do not soak product. Some stains such as grape juice may be removed by wetting the surface and sprinkling with baking soda, then wiping clean with a damp cloth. (Do not allow the baking soda to remain more than two minutes.) As always, thoroughly dry the surface with a dry cloth. Never use harsh abrasives such as Comet cleanser, scrub pads, etc. to clean the surface. The exposed plywood edge is finished in Tung oil. Avoid contact with solvents. Furniture polish may be applied to maintain a bright attractive finish on the entire laminate surface.

CAUTION: Do not use a coarse cloth when applying cleaning agents to smooth surfaces.

