

SPECIFICATIONS - ASSURANCE II

	CONSTRUCTION	Slip-Resistance Sheet
	AVAILABLE SIZES	Available in 6' (1.83 m)
	OVERALL THICKNESS	.080" (2.03 mm)
	WEIGHT PER SQUARE YARD	6.5 lbs/yd ² (3.53 kg/m ²). For packing weight, it includes interleaf of 0.40 lbs. per sq. yd.(0.22 kg/m ²)
	SQUARE YARD PER ROLL (MIN-MAX)	30 - 68 sq. yds. (25.1 - 56.9 sq. m.)
	3RD PARTY CERTIFICATIONS	FloorScore
	WARRANTY	This product is backed by our Limited 5 year Commercial Warranty and Limited 5 year Quantum Guard HP Wear Warranty.
	LEED	Mannington Commercial products contribute to multiple LEED credits.
STATIC LOAD LIMIT		750 PSI
SPECIFICATION (ASTM F-1913)		Exceeds
HUD/FHA REQUIREMENTS		Meets or exceeds
ADA		Meets or exceeds ADA Requirements
COEFFICIENT OF FRICTION		COF ≥ 0.5 Leather; 0.6 Rubber
FLOORING RADIANT PANEL TEST (ASTM-E-648)		≥ .45 watts/cm ² , Passes - Class 1
N.B.S. SMOKE CHAMBER TEST (ASTM-E-662)		< 450, Passes
INSTALLATION ADHESIVE		V-82 / Full Spread Porous Subfloor, V-95 / Full Spread Non-Porous Subfloor Note: Must use V-95 Adhesive under hospital beds and heavy rolling loads or where high performance is needed. M-Guard V-88/ Full Spread Transitional Pressure Sensitive/ Porous & Non-Porous or High Moisture Subfloors
SEAM METHOD		Mannington Commercial Solid Weld Rods. Heat welding is the recommended procedure for healthcare and high traffic applications.

Floor designs copyrighted by Mannington Mills, Inc. 2014. Quantum Guard® HP patents 6,218,001 and 6,291,078 and 7,384,697.

For complete specifications, visit www.manningtoncommercial.com.



MANNINGTON
COMMERCIAL