

Morikato Wood



Drawing inspiration from the Japanese word for “forest,” Morikato Wood enhanced resilient tile features hardwood visuals with distressed, reclaimed style. Aesthetics include charred wood, cerused grains and worn cross hatching, available in a variety of species.

Style Names	Morikato Wood
Style Numbers	C0016
Brand	Mohawk Group – Hard Surface
Product Type	Enhanced Resilient Tile



DESIGN

Overall Gauge	.10" (2.5mm)
Wear Layer	20 mil (0.5mm)
Finish	M-Force™ Enhanced Urethane
Colors Available	10 Colors
Size	7" W x 48" L
Packaging	37.28 sf/ctn; 16 pcs/ctn; 33.09 lbs/ctn
Installation	Glue Down
Required Adhesive	MS160 Spray Adhesive, M95.0 Resilient Flooring Adhesive, M700 Pressure Sensitive Adhesive
Optional Underlayment	Mohawk AccuSound™

Features

- Wide range of wood visuals accommodates a variety of design schemes
- Oversized 7" x 48" planks install over large areas quickly
- 2.5mm overall thickness and 20 mil commercial wear layer for superior durability
- M-Force™ Enhanced Urethane finish for stain and wear resistance
- Installs over slabs up to 95% RH using Mohawk M95.0 or MS160 adhesives
- Contains a minimum of 8% bio-based renewable resource content by total product weight
- Avoids harmful phthalates without sacrificing performance, quality or ease of maintenance by substituting a bio-based, rapidly renewable plasticizer



PERFORMANCE

Construction	Commercial Grade Enhanced Resilient Tile
Classification	ASTM F1700 - Class III, Type A - Smooth, Type B - Embossed
Squareness	ASTM F2055 - Passes - 0.10" max
Size and Tolerance	ASTM F2055 - Passes - ± 0.016 "/linear foot
Thickness	ASTM F386 - Passes - Nominal ± 0.005 "
Flexibility	ASTM F137 - Passes - 1" mandrel
Dimensional Stability	ASTM F2199 - Passes - ≤ 0.024 "/linear foot
Static Load Limit	ASTM F970 - Passes, modified at 1500 psi
Residual Indentation	ASTM F1914 - Passes - Average less than 8%
Slip Resistance	ASTM D2047 - Passes - > 0.6 Wet, 0.6 Dry
Resistance to Chemicals	ASTM F925 - Passes - No change or Slight Change
Resistance to Light	ASTM F1515 - Passes - $\Delta E \leq 8$
Resistance to Heat	ASTM F1514 - Passes - $\Delta E \leq 8$
Critical Radiant Flux	ASTM E648 - Passes - ≥ 0.45 watts/cm2, Class 1
Smoke Density	ASTM E662 Passes



SUSTAINABILITY

Certification	FloorScore® Certified
Bio-Based Content	Contains a minimum of 8% bio-based renewable resource content by total product weight
Phthalate-Free Composition	Avoids harmful phthalates without sacrificing performance, quality or ease of maintenance by substituting a bio-based, rapidly renewable plasticizer.



SERVICE

Warranty	Limited 10 Year Commercial Warranty
----------	-------------------------------------

Morikato Wood

Colorways



222 Japanese Maple



231 Teak



321 Charred Ash



811 Kabuki



828 Parchment



873 Tambur



883 Otter



911 Ukiyo



933 Katana



963 Smoke

High Performance Enhanced Resilient Tile

Construction: Morikato Wood features a 20 mil commercial wear layer, M-Force™ Enhanced Urethane and polish-optional finish for cost-effective maintenance. Morikato Wood carries a 10 year commercial warranty.

M-Force™ Enhanced Urethane Finish
Heavy Commercial Wear Layer
Decorative Print Layer
Commercial Base
Stabilizing Backing Layer

