

# SENSE

## Aqua Viva

Modular Tile

**Construction**

Tufted, Textured Loop

**Tile Size**

1 m x 1 m (39.4" x 39.4")

**Yarn Type**

Antron Legacy® Nylon Type 6,6

**Stain Repel / Stain Resist / Soil Release**

StainSmart®

**Bleach Resistance**

ColorSeal®

**Antimicrobial**

AlphaSan® AF Built-In Protection†

**Dye Method**

DCP (Digital Color Placement)

**Tufted Face Weight**

20 oz/yd² (678 g/m²)

**Gauge**

1/13

**Stitches Per Inch**

11.2

**Tufts**

146/in² (2,255/100 cm²)

**Finished Pile Height**

0.14" (3.56 mm)

**Finished Pile Thickness**

0.09" (2.29 mm)

**Average Density (Finished)**

7,400

**Standard Backing**PVC-Free Underscore™ ES Cushion  
Available with TractionBack®**Recycled Content by Total Weight**ES Backing: 37.1% Pre-Consumer,  
0.0% Post-Consumer  
ESP Backing: 27.0% Pre-Consumer,  
10.1% Post-Consumer**Nominal Total Thickness**

0.32" (8.1 mm)

**Nominal Total Weight**

95 oz/yd² (3,204 g/m²)

**Flammability (Radiant Panel****ASTM-E-648)**

≥ 0.45 (Class I)

**Smoke Density (NFPA-258-T or****ASTM-E-662)**

≤ 450

**Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859**

Self-Extinguishing

**Lightfastness (AATCC 16E)**

≥ 4.0 at 80 Hours

**Crocking (AATCC 165)**

≥ 4.0 Wet or Dry

**Static Electricity (AATCC-134) 20% R.H., 70° F.**

≤ 3.5 KV, Permanent Conductive Fiber

**Texture Appearance Retention Rating (TARR)**

Severe Traffic End-Use Applications

**Recommended Maintenance**MilliCare® Textile and Carpet Care  
Service Network**Indoor Air Quality—CRI Green Label Plus™**

GLP0793, Carpet Category 5Y

**Recommended Installation Method(s)**

Monolithic

**WARRANTIES**

Lifetime Antimicrobial Protection (AlphaSan®)

Lifetime Face Fiber Wear

Lifetime Antistatic

Lifetime Floor Compatibility

Lifetime Color Pattern Permanency

Lifetime Floor Release

Lifetime Cushion Resiliency

Lifetime Moisture Resistance

Lifetime Delamination of Backing

Lifetime Staining/Soiling (StainSmart®)

Lifetime Dimensional Stability

Lifetime Tuft Bind

Lifetime Edge Ravel

Flammability



This cushion-back carpet tile product is covered by one or more patents, published applications and/or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.