Milliken

SENSE

Awaken

Modular Tile

Construction

Tufted, Textured Loop

Tile Size

1 m x 1 m (39.4" x 39.4")

Yarn Type

Antron Legacy® Nylon Type 6,6

Stain Repel / Stain Resist / Soil

Release

StainSmart®

Bleach Resistance

ColorSeal®

Antimicrobial

AlphaSan® AF Built-In Protection†

Dye Method

DCP (Digital Color Placement)

Tufted Face Weight

 $20 \text{ oz/yd}^2 (678 \text{ g/m}^2)$

Gauge

1/13

Stitches Per Inch

11.2

Tufts

146/in² (2,255/100 cm²)

Finished Pile Height

0.14" (3.56 mm)

Finished Pile Thickness

0.09" (2.29 mm)

Average Density (Finished)

7,400

Standard Backing

 $\begin{array}{l} {\sf PVC\text{-}Free\ Underscore^{\tiny\mathsf{TM}}\ ES\ Cushion} \\ {\sf Available\ with\ TractionBack}^{\tiny \circledcirc} \end{array}$

Recycled Content by Total Weight

ES Backing: 37.1% Pre-Consumer,

0.0% Post-Consumer

ESP Backing: 27.0% Pre-Consumer,

10.1% Post-Consumer

Nominal Total Thickness

0.32" (8.1 mm)

Nominal Total Weight

 $95 \text{ oz/yd}^2 (3,204 \text{ g/m}^2)$

Flammability (Radiant Panel

ASTM-E-648)

≥ 0.45 (Class I)

Smoke Density (NFPA-258-T or

ASTM-E-662)

≤ 450

Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859

Self-Extinguishing

Lightfastness (AATCC 16E)

≥ 4.0 at 80 Hours

Crocking (AATCC 165)

 \geq 4.0 Wet or Dry

Static Electricity (AATCC-134) 20%

R.H.,70° F.

≤ 3.5 KV, Permanent Conductive Fiber

Texture Appearance Retention Rating (TARR)

Severe Traffic End-Use Applications

Recommended Maintenance

MilliCare® Textile and Carpet Care

Service Network

Indoor Air Quality—CRI Green Label

Plus™

GLP0793, Carpet Category 5Y

Recommended Installation Method(s)

Monolithic

WARRANTIES

Lifetime Antimicrobial Protection (AlphaSan®) Lifetime Face Fiber Wear Lifetime Antistatic Lifetime Floor Compatibility Lifetime Color Pattern Permanency Lifetime Floor Release
Lifetime Cushion Resiliency
Lifetime Moisture Resistance
Lifetime Delamination of Backing
Lifetime Staining/Soiling (StainSmart®)

Lifetime Dimensional Stability Lifetime Tuft Bind Lifetime Edge Ravel Flammability









This cushion-back carpet tile product is covered by one or more patents, published applications and/ or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.