

LUXURY VINYL TILE

Abstract / Stone / Wood

Construction	High Performance Luxury Vinyl Tile
Finish	Adámas™ UV-Cured Polyurethane
Wear Layer Thickness	0,7 mm
Overall Thickness	2.5 mm
Edge Profile	Micro Bevel
Product Weight	4000 g/m ²

PERFORMANCE

Critical Radiant Flux (ASTM E648-10)	Pass - Class 1
Flammability (EN 13501-1.2002)	Class Bfl-s1
Use Classification (EN 10852.2012)	Class 34 Very Heavy Commercial Use, Class 43 Heavy-Light Industrial Use
Castor Chair (ISO 4918: 2009)	Pass
Determination of Anti-slip (DIN 51130)	R10
Flexibility (ISO 242344)	Pass
Heat Stability by Colour Change (ASTM F1514-03)	Pass
Light Stability (ASTM F1515 - 03)	Pass
Static Electrical Propensity (ISO 6356)	Pass ≤2.0 KV
Dimensional Stability (EN ISO 23999)	Pass
Resistance to Chemicals (ASTM F925-13)	Pass
Static Load Limit (ASTM F970-07)	Pass

INSTALLATION

Glue down

WARRANTIES

12 year wear warranty

CERTIFICATIONS

INSTALLATION

Charlotte 	Charlotte 	PowerGrid 2.5 / Serpeggiante / Stone
Monolithic	Quarter Turn	Half Drop

CE MARKING

15 DOP-1004-05 EN 14041:2004 EN 649	Bfl-s1	E1 HCHO		DS		

INSTALLATION

Aged Oak / Eero 2.5 / Eucalyptus / Saligna / Fine Line / Kokutan / Laurel Oak / Rosewood / Rustic Pine 	Aged Oak / Eucalyptus / Saligna / Fine Line / Kokutan / Laurel Oak / Rosewood / Rustic Pine
Ashlar Random	Herringbone