


FEATURES

- Dual 120/277 VAC 60Hz input
- Two-step charger
- Line-latched transfer circuit, brownout protection
- "Self-Check" diagnostics
- Sealed, maintenance-free, long-life lead calcium battery
- White powder-coat on 20-gauge cold-rolled steel
- Universal mounting knockouts provided

Compliances may not apply to all product configurations. Please consult the product spec sheet for compliance details.

COMPLIANCES: UL924 Listed; NFPA 101 Compliant, NYC Code Compliant



**A COMMERCIAL
EMERGENCY
LIGHT**

ORDERING INFORMATION - NEW YORK CITY

Family	Capacity in Watts (Hours)				Number of Heads	Watts per Head	Max Remote Heads	Replacement Lamp	Dimensions (mm)				Shipping Weight
	1.5	2	3	4					A	B	C	D	
6 VOLT													
6ACNY1	27	–	–	–	2	12	–	6RW12	14" (355mm)	10" (254mm)	2-5/8" (67mm)	9" (229mm)	13
6ACNY4	54	44	–	–	2	12	2	6RW12	14" (355mm)	13" (330mm)	2-5/8" (67mm)	9" (229mm)	19
6ACNY5	100	75	50	–	2	12	6	6RW12	14" (355mm)	13" (330mm)	4-1/8" (165mm)	9" (229mm)	22
6ACNY5-3	100	75	50	–	3	12	5	6RW12	14" (355mm)	13" (330mm)	4-1/8" (165mm)	9" (229mm)	23
12 VOLT													
12ACNY2	27	–	–	–	2	12	–	12RW12	14" (355mm)	10" (254mm)	2-5/8" (67mm)	9" (229mm)	14
12ACNY3-3	36	–	–	–	3	12	–	12RW12	14" (355mm)	13" (330mm)	2-5/8" (67mm)	9" (229mm)	17
12ACNY4	54	44	–	–	2	12	2	12RW12	14" (355mm)	13" (330mm)	2-5/8" (67mm)	9" (229mm)	19
12ACNY4-3	54	–	–	–	3	12	1	12RW12	14" (355mm)	13" (330mm)	2-5/8" (67mm)	9" (229mm)	20
12ACNY5	100	75	50	45	2	12	6	12RW12	14" (355mm)	13" (330mm)	4-1/8" (165mm)	9" (229mm)	22
12ACNY5-3	100	–	–	–	3	12	5	12RW12	14" (355mm)	13" (330mm)	4-1/8" (165mm)	9" (229mm)	23

ORDERING INFORMATION - NATIONAL

Family	Capacity in Watts (Hours)				Number of Heads	Watts per Head	Max Remote Heads	Replacement Lamp	Dimensions (mm)				Shipping Weight
	1.5	2	3	4					A	B	C	D	
6 VOLT													
6AC27	27	22	18	–	2	9	–	6RW9	14" (355mm)	10" (254mm)	2-5/8" (67mm)	9" (229mm)	13
6AC54	54	44	36	–	2	9	4	6RW9	14" (355mm)	13" (330mm)	2-5/8" (67mm)	9" (229mm)	19
6AC100	100	75	50	45	2	9	9	6RW9	14" (355mm)	13" (330mm)	4-1/8" (165mm)	9" (229mm)	22
12 VOLT													
12AC54	54	44	36	–	2	9	4	12RW9	14" (355mm)	13" (330mm)	2-5/8" (67mm)	9" (229mm)	19
12AC100	100	75	50	45	2	9	4	12RW9	14" (355mm)	13" (330mm)	4-1/8" (165mm)	9" (229mm)	22

OPTIONS AND ACCESSORIES

Options: Add to catalog number Description	Code	Accessories: Add to catalog number Description	Code
No Heads	0	Cord Sets	
One Head	1	120 Volt	3 CP
Three Heads	3	277 Volt (specify male plug type)	3 OP
Voltmeter (1)	V	Mounting Bracket (specify model to be used with)	MBI
Ammeter (1)	A		
Time Delay	TD	Mounting Shelf (specify model to be used with)	MS
Non Standard Voltages (consult factory)			
New York City Approved	NY	Wire Guards (consult factory)	

HALOGEN LAMP OPTIONS ⁽²⁾

⁽¹⁾Only available with OS Head

Unit	Watt Lamp Only	Replacement Lamp Number
6 Volt (all units)	12	6 HB 12*
12 Volt (all units)	12	12 HB 12*

Remote Fixtures (to order see remote fixtures section)

Notes: N.Y.B.S.A. Calendar (approval) #34013.

(1) Units may NOT be equipped with a voltmeter and ammeter at the same time.

(2) When using halogen lamps, total connected lamp load must be at least 80% of 90 min. rating, or premature lamp failure may occur.

Specifications and dimensions subject to change without notice. Consult your Cooper Lighting Representative or visit www.cooperlighting.com for available options, accessories and ordering information.