

**FEATURES**

- Dual 120/277 VAC, 60Hz input
- Solid-state charger and transfer circuitry
- Two-step charger
- Circuit is battery short circuit and reverse polarity protected
- Brownout protection, low-voltage disconnect
- 6 or 12 Volt sealed, nickel cadmium battery
- Steel units fabricated of 18-gauge steel
- Durable, white powder-coat standard finish

Compliances may not apply to all product configurations. Please consult the product spec sheet for compliance details.

**COMPLIANCES:** UL924 Listed; NFPA 101 Compliant, NYC Code Compliant



**ST RECESSED  
EMERGENCY  
LIGHT**

**ORDERING INFORMATION - NEW YORK CITY / NATIONAL**

Family	Capacity in Watts (Hours)				Number of Heads	Watts per Head	Lamp Type	Replacement Lamp
	1.5	2	3	4				
<b>6 VOLT</b>								
<b>6ST1</b>	27	22	18	–	2	9	Incandescent	6RW9
<b>6ST4</b>	54	44	36	–	2	9	Incandescent	6RW9
<b>6ST5</b>	100	75	50	45	2	9	Incandescent	6RW9
<b>12 VOLT</b>								
<b>12ST1</b>	27	22	18	–	2	12	Incandescent	12RW12
<b>12ST4</b>	54	44	36	–	2	12	Incandescent	12RW12

**OPTIONS AND ACCESSORIES**

Options: Add to catalog number Description	Code	Accessories: Add to catalog number Description	Code
No Heads	0	Cord Sets	
One Head	1	120 Volt	3 CP
Three Heads	3	277 Volt (specify male plug type)	0 CP
Four Heads	4		
Voltmeter (1)	V		
Time Delay	TD		
Nickel Cadmium Battery	NC		
New York City Approved	NY		

**HALOGEN LAMP OPTIONS <sup>(1)</sup>**

\*Only available with OS Head

Unit	Watt Lamp Only	Replacement Lamp Number
6 Volt (all units)	12	6 HB 12*
12 Volt (all units)	12	12 HB 12*

Notes: N.Y.B.S.A. Calendar (approval) #34013.

(1) When using halogen lamps, total connected lamp load must be at least 80% of 90 min. rating, or premature lamp failure may occur.

