

LED Rated Dimmers

D010TE 4500 Lumen

| Dimmer Make | Dimmer Series | Dimmer Model # | Dimmer Rating | Minimum Luminaires (per circuit) | Maximum Recommended Luminaires (per circuit) | Max Dimming percentage (%) | Min Dimming percentage (%) | Start Time |
|-------------|---------------|----------------|------------------------------------|----------------------------------|--|----------------------------|----------------------------|------------|
| Lutron | Diva | DVCL-153P | Triac(INC/HAL/CFL/LED) | 1 | 7 | 98% | 16% | >1 sec |
| Lutron | Maestro | MACL-153M | Triac (INC/CFL/LED) | 1 | 7 | 96% | 7% | >1 sec |
| Leviton | Decora | IPL06-10Z | Triac (INC/LED/CFL) | 1 | 7 | 98% | 6% | >1 sec |
| Leviton | Decora | 6674 | Triac (INC/LED/CFL) | 1 | 7 | 98% | 7% | >1 sec |
| CWD | Accell | AAL06P | Triac(INC/HAL/FLR/MLV/ELV/CFL/LED) | 1 | 13 | 98% | 6% | ≥1 sec |
| CWD | SKYE | SAL06P | Triac(INC/HAL/FLR/MLV/ELV/CFL/LED) | 1 | 13 | 99% | 9% | ≥1 sec |
| CWD | Devine | DAL06P | Triac(INC/HAL/FLR/MLV/ELV/CFL/LED) | 1 | 13 | 99% | 3% | >1 sec |
| CWD | SKYE | SLC03PC-PTA | Triac (INC/HAL/CFL/LED) | 1 | 13 | 99% | 3% | ≥1 sec |
| CWD | Devine | DLC03P | Triac (INC/HAL/CFL/LED) | 1 | 13 | 98% | 5% | >1 sec |

D010TE 5500 Lumen

| Dimmer Make | Dimmer Series | Dimmer Model # | Dimmer Rating | Minimum Luminaires (per circuit) | Maximum Recommended Luminaires (per circuit) | Max Dimming percentage (%) | Min Dimming percentage (%) | Start Time |
|-------------|---------------|----------------|------------------------------------|----------------------------------|--|----------------------------|----------------------------|------------|
| CWD | Devine | DLC03P | Triac (INC/HAL/CFL/LED) | 1 | 17 | 97% | 4% | >1 sec |
| Lutron | Diva | DVCL-153P | Triac(INC/HAL/CFL/LED) | 1 | 17 | 96% | 3% | >1 sec |
| CWD | Skye | SLC03PC-PTA | Triac (INC/HAL/CFL/LED) | 1 | 17 | 97% | 3% | >1 sec |
| CWD | Devine | DAL06P | Triac(INC/HAL/FLR/MLV/ELV/CFL/LED) | 1 | 17 | 99% | 14% | ≥1 sec |

LED Rated Dimmers

D010TE 7000 Lumen

| Dimmer Make | Dimmer Series | Dimmer Model # | Dimmer Rating | Minimum Luminaires (per circuit) | Maximum Recommended Luminaires (per circuit) | Max Dimming percentage (%) | Min Dimming percentage (%) | Start Time |
|-------------|---------------|----------------|------------------------------------|----------------------------------|--|----------------------------|----------------------------|------------|
| CWD | Devine | DLC03P | Triac (INC/HAL/CFL/LED) | 1 | 6 | 97% | 4% | >1 sec |
| Lutron | Diva | DVCL-153P | Triac(INC/HAL/CFL/LED) | 1 | 13 | 96% | 3% | >1 sec |
| CWD | Skye | SLC03PC-PTA | Triac (INC/HAL/CFL/LED) | 1 | 13 | 97% | 3% | >1 sec |
| CWD | Devine | DAL06P | Triac(INC/HAL/FLR/MLV/ELV/CFL/LED) | 1 | 13 | 98% | 12% | ≥1 sec |

D010TE 8000 Lumen

| Dimmer Make | Dimmer Series | Dimmer Model # | Dimmer Rating | Minimum Luminaires (per circuit) | Maximum Recommended Luminaires (per circuit) | Max Dimming percentage (%) | Min Dimming percentage (%) | Start Time |
|-------------|---------------|----------------|-----------------------------|----------------------------------|--|----------------------------|----------------------------|------------|
| Lutron | Diva | DVCL-153P | INC/HAL/CFL/LED | 1 | 3 | 97% | 5% | ≥1 sec |
| Lutron | Maestro | MACL-153M | INC/CFL/LED | 1 | 3 | 97% | 10% | ≥1 sec |
| Leviton | Decora | IPL06-10Z | INC/LED/CFL | 1 | 3 | 97% | 10% | ≥1 sec |
| Leviton | Decora | 6674 | INC/LED/CFL | 1 | 3 | 97% | 14% | ≥1 sec |
| CWD | Accell | AAL06P | INC/HAL/FLR/MLV/ELV/CFL/LED | 1 | 6 | 97% | 4% | ≥1 sec |
| CWD | SKYE | SAL06P | INC/HAL/FLR/MLV/ELV/CFL/LED | 1 | 6 | 98% | 14% | ≥1 sec |
| CWD | SKYE | SLC03PC-PTA | INC/HAL/CFL/LED | 1 | 6 | 97% | 4% | ≥1 sec |
| CWD | Devine | DLC03P | INC/HAL/CFL/LED | 1 | 6 | 98% | 6% | ≥1 sec |

D010TE 9000 Lumen

| Dimmer Make | Dimmer Series | Dimmer Model # | Dimmer Rating | Minimum Luminaires (per circuit) | Maximum Recommended Luminaires (per circuit) | Max Dimming percentage (%) | Min Dimming percentage (%) | Start Time |
|-------------|---------------|----------------|------------------------------------|----------------------------------|--|----------------------------|----------------------------|-----------------------|
| Lutron | Diva | DVCL-153P | Triac(INC/HAL/CFL/LED) | 1 | 6 | 97% | 1% | ≥1 sec |
| Lutron | Maestro | MACL-153-M | Triac (INC/HAL/CFL/LED) | 1 | 1 | 95% | 1% | >1 sec ^{2,4} |
| CWD | Devine | DAL06P | Triac(INC/HAL/FLR/MLV/ELV/CFL/LED) | 1 | 3 | 99% | 1% | ≥1 sec ⁴ |
| CWD | Toggle | TAL06P | Triac (INC/HAL/MLV/ELV/CFL/LED) | 1 | 3 | 99% | 9% | ≥1 sec ⁴ |
| CWD | Skye | SAL06P | Triac(INC/HAL/FLR/MLV/ELV/CFL/LED) | 1 | 3 | 98% | 9% | ≥1 sec ⁴ |
| CWD | Skye | SLC06P | Triac(INC/HAL/LED/CFL) | 1 | 0 | 98% | 1% | >1 sec ⁴ |

LED Rated Dimmers

D010TR 4500 Lumen

| Dimmer Make | Dimmer Series | Dimmer Model # | Dimmer Rating | Minimum Luminaires (per circuit) | Maximum Recommended Luminaires (per circuit) | Max Dimming percentage (%) | Min Dimming percentage (%) | Start Time |
|-------------|---------------|----------------|------------------------------------|----------------------------------|--|----------------------------|----------------------------|---------------------|
| Lutron | Diva | DVCL-153P | Triac(INC/HAL/CFL/LED) | 1 | 11 | 100% | 2% | >1 sec ⁴ |
| Lutron | Maestro | MACL-153-M | Triac (INC/HAL/CFL/LED) | 1 | 2 | 98% | 2% | >1 sec ⁴ |
| CWD | Devine | DAL06P | Triac(INC/HAL/FLR/MLV/ELV/CFL/LED) | 1 | 5 | 100% | 3% | ≥1 sec ⁴ |
| CWD | Toggle | TAL06P | Triac (INC/HAL/MLV/ELV/CFL/LED) | 1 | 5 | 100% | 2% | ≥1 sec ⁴ |
| CWD | Skye | SAL06P | Triac(INC/HAL/FLR/MLV/ELV/CFL/LED) | 1 | 5 | 100% | 2% | ≥1 sec ⁴ |
| CWD | Skye | SLC03P | Triac (INC/HAL/CFL/LED) | 1 | 5 | 100% | 2% | >1 sec ⁴ |
| CWD | Devine | DLC03P | Triac (INC/HAL/CFL/LED) | 1 | 5 | 100% | 2% | >1 sec ⁴ |
| CWD | Smart | AAL06 | Triac(INC/HAL/FLR/MLV/ELV/CFL/LED) | 1 | 5 | 100% | 1% | >1 sec ⁴ |
| Leviton | SureSlide | 6674 | Triac (INC/LED/CFL) | 1 | 2 | 100% | 2% | >1 sec ⁴ |
| Leviton | Illumatech | IPL06 | Triac (INC/LED/CFL) | 1 | 2 | 99% | 2% | >1 sec ⁴ |

D010TR 5500 Lumen

| Dimmer Make | Dimmer Series | Dimmer Model # | Dimmer Rating | Minimum Luminaires (per circuit) | Maximum Recommended Luminaires (per circuit) | Max Dimming percentage (%) | Min Dimming percentage (%) | Start Time |
|-------------|---------------|----------------|------------------------------------|----------------------------------|--|----------------------------|----------------------------|------------|
| CWD | Devine | DLC03P | Triac (INC/HAL/CFL/LED) | 1 | 8 | 99% | 3% | ≥1 sec |
| Lutron | Diva | DVCL-153P | Triac(INC/HAL/CFL/LED) | 1 | 8 | 98% | 2% | ≥1 sec |
| CWD | Skye | SLC03PC-PTA | Triac (INC/HAL/CFL/LED) | 1 | 8 | 99% | 4% | ≥1 sec |
| CWD | Devine | DAL06P | Triac(INC/HAL/FLR/MLV/ELV/CFL/LED) | 1 | 8 | 99% | 5% | ≥1 sec |
| CWD | Skye | SAL06P | Triac(INC/HAL/FLR/MLV/ELV/CFL/LED) | 1 | 8 | 99% | 6% | ≥1 sec |
| CWD | Aspire | AAL06 | Triac(INC/HAL/FLR/MLV/ELV/CFL/LED) | 1 | 8 | 99% | 2% | ≥1 sec |

LED Rated Dimmers

D010TR 7000 Lumen

| Dimmer Make | Dimmer Series | Dimmer Model # | Dimmer Rating | Minimum Luminaires (per circuit) | Maximum Recommended Luminaires (per circuit) | Max Dimming percentage (%) | Min Dimming percentage (%) | Start Time |
|-------------|---------------|----------------|------------------------------------|----------------------------------|--|----------------------------|----------------------------|---------------------|
| Lutron | Diva | DVCL-153P | Triac(INC/HAL/CFL/LED) | 1 | 6 | 100% | 2% | >1 sec ⁴ |
| Lutron | Maestro | MACL-153-M | Triac (INC/HAL/CFL/LED) | 1 | 6 | 99% | 2% | >1 sec ⁴ |
| CWD | Devine | DAL06P | Triac(INC/HAL/FLR/MLV/ELV/CFL/LED) | 1 | 6 | 100% | 2% | ≥1 sec ⁴ |
| CWD | Toggle | TAL06P | Triac (INC/HAL/MLV/ELV/CFL/LED) | 1 | 6 | 100% | 5% | ≥1 sec ⁴ |
| CWD | Skye | SAL06P | Triac(INC/HAL/FLR/MLV/ELV/CFL/LED) | 1 | 6 | 100% | 5% | ≥1 sec ⁴ |
| CWD | Skye | SLC03P | Triac (INC/HAL/CFL/LED) | 1 | 3 | 100% | 2% | >1 sec ⁴ |
| CWD | Devine | DLC03P | Triac (INC/HAL/CFL/LED) | 1 | 3 | 100% | 2% | >1 sec ⁴ |
| CWD | Smart | AAL06 | Triac(INC/HAL/FLR/MLV/ELV/CFL/LED) | 1 | 6 | 99% | 2% | ≥1 sec ⁴ |
| Leviton | SureSlide | 6674 | Triac (INC/LED/CFL) | 1 | 6 | 99% | 2% | >1 sec ⁴ |
| Leviton | Illumatech | IPL06 | Triac (INC/LED/CFL) | 1 | 6 | 100% | 3% | >1 sec ⁴ |

D010TR 8000 Lumen

| Dimmer Make | Dimmer Series | Dimmer Model # | Dimmer Rating | Minimum Luminaires (per circuit) | Maximum Recommended Luminaires (per circuit) | Max Dimming percentage (%) | Min Dimming percentage (%) | Start Time |
|-------------|---------------|----------------|-------------------------|----------------------------------|--|----------------------------|----------------------------|------------|
| CWD | Devine | DLC03P | Triac (INC/HAL/CFL/LED) | 1 | 5 | 100% | 2% | ≥1 sec |
| Lutron | Diva | DVCL-153P | Triac(INC/HAL/CFL/LED) | 1 | 5 | 100% | 4% | ≥1 sec |
| CWD | Skye | SLC03PC-PTA | Triac (INC/HAL/CFL/LED) | 1 | 5 | 100% | 3% | ≥1 sec |

¹ Slight flash at startup

² Slight issues with dimming smoothness

³ Slight flicker at low light

⁴ Audible noise present

CWD = Eaton's Cooper Wiring Devices Business

Dimmer Rating - Load Type

INC = Incandescent

HAL = Halogen

FLR = Fluorescent

MLV = Magnetic Low Voltage

ELV = Electric Low Voltage

CFL = Compact Fluorescent

LED = Light Emitting Diode

Cooper Lighting

by **EATON**

LED Rated Dimmers

D010TE 0-10V 4500 Lumen

| Dimmer Make | Dimmer Series | Dimmer Model # | Dimmer Rating | Minimum Luminaires (per circuit) | Maximum Recommended Luminaires (per circuit) | Max Dimming percentage (%) | Min Dimming percentage (%) | Start Time | Comments |
|-------------|---------------|----------------|---------------|----------------------------------|--|----------------------------|----------------------------|------------|---|
| CWD | SKYE | SF10P | 0-10V | 1 | 20 | 72 | 97% | 14% | |
| CWD | DEVINE | DF10P | 0-10V | 1 | 20 | 72 | 97% | 8% | |
| Leviton | Illumatech | IP710-DL | 0-10V | 1 | 20 | 52 | 96% | 9% | |
| Lutron | NTFTV | NOVA T | 0-10V | 1 | 42 | 96 | 96% | 7% | Please refer to Lutron Power Pack for additional information. |
| Lutron | DIVA | DVTV | 0-10V | 1 | 42 | 96 | 97% | 9% | |

Note: Maximum recommended luminaires based on a 100 feet wiring distance from dimmer to luminaire.

D010TE 0-10V 5500 Lumen

| Dimmer Make | Dimmer Series | Dimmer Model # | Dimmer Rating | Minimum Luminaires (per circuit) | Maximum Recommended Luminaires (per circuit) | Max Dimming percentage (%) | Min Dimming percentage (%) | Start Time | Comments |
|-------------|---------------|----------------|---------------|----------------------------------|--|----------------------------|----------------------------|------------|---|
| CWD | SKYE | SF10P | 0-10V | 1 | 17 | 59 | 99% | 14% | |
| CWD | DEVINE | DF10P | 0-10V | 1 | 17 | 59 | 99% | 10% | |
| Leviton | Illumatech | IP710-DL | 0-10V | 1 | 17 | 42 | 99% | 10% | |
| Lutron | NTFTV | NOVA T | 0-10V | 1 | 17 | 79 | 99% | 12% | Please refer to Lutron Power Pack for additional information. |
| Lutron | DIVA | DVTV | 0-10V | 1 | 17 | 79 | 99% | 12% | |

D010TE 0-10V 7000 Lumen

| Dimmer Make | Dimmer Series | Dimmer Model # | Dimmer Rating | Minimum Luminaires (per circuit) | Maximum Recommended Luminaires (per circuit) | Max Dimming percentage (%) | Min Dimming percentage (%) | Start Time | Comments |
|-------------|---------------|----------------|---------------|----------------------------------|--|----------------------------|----------------------------|------------|---|
| CWD | SKYE | SF10P | 0-10V | 1 | 13 | 44 | 99.28% | 14% | |
| CWD | DEVINE | DF10P | 0-10V | 1 | 13 | 44 | 99.52% | 9% | |
| Leviton | Illumatech | IP710-DL | 0-10V | 1 | 13 | 32 | 96.87% | 10% | |
| Lutron | NTFTV | NOVA T | 0-10V | 1 | 13 | 59 | 98.25% | 13% | Please refer to Lutron Power Pack for additional information. |
| Lutron | DIVA | DVTV | 0-10V | 1 | 13 | 59 | 100.00% | 12% | |

LED Rated Dimmers

D010TE 0-10V 8000 Lumen

| Dimmer Make | Dimmer Series | Dimmer Model # | Dimmer Rating | Minimum Luminaires (per circuit) | Maximum Recommended Luminaires (per circuit) | Max Dimming percentage (%) | Min Dimming percentage (%) | Start Time | Comments |
|-------------|---------------|----------------|---------------|----------------------------------|--|----------------------------|----------------------------|------------|---|
| CWD | SKYE | SF10P | 0-10V | 1 | 11 | 34 | 99.58% | 13% | |
| CWD | DEVINE | DF10P | 0-10V | 1 | 11 | 34 | 99.70% | 10% | |
| Leviton | Illumatech | IP710-DL | 0-10V | 1 | 11 | 24 | 99.34% | 10% | |
| Lutron | NTFTV | NOVA T | 0-10V | 1 | 22 | 51 | 99.82% | 12% | Please refer to Lutron Power Pack for additional information. |
| Lutron | DIVA | DVTV | 0-10V | 1 | 22 | 51 | 99.82% | 10% | |

D010TE 0-10V 9000 Lumen

| Dimmer Make | Dimmer Series | Dimmer Model # | Dimmer Rating | Minimum Luminaires (per circuit) | Maximum Recommended Luminaires (per circuit) | Max Dimming percentage (%) | Min Dimming percentage (%) | Start Time | Comments |
|-------------|---------------|----------------|---------------|----------------------------------|--|----------------------------|----------------------------|------------|---|
| CWD | SKYE | SF10P | 0-10V | 1 | 9 | 38 | 100% | 7% | |
| CWD | DEVINE | DF10P | 0-10V | 1 | 9 | 38 | 100% | 7% | |
| Leviton | Illumatech | IP710-DL | 0-10V | 1 | 9 | 27 | 100% | 7% | |
| Lutron | NTFTV | NOVA T | 0-10V | 1 | 22 | 51 | 100% | 7% | Please refer to Lutron Power Pack for additional information. |
| Lutron | DIVA | DVTV | 0-10V | 1 | 22 | 51 | 100% | 7% | |

D010TR 0-10V 5500 Lumen

| Dimmer Make | Dimmer Series | Dimmer Model # | Dimmer Rating | Minimum Luminaires (per circuit) | Maximum Recommended Luminaires (per circuit) | Max Dimming percentage (%) | Min Dimming percentage (%) | Start Time | Comments |
|-------------|---------------|----------------|---------------|----------------------------------|--|----------------------------|----------------------------|------------|---|
| CWD | SKYE | SF10P | 0-10V | 1 | 22 | 38 | 99.58% | 6.90% | |
| CWD | DEVINE | DF10P | 0-10V | 1 | 22 | 38 | 99.58% | 6.77% | |
| Leviton | Illumatech | IP710-DL | 0-10V | 1 | 22 | 27 | 99.58% | 7.06% | |
| Lutron | NTFTV | NOVA T | 0-10V | 1 | 23 | 51 | 99.58% | 6.83% | Please refer to Lutron Power Pack for additional information. |
| Lutron | DIVA | DVTV | 0-10V | 1 | 23 | 51 | 99.58% | 7.01% | |

LED Rated Dimmers

D010TR 0-10V 7000 Lumen

| Dimmer Make | Dimmer Series | Dimmer Model # | Dimmer Rating | Minimum Luminaires (per circuit) | Maximum Recommended Luminaires (per circuit) | Max Dimming percentage (%) | Min Dimming percentage (%) | Start Time | Comments |
|-------------|---------------|----------------|---------------|----------------------------------|--|----------------------------|----------------------------|------------|---|
| CWD | Arrow Hart | SF10P | 0-10V | 1 | 17 | 30 | 99% | 8% | |
| CWD | Arrow Hart | DF10P | 0-10V | 1 | 17 | 30 | 99% | 8% | |
| Leviton | Illumatech | IP710-DL | 0-10V | 1 | 17 | 21 | 99% | 8% | |
| Lutron | Nova | NOVA T | 0-10V | 1 | 18 | 40 | 99% | 9% | Please refer to Lutron Power Pack for additional information. |
| Lutron | Diva | DVTV | 0-10V | 1 | 18 | 40 | 99% | 9% | |

D010TR 0-10V 8000 Lumen

| Dimmer Make | Dimmer Series | Dimmer Model # | Dimmer Rating | Minimum Luminaires (per circuit) | Maximum Recommended Luminaires (per circuit) | Max Dimming percentage (%) | Min Dimming percentage (%) | Start Time | Comments |
|-------------|---------------|----------------|---------------|----------------------------------|--|----------------------------|----------------------------|------------|---|
| CWD | Arrow Hart | SF10P | 0-10V | 1 | 13 | 23 | 100% | 18% | |
| CWD | Arrow Hart | DF10P | 0-10V | 1 | 13 | 23 | 100% | 17% | |
| Leviton | Illumatech | IP710-DL | 0-10V | 1 | 13 | 16 | 100% | 16% | |
| Lutron | Nova | NOVA T | 0-10V | 1 | 13 | 31 | 100% | 17% | Please refer to Lutron Power Pack for additional information. |
| Lutron | Diva | DVTV | 0-10V | 1 | 13 | 31 | 100% | 16% | |

D010TR 0-10V 9000 Lumen

| Dimmer Make | Dimmer Series | Dimmer Model # | Dimmer Rating | Minimum Luminaires (per circuit) | Maximum Recommended Luminaires (per circuit) | Max Dimming percentage (%) | Min Dimming percentage (%) | Start Time | Comments |
|-------------|---------------|----------------|---------------|----------------------------------|--|----------------------------|----------------------------|------------|---|
| CWD | Arrow Hart | SF10P | 0-10V | 1 | 11 | 20 | 99.82% | 25% | |
| CWD | Arrow Hart | DF10P | 0-10V | 1 | 11 | 20 | 99.88% | 24% | |
| Leviton | Illumatech | IP710-DL | 0-10V | 1 | 11 | 14 | 100.00% | 25% | |
| Lutron | Nova | NOVA T | 0-10V | 1 | 12 | 27 | 99.76% | 24% | Please refer to Lutron Power Pack for additional information. |
| Lutron | Diva | DVTV | 0-10V | 1 | 12 | 27 | 99.94% | 24% | |

Incandescent and Electronic Low Voltage Rated Dimmers - For Reference Only

Testing conducted by Cooper Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards. Refer to this dimming guide notes section. Consult the dimmer manufacturer prior to installation to ensure compatibility.

D010TE 4500 Lumen

| Dimmer Make | Dimmer Series | Dimmer Model # | Types of Dimmer | Minimum Luminaires (per circuit) | Maximum Recommended Luminaires (per circuit) | Max Dimming percentage (%) | Min Dimming percentage (%) | Start Time |
|-------------|---------------|----------------|-----------------|----------------------------------|--|----------------------------|----------------------------|------------|
| CWD | Devine | DEL06P | ELV | 1 | 13 | 96% | 5% | >1 sec |
| Leviton | Vizia | VPE06 | ELV | 1 | 17 | 96% | 9% | >1 sec |
| Leviton | Illumatech | IPE04 | ELV | 1 | 13 | 96% | 9% | >1 sec |
| Leviton | Vizia | VZE04 | ELV | 1 | 17 | 97% | 15% | >1 sec |
| Lutron | Maestro | MAELV600 | ELV | 1 | 26 | 96% | 11% | >1 sec |
| Lutron | Faendra | FAELV500 | ELV | 1 | 22 | 96% | 11% | >1 sec |
| Lutron | Diva | DVELV303P | ELV | 1 | 13 | 95% | 7% | >1 sec |
| Lutron | Skylark | SELV300P | ELV | 1 | 13 | 95% | 7% | >1 sec |
| Lightolier | Sunrise | ZP260QEW | ELV | 1 | 11 | 95% | 4% | >1 sec |

D010TE 5500 Lumen

| Dimmer Make | Dimmer Series | Dimmer Model # | Dimmer Rating | Minimum Luminaires (per circuit) | Maximum Recommended Luminaires (per circuit) | Max Dimming percentage (%) | Min Dimming percentage (%) | Start Time |
|-------------|---------------|----------------|------------------------------|----------------------------------|--|----------------------------|----------------------------|-----------------------|
| Leviton | Decora | 6673 | Triac (CFL/INC) | 1 | 8 | 99% | 45% | >1 sec ^{1,2} |
| Leviton | SureSlide | 6631-2 | Triac (Incandescent) | 1 | 17 | 99% | 9% | >1 sec |
| Leviton | Illumatech | RP106 | Triac (Incandescent) | 1 | 17 | 100% | 14% | >1 sec ^{2,3} |
| Leviton | Illumatech | IPI06 | Triac (Incandescent) | 1 | 17 | 99% | 12% | ≥1 sec |
| Leviton | Vizia | VP106 | Triac (Incandescent) | 1 | 17 | 98% | 12% | ≥1 sec ³ |
| Leviton | Decora | 6161 | Triac (Incandescent) | 1 | 14 | 99% | 21% | ≥1 sec ³ |
| Leviton | SureSlide | 6633-P | Triac (Incandescent) | 1 | 17 | 99% | 4% | >1 sec |
| Lutron | Toggler | TG-600P | Triac (Incandescent) | 1 | 17 | 99% | 18% | >1 sec |
| Lutron | Diva | DV600P | Triac (Incandescent) | 1 | 17 | 99% | 9% | >1 sec |
| Lutron | Toggler | TGCL-153P | Triac (Incandescent/Halogen) | 1 | 17 | 98% | 1% | >1 sec |
| Lutron | Lumea | LG600P | Triac (Incandescent/Halogen) | 1 | 17 | 98% | 10% | >1 sec |
| Lutron | Skylark | S600P | Triac (Incandescent/Halogen) | 1 | 17 | 99% | 9% | >1 sec |

Incandescent and Electronic Low Voltage Rated Dimmers - For Reference Only

Testing conducted by Cooper Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards. Refer to this dimming guide notes section. Consult the dimmer manufacturer prior to installation to ensure compatibility.

D010TE 5500 Lumen Continued

| Dimmer Make | Dimmer Series | Dimmer Model # | Dimmer Rating | Minimum Luminaires (per circuit) | Maximum Recommended Luminaires (per circuit) | Max Dimming percentage (%) | Min Dimming percentage (%) | Start Time |
|-------------|--------------------|----------------|------------------------------|----------------------------------|--|----------------------------|----------------------------|---------------------|
| Lutron | Skylark Contour | CT103P | Triac (Incandescent/Halogen) | 1 | 29 | 99% | 12% | >1 sec |
| Lutron | Diva | DVCL-153P | Triac (Incandescent/Halogen) | 1 | 17 | 99% | 1% | ≥1 sec ¹ |
| CWD | Skye | SLC03PC-PTA | Triac (Incandescent/Halogen) | 1 | 17 | 99% | 3% | ≥1 sec |
| Leviton | Vizia | VPE06 | ELV | 1 | 17 | 99% | 11% | >1 sec |
| Leviton | Illumatech | IPE04 | ELV | 1 | 8 | 99% | 12% | >1 sec ² |
| Leviton | Vizia | VZE04 | ELV | 1 | 11 | 99% | 17% | ≥1 sec |
| Leviton | Acenti | ATX-10 | ELV (Fluorescent) | 1 | 29 | 99% | 40% | ≥1 sec |
| Lutron | Maestro | MAELV600 | ELV | 1 | 17 | 98% | 14% | >1 sec |
| Lutron | Faendra | FAELV500 | ELV | 1 | 17 | 99% | 13% | >1 sec |
| Lutron | Diva | DVELV303P | ELV | 1 | 8 | 99% | 9% | >1 sec |
| Lutron | Skylark | SELV300P | ELV | 1 | 8 | 99% | 9% | >1 sec |
| Lightolier | Sunrise | ZP260QEW | ELV | 1 | 7 | 99% | 5% | >1 sec ³ |
| Leviton | PlugIn Lamp Dimmer | TBI03 | Triac | 1 | 8 | 99% | 2% | ≥1 sec |

D010TE 7000 Lumen

| Dimmer Make | Dimmer Series | Dimmer Model # | Dimmer Rating | Minimum Luminaires (per circuit) | Maximum Recommended Luminaires (per circuit) | Max Dimming percentage (%) | Min Dimming percentage (%) | Start Time |
|-------------|---------------|----------------|------------------------------|----------------------------------|--|----------------------------|----------------------------|-----------------------|
| Leviton | Decora | 6673 | Triac (CFL/INC) | 1 | 6 | 96% | 45% | ≥1 sec ¹ |
| Leviton | SureSlide | 6631-2 | Triac (Incandescent) | 1 | 13 | 97% | 7% | >1 sec |
| Leviton | Illumatech | RP106 | Triac (Incandescent) | 1 | 13 | 98% | 15% | >1 sec ^{2,3} |
| Leviton | Illumatech | IPI06 | Triac (Incandescent) | 1 | 13 | 98% | 12% | >1 sec |
| Lutron | Toggler | TG-600P | Triac | 1 | 13 | 96% | 25% | >1 sec |
| Lutron | Diva | DV600P | Triac (Incandescent) | 1 | 13 | 97% | 11% | >1 sec |
| Lutron | Toggler | TGCL-153P | Triac (Incandescent/Halogen) | 1 | 13 | 96% | 3% | >1 sec |
| Lutron | Lumea | LG600P | Triac (Incandescent/Halogen) | 1 | 13 | 97% | 13% | >1 sec |
| Lutron | Skylark | S600P | Triac (Incandescent/Halogen) | 1 | 13 | 97% | 12% | >1 sec |

Incandescent and Electronic Low Voltage Rated Dimmers

- For Reference Only

Testing conducted by Cooper Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards. Refer to this dimming guide notes section. Consult the dimmer manufacturer prior to installation to ensure compatibility.

D010TE 7000 Lumen Continued

| Dimmer Make | Dimmer Series | Dimmer Model # | Dimmer Rating | Minimum Luminaires (per circuit) | Maximum Recommended Luminaires (per circuit) | Max Dimming percentage (%) | Min Dimming percentage (%) | Start Time |
|-------------|--------------------|----------------|------------------------------|----------------------------------|--|----------------------------|----------------------------|---------------------|
| Lutron | Skylark Contour | CT103P | Triac (Incandescent/Halogen) | 1 | 21 | 97% | 12% | >1 sec |
| Lutron | Diva | DV603P | Triac (Incandescent/Halogen) | 1 | 13 | 97% | 17% | >1 sec |
| Lutron | Diva | DVCL-153P | Triac (Incandescent/Halogen) | 1 | 13 | 96% | 3% | >1 sec |
| CWD | Skye | SLC03PC-PTA | Triac (Incandescent/Halogen) | 1 | 13 | 97% | 3% | >1 sec |
| Leviton | Vizia | VPE06 | ELV | 1 | 13 | 97% | 10% | >1 sec |
| Leviton | Illuminatech | IPE04 | ELV | 1 | 6 | 96% | 11% | >1 sec ² |
| Leviton | Vizia | VZE04 | ELV | 1 | 8 | 97% | 16% | ≥1 sec |
| Leviton | Acenti | ATX-10 | ELV (Fluorescent) | 1 | 21 | 97% | 38% | >1 sec |
| Lutron | Maestro | MAELV600 | ELV | 1 | 13 | 97% | 13% | >1 sec |
| Lutron | Faendra | FAELV500 | ELV | 1 | 13 | 97% | 13% | >1 sec |
| Lutron | Diva | DVELV303P | ELV | 1 | 6 | 96% | 8% | >1 sec |
| Lutron | Skylark | SELV300P | ELV | 1 | 6 | 96% | 8% | >1 sec |
| Lightolier | Sunrise | ZP260QEW | ELV | 1 | 5 | 96% | 3% | >1 sec |
| Leviton | PlugIn Lamp Dimmer | TBI03 | Triac (Incandescent) | 1 | 6 | 99% | 16% | >1 sec |

D010TE 8000 Lumen

| Dimmer Make | Dimmer Series | Dimmer Model # | Dimmer Rating | Minimum Luminaires (per circuit) | Maximum Recommended Luminaires (per circuit) | Max Dimming percentage (%) | Min Dimming percentage (%) | Start Time |
|-------------|---------------|----------------|---------------|----------------------------------|--|----------------------------|----------------------------|------------|
| CWD | Devine | DEL06P | ELV | 1 | 6 | 94% | 6% | ≥1 sec |
| Leviton | Vizia | VPE06 | ELV | 1 | 8 | 95% | 4% | >1 sec |
| Leviton | Illuminatech | IPE04 | ELV | 1 | 6 | 92% | 4% | >1 sec |
| Leviton | Vizia | VZE04 | ELV | 1 | 8 | 94% | 10% | ≥1 sec |
| Lutron | Maestro | MAELV600 | ELV | 1 | 12 | 91% | 6% | >1 sec |
| Lutron | Faendra | FAELV500 | ELV | 1 | 10 | 92% | 5% | >1 sec |
| Lutron | Diva | DVELV303P | ELV | 1 | 6 | 88% | 2% | >1 sec |
| Lutron | Skylark | SELV300P | ELV | 1 | 6 | 88% | 2% | >1 sec |
| Lightolier | Sunrise | ZP260QEW | ELV | 1 | 5 | 88% | 1% | >1 sec |

Incandescent and Electronic Low Voltage Rated Dimmers - For Reference Only

Testing conducted by Cooper Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards. Refer to this dimming guide notes section. Consult the dimmer manufacturer prior to installation to ensure compatibility.

D010TE 9000 Lumen

| Dimmer Make | Dimmer Series | Dimmer Model # | Dimmer Rating | Minimum Luminaires (per circuit) | Maximum Recommended Luminaires (per circuit) | Max Dimming percentage (%) | Min Dimming percentage (%) | Start Time |
|-------------|-----------------|----------------|------------------------------|----------------------------------|--|----------------------------|----------------------------|-------------------------|
| Leviton | Decora | 6673 | Triac (CFL/INC) | 1 | 2 | 98% | 9% | ≥1 sec ^{1,4} |
| Leviton | SureSlide | 6631-2 | Triac (Incandescent) | 1 | 4 | 98% | 1% | >1 sec ^{2,3,4} |
| Leviton | Illumatech | RP106 | Triac (Incandescent) | 1 | 4 | 99% | 16% | >1 sec ^{2,3,4} |
| Leviton | Illumatech | IPI06 | Triac (Incandescent) | 1 | 4 | 99% | 7% | >1 sec ⁴ |
| Leviton | Decora | 6161 | Triac (Incandescent) | 1 | 4 | 98% | 16% | ≥1 sec |
| Leviton | SureSlide | 6633-P | Triac (Incandescent) | 1 | 4 | 99% | 1% | >1 sec ^{2,4} |
| Lutron | Toggler | TG-600P | Triac (Incandescent) | 1 | 4 | 97% | 13% | >1 sec ⁴ |
| Lutron | Nova T | NTFTU-5A | Triac (Fluorescent) | 1 | 4 | 98% | 37% | ≥1 sec ⁴ |
| Lutron | Diva | DV600P | Triac (Incandescent) | 1 | 4 | 98% | 1% | >1 sec ^{2,3,4} |
| Lutron | Toggler | TGCL-153P | Triac (Incandescent/Halogen) | 1 | 4 | 96% | 3% | >1 sec ⁴ |
| Lutron | Lumea | LG600P | Triac (Incandescent/Halogen) | 1 | 4 | 98% | 0% | >1 sec ^{2,4} |
| Lutron | Skylark | S600P | Triac (Incandescent/Halogen) | 1 | 4 | 97% | 1% | >1 sec ^{2,3,4} |
| Lutron | Skylark Contour | CT103P | Triac (INC/HAL/MLV) | 1 | 8 | 97% | 3% | >1 sec ^{2,4} |
| Lutron | Diva | DV603P | Triac (Incandescent/Halogen) | 1 | 4 | 97% | 3% | >1 sec ⁴ |
| Leviton | Vizia | VPE06 | ELV | 1 | 4 | 99% | 7% | >1 sec |
| Leviton | Illumatech | IPE04 | ELV | 1 | 2 | 99% | 2% | >1 sec |
| Leviton | Vizia | VZE04 | ELV | 1 | 3 | 99% | 14% | ≥1 sec |
| Leviton | Acenti | ATX10 | Triac (Fluorescent) | 1 | 8 | 79% | 42% | ≥1 sec |
| Lutron | Maestro | MAELV600 | ELV | 1 | 4 | 98% | 12% | >1 sec |
| Lutron | Faetra | FAELV500 | ELV | 1 | 4 | 96% | 10% | ≥1 sec |
| Lutron | Diva | DVELV303P | ELV | 1 | 2 | 95% | 5% | >1 sec |
| Lutron | Skylark | SELV300P | ELV | 1 | 2 | 95% | 4% | >1 sec |
| Lightolier | Sunrise | ZP260QEW | ELV | 1 | 2 | 93% | 2% | ≥1 sec |
| CWD | Aspire | 9530AW | Triac (Incandescent) | 1 | 4 | 99% | 1% | ≥1 sec ⁴ |
| CWD | React | RI061 | Triac (Incandescent/Halogen) | 1 | 4 | 98% | 18% | >1 sec ^{2,4} |
| CWD | Devine | DE06P | ELV | 1 | 4 | 95% | 12% | >1 sec ⁴ |
| CWD | Toggle | TI061 | Triac (Incandescent/Halogen) | 1 | 4 | 94% | 6% | ≥1 sec ⁴ |

Incandescent and Electronic Low Voltage Rated Dimmers - For Reference Only

Testing conducted by Cooper Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards. Refer to this dimming guide notes section. Consult the dimmer manufacturer prior to installation to ensure compatibility.

D010TR 4500 Lumen

| Dimmer Make | Dimmer Series | Dimmer Model # | Dimmer Rating | Minimum Luminaires (per circuit) | Maximum Recommended Luminaires (per circuit) | Max Dimming percentage (%) | Min Dimming percentage (%) | Start Time |
|-------------|-----------------|----------------|------------------------------|----------------------------------|--|----------------------------|----------------------------|-----------------------|
| Leviton | SureSlide | 6631-2 | Triac (Incandescent) | 1 | 11 | 100% | 0% | >1 sec ⁴ |
| Leviton | Illumatech | IPI06 | Triac (Incandescent) | 1 | 11 | 100% | 0% | >1 sec ⁴ |
| Leviton | Vizia | VP106 | Triac (Incandescent) | 1 | 11 | 99% | 2% | >1 sec ⁴ |
| Leviton | Decora | 6161 | Triac (Incandescent) | 1 | 9 | 100% | 5% | ≥1 sec ⁴ |
| Leviton | SureSlide | 6633-P | Triac (Incandescent) | 1 | 11 | 100% | 1% | >1 sec ⁴ |
| Lutron | Toggler | TG-600P | Triac (Incandescent) | 1 | 11 | 100% | 6% | >1 sec ⁴ |
| Lutron | Diva | DV600P | Triac (Incandescent) | 1 | 11 | 99% | 1% | >1 sec ⁴ |
| Lutron | Maestro | MAW600 | Triac (Incandescent/Halogen) | 1 | 11 | 100% | 0% | ≥1 sec ⁴ |
| Lutron | Toggler | TGCL-153P | Triac (Incandescent/Halogen) | 1 | 11 | 99% | 2% | >1 sec ⁴ |
| Lutron | Lumea | LG600P | Triac (Incandescent/Halogen) | 1 | 11 | 100% | 1% | >1 sec ⁴ |
| Lutron | Skylark | S600P | Triac (Incandescent/Halogen) | 1 | 11 | 100% | 1% | >1 sec ⁴ |
| Lutron | Skylark Contour | CT103P | Triac (INC/HAL/MLV) | 1 | 18 | 100% | 5% | >1 sec ⁴ |
| Lutron | Diva | DV603P | Triac (Incandescent/Halogen) | 1 | 11 | 99% | 3% | >1 sec ⁴ |
| Leviton | Vizia | VPE06 | ELV | 1 | 11 | 100% | 3% | >1 sec ⁴ |
| Leviton | Illumatech | IPE04 | ELV | 1 | 5 | 100% | 1% | >1 sec ^{2,4} |
| Leviton | Vizia | VZE04 | ELV | 1 | 7 | 100% | 6% | ≥1 sec ⁴ |
| Leviton | Acenti | ATX10 | Triac (Fluorescent) | 1 | 18 | 100% | 15% | ≥1 sec ⁴ |
| Lutron | Maestro | MAELV600 | ELV | 1 | 11 | 99% | 5% | >1 sec ⁴ |
| Lutron | Faetra | FAELV500 | ELV | 1 | 11 | 99% | 4% | >1 sec ⁴ |
| Lutron | Diva | DVELV303P | ELV | 1 | 5 | 95% | 2% | >1 sec ⁴ |
| Lutron | Skylark | SELV300P | ELV | 1 | 5 | 96% | 2% | >1 sec ⁴ |
| Lightolier | Sunrise | ZP260QEW | ELV | 1 | 4 | 96% | 2% | >1 sec ⁴ |
| CWD | Aspire | 9530AW | Triac (Incandescent) | 1 | 11 | 100% | 1% | >1 sec ⁴ |
| CWD | Skye | SF8AP | Triac (Fluorescent) | 1 | 11 | 100% | 22% | ≥1 sec ^{3,4} |
| CWD | Devine | DE06P | ELV | 1 | 11 | 97% | 4% | >1 sec ^{1,4} |
| CWD | Toggle | TI061 | Triac (Incandescent/Halogen) | 1 | 11 | 95% | 3% | ≥1 sec ⁴ |

Incandescent and Electronic Low Voltage Rated Dimmers - For Reference Only

Testing conducted by Cooper Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards. Refer to this dimming guide notes section. Consult the dimmer manufacturer prior to installation to ensure compatibility.

D010TR 5500 Lumen

| Dimmer Make | Dimmer Series | Dimmer Model # | Dimmer Rating | Minimum Luminaires (per circuit) | Maximum Recommended Luminaires (per circuit) | Max Dimming percentage (%) | Min Dimming percentage (%) | Start Time |
|-------------|--------------------|----------------|-------------------------------|----------------------------------|--|----------------------------|----------------------------|---------------------|
| Leviton | Decora | 6673 | Triac (CFL/INC) | 1 | 4 | 99% | 4% | ≥1 sec ¹ |
| Leviton | SureSlide | 6631-2 | Triac (Incandescent) | 1 | 8 | 99% | 3% | ≥1 sec |
| Leviton | Illumatech | RP106 | Triac (Incandescent) | 1 | 8 | 100% | 7% | >1 sec |
| Leviton | Illumatech | IPI06 | Triac (Incandescent) | 1 | 8 | 99% | 5% | ≥1 sec |
| Leviton | Vizia | VP106 | Triac (Incandescent) | 1 | 8 | 100% | 5% | ≥1 sec |
| Leviton | Decora | 6161 | Triac (Incandescent) | 1 | 7 | 99% | 9% | ≥1 sec |
| Leviton | SureSlide | 6633-P | Triac (Incandescent) | 1 | 8 | 99% | 0% | >1 sec |
| Lutron | Toggler | TG-600P | Triac (Incandescent) | 1 | 8 | 98% | 9% | ≥1 sec |
| Lutron | Diva | DV600P | Triac (Incandescent) | 1 | 8 | 99% | 3% | ≥1 sec |
| Lutron | Maestro | MAW600 | Triac (Incandescent/Halogen) | 1 | 8 | 99% | 1% | ≥1 sec |
| Lutron | Toggler | TGCL-153P | Triac (Incandescent/Halogen) | 1 | 8 | 98% | 7% | ≥1 sec |
| Lutron | Lumea | LG600P | Triac (Incandescent/Halogen) | 1 | 8 | 99% | 4% | ≥1 sec |
| Lutron | Skylark | S600P | Triac (Incandescent/Halogen) | 1 | 8 | 98% | 3% | ≥1 sec |
| Lutron | Skylark Contour | CT103P | Triac (INC/HAL/MLV) | 1 | 14 | 98% | 9% | ≥1 sec |
| Lutron | Diva | DV603P | Triac (Incandescent/Halogen) | 1 | 8 | 98% | 5% | ≥1 sec |
| Leviton | Vizia | VPE06 | ELV | 1 | 8 | 100% | 5% | ≥1 sec |
| Leviton | Illumatech | IPE04 | ELV | 1 | 4 | 99% | 6% | ≥1 sec |
| Leviton | Vizia | VZE04 | ELV | 1 | 5 | 99% | 1% | ≥1 sec |
| Leviton | Acenti | ATX-10 | ELV (Fluorescent) | 1 | 14 | 99% | 2% | ≥1 sec |
| Lutron | Maestro | MAELV600 | ELV | 1 | 8 | 99% | 8% | ≥1 sec |
| Lutron | Faetra | FAELV500 | ELV | 1 | 8 | 98% | 7% | ≥1 sec |
| Lutron | Diva | DVELV303P | ELV | 1 | 4 | 96% | 4% | ≥1 sec |
| Lutron | Skylark | SELV300P | ELV | 1 | 4 | 96% | 4% | ≥1 sec |
| CWD | Devine | DEL06P | ELV | 1 | 0 | 98% | 2% | ≥1 sec |
| Lightolier | Sunrise | ZP260QEW | ELV | 1 | 3 | 96% | 3% | ≥1 sec |
| Leviton | PlugIn Lamp Dimmer | TBI03 | Triac (Incandescent) | 1 | 4 | 99% | 0% | ≥1 sec |

Incandescent and Electronic Low Voltage Rated Dimmers

- For Reference Only

Testing conducted by Cooper Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards. Refer to this dimming guide notes section. Consult the dimmer manufacturer prior to installation to ensure compatibility.

D010TR 7000 Lumen

| Dimmer Make | Dimmer Series | Dimmer Model # | Dimmer Rating | Minimum Luminaires (per circuit) | Maximum Recommended Luminaires (per circuit) | Max Dimming percentage (%) | Min Dimming percentage (%) | Start Time |
|-------------|---------------|----------------|-------------------------------------|----------------------------------|--|----------------------------|----------------------------|---------------------|
| Leviton | Decora | 6673 | Triac (CFL/INC) | 1 | 3 | 100% | 4% | ≥1 sec ⁴ |
| Leviton | SureSlide | 6631-2 | Triac (Incandescent) | 1 | 6 | 100% | 1% | >1 sec ⁴ |
| Leviton | Illumatech | IPI06 | Triac (Incandescent) | 1 | 6 | 100% | 3% | >1 sec ⁴ |
| Leviton | Vizia | VP106 | Triac (Incandescent) | 1 | 6 | 100% | 5% | ≥1 sec ⁴ |
| Leviton | Decora | 6161 | Triac (Incandescent) | 1 | 5 | 100% | 9% | ≥1 sec ⁴ |
| Leviton | SureSlide | 6633-P | Triac (Incandescent) | 1 | 6 | 100% | 0% | >1 sec ⁴ |
| Lutron | Toggler | TG-600P | Triac (Incandescent) | 1 | 6 | 100% | 8% | >1 sec ⁴ |
| Lutron | Diva | DV600P | Triac (Incandescent) | 1 | 6 | 100% | 3% | >1 sec ⁴ |
| Lutron | Maestro | MAW600 | Triac (Incandescent/Halogen) | 1 | 6 | 100% | 1% | ≥1 sec ⁴ |
| Lutron | Toggler | TGCL-153P | Triac (Incandescent/Halogen) | 1 | 6 | 100% | 2% | >1 sec ⁴ |
| Lutron | Diva | DV603P | Triac (Incandescent/Halogen) | 1 | 6 | 100% | 5% | >1 sec ⁴ |
| Leviton | Vizia | VPE06 | ELV | 1 | 6 | 99% | 4% | >1 sec |
| Leviton | Illumatech | IPE04 | ELV | 1 | 3 | 99% | 2% | >1 sec |
| Leviton | Vizia | VZE04 | ELV | 1 | 4 | 100% | 8% | ≥1 sec |
| Leviton | Acenti | ATX10 | Triac (Fluorescent) | 1 | 11 | 99% | 20% | ≥1 sec ⁴ |
| Lutron | Maestro | MAELV600 | ELV | 1 | 6 | 99% | 7% | ≥1 sec |
| Lutron | Faetra | FAELV500 | ELV | 1 | 6 | 99% | 6% | ≥1 sec |
| Lutron | Diva | DVELV303P | ELV | 1 | 3 | 96% | 3% | >1 sec |
| Lutron | Skylark | SELV300P | ELV | 1 | 3 | 97% | 3% | >1 sec |
| Lightolier | Sunrise | ZP260QEW | ELV | 1 | 2 | 98% | 3% | >1 sec |
| CWD | Aspire | 9530AW | Triac (Incandescent) | 1 | 6 | 100% | 1% | >1 sec ⁴ |
| CWD | Skye | SF8AP | Triac (Fluorescent) | 1 | 7 | 100% | 30% | ≥1 sec ⁴ |
| CWD | Devine | DE06P | ELV | 1 | 6 | 99% | 7% | >1 sec ⁴ |
| CWD | Toggle | TI061 | Triac (Incandescent/Halogen) | 1 | 6 | 98% | 6% | ≥1 sec ⁴ |
| CWD | Smart | AAL06 | Triac (INC/HAL/FLR/MLV/ELV/CFL/LED) | 1 | 6 | 99% | 2% | ≥1 sec ⁴ |

Incandescent and Electronic Low Voltage Rated Dimmers

- For Reference Only

Testing conducted by Cooper Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards. Refer to this dimming guide notes section. Consult the dimmer manufacturer prior to installation to ensure compatibility.

D010TR 8000 Lumen

| Dimmer Make | Dimmer Series | Dimmer Model # | Dimmer Rating | Minimum Luminaires (per circuit) | Maximum Recommended Luminaires (per circuit) | Max Dimming percentage (%) | Min Dimming percentage (%) | Start Time |
|-------------|-----------------|----------------|------------------------------|----------------------------------|--|----------------------------|----------------------------|---------------------|
| Leviton | Decora | 6673 | Triac (CFL/INC) | 1 | 2 | 100% | 5% | ≥1 sec ¹ |
| Leviton | SureSlide | 6631-2 | Triac (Incandescent) | 1 | 5 | 100% | 2% | >1 sec |
| Leviton | Illumatech | RP106 | Triac (Incandescent) | 1 | 5 | 100% | 0% | >1 sec ² |
| Leviton | Vizia | VP106 | Triac (Incandescent) | 1 | 5 | 100% | 5% | ≥1 sec |
| Leviton | Decora | 6161 | Triac (Incandescent) | 1 | 4 | 100% | 10% | ≥1 sec |
| Leviton | SureSlide | 6633-P | Triac (Incandescent) | 1 | 5 | 100% | 0% | >1 sec |
| Lutron | Toggler | TG-600P | Triac (Incandescent) | 1 | 5 | 100% | 10% | ≥1 sec |
| Lutron | Diva | DV600P | Triac (Incandescent) | 1 | 5 | 100% | 3% | ≥1 sec |
| Lutron | Maestro | MAW600 | Triac (Incandescent/Halogen) | 1 | 5 | 100% | 1% | ≥1 sec |
| Lutron | Toggler | TGCL-153P | Triac (Incandescent/Halogen) | 1 | 5 | 100% | 2% | >1 sec |
| Lutron | Lumea | LG600P | Triac (Incandescent/Halogen) | 1 | 5 | 100% | 4% | ≥1 sec |
| Lutron | Skylark | S600P | Triac (Incandescent/Halogen) | 1 | 5 | 100% | 3% | >1 sec |
| Lutron | Skylark Contour | CT103P | Triac (INC/HAL/MLV) | 1 | 9 | 100% | 10% | ≥1 sec |
| Lutron | Diva | DV603P | Triac (Incandescent/Halogen) | 1 | 5 | 100% | 6% | ≥1 sec |
| Leviton | Vizia | VPE06 | ELV | 1 | 5 | 100% | 5% | ≥1 sec |
| Leviton | Illumatech | IPE04 | ELV | 1 | 2 | 100% | 6% | ≥1 sec |
| Leviton | Vizia | VZE04 | ELV | 1 | 3 | 100% | 9% | ≥1 sec |
| Lutron | Maestro | MAELV600 | ELV | 1 | 5 | 100% | 7% | ≥1 sec |
| Lutron | Faetra | FAELV500 | ELV | 1 | 5 | 100% | 7% | ≥1 sec |
| Lutron | Diva | DVELV303P | ELV | 1 | 2 | 100% | 4% | ≥1 sec |
| Lutron | Skylark | SELV300P | ELV | 1 | 2 | 100% | 4% | ≥1 sec |
| Lightolier | Sunrise | ZP260QEW | ELV | 1 | 2 | 100% | 2% | ≥1 sec |

Note: Cooper has tested these dimmers for performance. The limitations of the dimmers are based on many factors outside of our control. The application of dimming controls and limitations may change without notice to Cooper or any other user. Prior to Installation the dimmer manufacturer should be contacted to ensure capatibility.

Dimmer Notes:

- 1) Start time is measured at the lowest dimmer setting.
- 2) Some LED rated dimmers have a "rapid start" design used to provide a momentary power boost for LED and CFL lamps during start-up. When a LED luminaire is on a dimmer with "rapid start" the boost may cause a momentary flash of the LED lighting. This "flash" is generated by the dimmer, and may be more noticeable when the dimmer is at a low setting. A solution is available in the following CWD dimmers which provide adjustment capability of the "rapid start": Devine (DAL06P), Accell (AL06P), and Trace (TAL06P). Refer to product specifications online at www.cooperwiringdevices.com for more details.

Dimming Guide Disclaimer:

- 1) CC is Cooper Controls, part of Eaton's Cooper Lighting business. CWD is Eaton's Cooper Wiring Devices business. Cooper Controls and Cooper Wiring Devices brand names, where identified above, are trade names or trademarks of Eaton or its Affiliates.
Leviton® is a registered trademark of Leviton Manufacturing Co. Inc., Lutron® is a registered trademark of Lutron Electronics Co. Inc., Lightolier is a registered trademark of Philips Lighting, and any other brands are trade names or trademarks of their respective company, and are not associated with Cooper Controls or Cooper Wiring Devices.
- 2) Testing conducted by Cooper Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification.
Refer to the manufacturer specifications for more detailed information on product certifications and standards.
- 3) This is a representative list of typical dimmers as tested by Cooper Lighting for performance with the designated LED luminaires only. Test data contained in this literature is based upon dimmers obtained in the marketplace. Information about these other manufacturers products is obtained from packaging and published information made available by the manufacturer and is deemed to be reliable, but has not been verified.
Dimmer performance and perceived limitations of the dimmers are based on factors outside of Cooper Lighting's control.
The specifications of these dimming controls and their conditions of use may change without notice to Cooper Lighting or any other user.
Cooper Lighting makes no specific recommendation on product selection and there are no warranties of performance or compatibility implied.
Installer must ensure proper local and national electrical codes are followed; and that the dimmer application and condition of use is per dimmer manufacturer instructions and guidelines.

Eaton's AL Series dimmers offer versatile options to set the mood and reduce energy consumption.

Visit www.cooperwiringdevices.com/ALSeries for more information.



| Dimmer Features | ACCELL (AAL06) | DEVINE (DAL06P) | SKYE (SAL06P) |
|---------------------------------|----------------------------------|-----------------------------|-----------------------------|
| Rapid Start feature | Selectable ON or OFF | Fully adjustable | Fixed ON |
| Adjustable high-end trim | • | | |
| Adjustable low-end trim | • | • | • |
| Wiring configurations | Single-pole or multi-location | Single-pole or three-way | Single-pole or three-way |
| Color change kits | • | • | |

Note: The Rapid Start feature is used to ensure the right amount of power boost during start-up. When a dimmer with Rapid Start is turned on from a low dimmer setting, the LED lighting may exhibit a momentary flash. Select dimmer models offer an adjustment of the Rapid Start feature. The user may wish to adjust this setting to reduce the boost and resulting momentary flash. If this capability is desired, the user should select dimmer models designated as "fully adjustable" or "selectable ON or OFF".