COOPER LIGHTING - SURE-LITES®

Catalog #	Туре
Project	
Comments	Date
Prepared by	

SPECIFICATION FEATURES

Flectrical

- 6V or 12V DC Input Voltage

Construction

- 20-gauge, die-stamped steel housing with white baked enamel finish
- Shallow 5 1/2" housing accommodates 2x6 construction
- Housing adjusts in plaster frame 1 3/8" to accommodate different ceiling thickness
- Bar hangers included for fast, easy installation
- White painted trim ring with 5 1/8" diameter flat albalite lens
- Junction box provided for wiring terminations

Code Compliance

- UL Damp Location Listed

Warranty

- Unit: 1-year

Lamp Data

- 6 Volt Incandescent Double Contact Bayonet Base
- 12 Volt Incandescent Double Contact Bayonet Base
- Consult factory for other lamp types.



RFR SERIES

ROUND SPECIALTY REMOTES

EMERGENCY LIGHTING



ORDERING INFORMATION

RFR Series

Catalog No.	Finish	Lamp Type	Volts	Watts	Lamp No.
RFR153	White Trim	Incandescent DC Bayonet Base	12	7.5	029-53

Alternate Lamps: Consult Cooper Lighting Representative Other Finishes Available: Cooper Lighting Representative

ENERGY DATA

Power Consumption is equal to lamp wattage.

