

Cadence

PROPERTIES

Description

Italian enhanced grain, semi-aniline leather. Available in 12 in-stock FiberDye® colors.

Attributes

Durable, anti-bacterial finish. Flame resistant. UV protected. Water and stain repellent dyed into the leather.

Hide Size

50.00 sq. ft. avg.

Thickness

1.1mm +/- 0.1mm

Weight

2.75oz +/- 0.25oz per sq. ft.

Grain Characteristics

Uniform

Finish Characteristics

Durable

TEST PERFORMANCE

ABRASION

CS-10

Taber Abrasion Resistance

1000+ cycles

ANTI-BACTERIAL

AATCC 100

Assessment of Anti-Bacterial Finishes on Textile Materials (Quantitative)

Meets Requirements

AATCC 147

Assessment of Anti-Bacterial Activity of Textile Materials (Qualitative)

Meets Requirements

ENVIRONMENTAL

GREENGUARD

Indoor Air Quality

Certified

FLAMMABILITY

California Technical Bulletin

117 Section E Flammability Test

Certified

FAR 25.853 (a) Am. 25-116,

App. F, Part I (a)(1)(ii)

Federal Aviation Regulation

for Flammability Resistance

May be treated to meet requirements

IMO A.652(16)8.2

International Marine Organization

Smouldering Cigarette Test

Passed

NFPA 260

National Fire Protection Association

Cigarette Ignition Resistance

Certified

Cadence maybe used in California

TB 133 applications with suitable fire backers.

DURABILITY

Excellent. Recommended for all upholstery applications, especially high traffic areas.



Available Worldwide
Visit garrettleather.com for a showroom in your area.



800.342.7738
www.garrettleather.com