

Forge Ahead

Product Specifications

Style Name	FORGE AHEAD
Style Number	I500V
Construction	Homogeneous Plus
Overall Thickness	.090" (2.3 mm)
Reference Specification	ASTM 1303-04 Type II, Grade I
Backing Class	Non-Foamed Plastic, Class B
Finish	ExoGuard™ Quartz Enhanced Urethane
Installation	Glue Down
Recommended Adhesive	Shaw 4100

Packaging

Roll Size	72" wide x 20 yd long rolls (40 sy/roll)
Actual	1.83 m wide x 18.23 m long rolls
Weight	6.5 lbs/yd ² (3.5 kg/m ²) 260.0 lbs/roll (140.0 kg/roll)

Performance Testing

Slip Resistance/ASTM D 2047	ADA Compliant
Static Load/ASTM F 970	1500 lbs/sq. in.
Residual Indentation/ASTM 1914	Passes <8%
Flexibility/ASTM F 137	Passes
Resistance to Heat/ASTM F 1514	Passes
Resistance to Light/ASTM F 1515	Passes
Resistance to Chemicals/ASTM 925	Passes
Resistance to Fungi/ASTM G 21	Passes, Rate 0 (Rate 0: Fungi Free)
Antibacterial Activity/AATCC 147	Passes, resists the propagation of bacteria
Radiant Flux/ASTM E 648	>0.45 watts/cm ² , NFPA Class I
Smoke Density/ASTM E 662	<450, Passes

Warranty

10 year limited commercial wear warranty.
10 year under bed warranty when installed with Shaw 4100 or Shaw S150 spray adhesive.
Please visit patcraft.com for the most current warranty information.

Environmental

Indoor Air Quality LEED Scorecard	FloorScore® Certified IEQ
--------------------------------------	------------------------------