

Wall Base Specification & Technical Information

Specifications

Style Number	S127V
Construction	Thermoplastic Rubber
Gauge	1/8"
Roll Size	4" x 120' roll/coil per carton
Recommended Adhesives	S132V Tube Wall Base Adhesives (Twelve 30/oz tubes per carton, sold by carton only) S133V Wall Base Adhesive (1 Gallon)
Warranty	5 years
Indoor Air Quality	FloorScore® certified

Installation

Requirements

Please note: In all cases, installations should comply with ASTM Standards – At a minimum, where "Better Than" ASTM Standards are recommended, please refer to Instructions below. Read the instructions completely before beginning.

General

The wall surface must be thoroughly dry, smooth, and free from dirt, wallpaper, vinyl wall covering, grease, old adhesives, and other extraneous material. DO NOT apply directly over outside walls in contact with earth (such as unfurred basement walls) or over ceramic tile, metals, or other impervious surfaces because poor adhesion may result.

Maintain the wall base, adhesive, and room air at a uniform temperature of at least 70°F for 24 hours prior to, during, and 48 hours after the installation. Rolled wall base should be unrolled and allowed to lie flat for 24 hours prior to the installation to regain its normal shape. Use Shaw Cove Base adhesive carefully following the directions on the container label.

Adhesive Requirements

S132V Tube Wall Base Adhesive (Twelve 30/oz tubes per carton, sold by carton only)
S133V Wall Base Adhesive (1 Gallon)

Solvent Free	Rubber & Vinyl Wall Base
Low Odor	Exceptional Wet Grab

Instructions

Patcraft Wall Base Adhesive is a premium light-colored, solvent-free acrylic adhesive for installing wall base on clean, dry interior walls. Patcraft Wall Base Adhesive has the powerful wet strength needed to hold Wall Base firmly to the wall until it dries.

transforming performance.

Advantages

- Good grab
- SCAQMD Rule 1168 – compliant
- Low odor
- Easy Clean Up
- Freeze thaw protection to 15°F

Coverage & Open Time

Coverage on 4" Wall Base (10.16 cm): 1/8" x 1/8" V-Notch = 220–240 linear feet per gallon.

20–30 Minutes.

Shelf Life

Two years from manufacturing date in an un-opened container.

Avoid excessive heat or cold. Protect from freezing – store at temperature between 65° and 95° F.

Wall Surfaces

Plaster, brick, wood, concrete, gypsum, drywall, plywood.

VOC content is below and is established by California SCAQMD Rule 1168.

Product Identifier

Patcraft Wall Base Adhesive/Shaw Cove Base Adhesive

LEED Program Certifications (where applicable)

IEQ Credit 4.1 – Low emitting materials

IEQ Credit 4.3 – Low VOC ratings help qualify installations for this credit as part of a flooring system

MR Credit 5 – Regional Materials – on jobsites within 500 miles of manufacturing location: Dalton, GA 30721

Initial Maintenance: Wall Base & Adhesive

Allow the adhesive on the wall base to dry thoroughly before completing initial maintenance. Wipe off any excess amounts of adhesive that may have come through the seams with a damp cloth. If needed, use a solvent such as Isopropyl Alcohol or Odorless Mineral Spirits to remove adhesive that has dried. Never scrape adhesive, as scraping may cause damage to the wall base. Initial maintenance and normal maintenance procedures are as follows:

- Wall base and Accessories are maintained by hand.
- Wash with a wet cloth or wet mop. Use a neutral pH cleaner.

transforming performance.



- Rinse with clear water.
- You may wipe with dry cloth or let air dry.
- Clean as needed.

Wall Base – Limited Warranty

Shaw Industries ("Shaw") conditionally warrants that products will be free from defects caused by (i) the raw materials used in production of Shaw products and (ii) manufacturing workmanship during the manufacturing of Shaw products for the following specified periods after purchase.

The following products will carry a five-year warranty*

- Wall Base

*Free from manufacturing defects related to manufacturing workmanship and materials.

EXCLUSIONS: The following are not covered by this warranty

- Damage caused by improper installation and/or maintenance
- Differences in color between products and samples or photographs
- Discoloration, including but not limited to U.V. light and heat sources
- Surface scratches, changes in shading, texture and/or gloss during use
- Inappropriate end-user activities
- Construction or installation-related damage
- Damage caused by fire, flooding or intentional abuse

PLEASE VISIT PATCRAFT.COM FOR THE COMPLETE INSTRUCTIONS FOR INSTALLATION & MAINTENANCE AND FOR THE FULL WARRANTY DETAILS.

transforming performance.



PO Box 2128 | Dalton, GA 30722-2128 | patcraft.com | 800.241.4014