

### What the Experts Say:



#### U.S. Environmental Protection Agency

"Moisture control is the key to mold control."

"Fix the source of the water problem to prevent mold growth."

"If mold is a problem in your home or school, you must eliminate sources of moisture."



#### Centers for Disease Control and Prevention

"These health effects can be prevented by making dampness prevention a goal."



#### Responsible Solutions to Mold Coalition

"If mold-resistant products are installed improperly, they offer little protection from the eventual growth of mold. Mold will grow on anything."



## Trapped moisture + stagnant air = MOLD RISK.

### Don't create a mold environment by trapping water and air under floors.

- Loose-lay installations do NOT prevent moisture intrusion and can create air space under floors where mold is likely to grow
- Hiding slab moisture problems below loose-lay flooring promotes mold
- Mold can grow on ANY surface, including concrete surfaces under flooring



## Eliminate the risk of mold under flooring with full-spread, high-moisture tolerant adhesive.

### Stop moisture AND eliminate cavities below flooring where mold thrives.

- Prevent water and air from becoming trapped under floors
- Install high-moisture tolerant adhesives to stop moisture intrusion
- Fully adhere the entire floor to the concrete slab without gaps or voids

**Dry-Tex™**  
S Y S T E M

Full-spread to 98% RH

**Gerfix**  
SPRAY ADHESIVE

Full-spread to 90% RH



Eliminate trip hazards by reducing the risk of curling and shifting associated with loose-lay installation.

Avoid the risk of loose-lay. Full-spread adhesives prevent floors from shifting or moving.



Gerflor adhesives are the safest and most eco-friendly available.

Gerfix Spray, Gerfix TPS+ and Gerpur for Dry-Tex are:

✓ **Recommended full-spread coverage for multi-purpose rooms**

No risk of trip hazards due to curling or shifting from rolling loads.  
No risk of trapped moisture or mold.

✓ **100% Solvent Free**

Completely free of potentially harmful chemical solvents.

✓ **Low VOC**

Certified to emit low levels of volatile organic compounds per rule 1168 of California SCAQMD and EPA test method 8260B.

✓ **LEED v3 IEQ / LEED v4 IEQ Credit**

Helps contribute to LEED project points for low-emitting adhesives.

✓ **Manufactured in an ISO 14001 certified facility**

International certification regarding manufacturing facilities' environmental impacts.

Gerflor adhesives have been supplied on multiple LEED Gold and Platinum projects.