

Ascend™ Elevator Protection Systems

Suggested Specifications



- Palladium Beveled Edge Panels - Superior impact resistance on panel face and edges
- Ascend clip mounting system - Quick and easy installation of panels and reveals
- Complete system (panels, trim, ceilings and handrail) - One source for easy ordering
- Class A fire-rating - Meets code requirements for elevator cab interiors

IPC.1849/REV.3

Installation Hotline • 866.EZINPRO
Inprocorp.com • 800.222.5556 • 262.679.9010
World Headquarters S80 W18766 Apollo Drive, Muskego, WI 53150 USA

ASCEND™ •
ELEVATOR PROTECTION SYSTEMS
A DIVISION OF INPRO®

Ascend™ Elevator Protection Systems

Suggested Specifications

PART 1 - GENERAL

1.01 SUMMARY

A. Ascend™ Elevator Protection System

1.02 SECTION INCLUDES

A. Elevator interior finish system with Palladium® beveled edge panels

1.03 REFERENCES

- A. American Society for Testing and Materials (ASTM)
- B. National Fire Protection Association (NFPA)
- C. Society of Automotive Engineers (SAE)

1.04 SYSTEM DESCRIPTION

A. Performance Requirements: Provide Ascend™ Elevator Protection Systems that conform to the following requirements of regulatory agencies and the quality control InPro Corporation.

- 1. Fire Performance Characteristics: Provide Palladium® Panels conforming with the NFPA Class A fire rating. Surface burning characteristics as determined by ASTM E-84 shall be flame spread of 15 and smoke developed of 400.
- 2. Chemical and Stain Resistance: Provide rigid vinyl that shows resistance to stain when tested in accordance with applicable provisions of ASTM D-543.
- 3. Fungal and Bacterial Resistance: Provide rigid vinyl that does not support fungal or bacterial growth as tested in accordance with ASTM G-21 and ASTM G-22.
- 4. Color Consistency: Provide components matched in accordance with SAE J-1545 - (Delta E) with a color difference no greater than 1.0 units using CIE Lab, CIE CMC, CIE LCh, Hunter Lab or similar color space scale systems.
- 5. GREENGUARD Certified: Provide GREENGUARD Certified material. Panels, trim pieces and reveals shall meet the requirements of GREENGUARD Certification Standards for Low-Emitting Products and GREENGUARD Product Emission Standard for Children & Schools.
- 6. System Impact Resistance: Provide a panel system that resists impact as tested in accordance with applicable provisions of ASTM F 476-84, paragraph 18.
- 7. Stainless Steel: Provide stainless steel components that conform to ASTM A240/ A240M Standard Specification for Chromium and Chromium-Nickel Stainless Steel Plate, Sheet and Strip for Pressure vessels and for General Applications.
- 8. Aluminum: Provide aluminum extrusions that conform to ASTM B221 Standard Specification for Aluminum and Aluminum-Alloy Extruded Bars, Rod Wire, Profiles and tubes.

1.05 SUBMITTALS

A. Product Data: Manufacturer's printed product data for each type of Ascend™ Elevator Protection

System specified.

- B. Detail Drawings: Mounting details with the appropriate fasteners for specific project substrates.
- C. Samples: Verification samples of Palladium® Wall Panel, 6" (152mm) square, of each type and color indicated.
- D. Manufacturer's Installation Instruction: Printed installation instructions for Ascend™ Elevator Protection Systems.

1.06 DELIVERY, STORAGE AND HANDLING

- A. Deliver materials in unopened factory packaging to the jobsite
- B. Inspect materials at delivery to assure that specified products have been received.
- C. Store in original packaging in a climate controlled location away from direct sunlight.

1.07 PROJECT CONDITIONS

A. Environmental Requirements: Products must be installed in an interior climate controlled environment.

1.08 WARRANTY

A. Standard Ascend™ Limited Lifetime Warranty against material and manufacturing defects.

PART 2 - PRODUCTS

2.01 MANUFACTURER

- A. Acceptable Manufacturer: Ascend™ Elevator Protection Systems, InPro Corporation, PO Box 406 Muskego, WI 53150 USA; Telephone: 800.222.5556, Fax: 888.715.8407, www.inprocorp.com
- B. Substitutions: Not permitted
- C. Provide all Ascend™ Elevator Protection Systems and IPC wall protection from a single source.

2.02 MANUFACTURED UNITS

- 1. Zenith: Provide elevator interior finish system that shall include 7 or 9 vertical Inpro® wall panels. Inpro® Panel System shall have .375" (9.5 mm) thick particleboard panels having a .040" thick PVC front and back surface. Panels shall be constructed of rigid vinyl sheet permanently bonded to front surface and edges of particleboard. Edges shall be bonded with "EPT" Edge Protection Technology.
 - a. Elevator interior finish system shall include: Stainless steel toe kick – 4.25" (108mm), stainless steel reveals - ¾" (19mm), stainless steel corners - 1¾" (44mm), stainless steel friezes 6.0" (152mm)
 - b. Options shall include stainless steel handrails/ wall guards and ceilings/ceiling lights/battery backup.
- 2. Titan: Provide elevator interior finish system that shall include 14 or 18 vertical Inpro® wall panels and stainless steel handrail panels. Inpro®

Panel System shall have .375" (9.5 mm) thick particleboard panels having a .040" thick PVC front and back surface. Panels shall be constructed of rigid vinyl sheet permanently bonded to front surface and edges of particleboard. Edges shall be bonded with "EPT" Edge Protection Technology.

- a. Elevator interior finish system shall include: Stainless steel toe kick – 4.25" (108mm), Stainless steel reveals - ¾" (19mm), stainless steel corners - 1¾" (44mm), stainless steel friezes - 6.0" (mm).
- b. Options shall include stainless steel handrails/ wall guards,) and stainless steel handrail panel – 10" (254mm) and ceilings/ceiling lights/battery backup.

3. Columba: Provide elevator interior finish system that shall include 12 horizontal Inpro® wall panels. Inpro® Panel System shall have .375" (9.5 mm) thick particleboard panels having a .040" thick PVC front and back surface. Panels shall be constructed of rigid vinyl sheet permanently bonded to front surface and edges of particleboard. Edges shall be bonded with "EPT" Edge Protection Technology.

- a. Elevator interior finish system shall include: Stainless steel toe kick – 4.25" (108mm), stainless steel reveals - ¾" (19mm), stainless steel corners - 1¾" (44mm), stainless steel friezes 6.0" (152mm)
- b. Options shall include stainless steel handrails/ wall guards and ceilings/ceiling lights/battery backup.

4. Hercules: Provide elevator interior finish system that shall include 9 horizontal Inpro® wall panels and stainless steel handrail panels. Inpro® Panel System shall have .375" (9.5 mm) thick particleboard panels having a .040" thick PVC front and back surface. Panels shall be constructed of rigid vinyl sheet permanently bonded to front surface and edges of particleboard. Edges shall be bonded with "EPT" Edge Protection Technology.

- a. Elevator interior finish system shall include: Stainless steel toe kick – 6" (152mm), Stainless steel reveals - ¾" (19mm), stainless steel corners - 1¾" (44mm), stainless steel friezes - 6.0" (152mm).
- b. Options shall include stainless steel handrails/ wall guards,) and stainless steel handrail panel – 10" (254mm) and ceilings/ceiling lights/battery backup.

5. Orion: Provide elevator interior finish system that shall include 10 or 12 vertical upper and horizontal lower Inpro® wall panels and stainless steel handrail panel. Inpro® Panel System shall have .375" (9.5 mm) thick particleboard panels having a .040" thick PVC front and back surface. Panels shall be constructed of rigid vinyl sheet permanently bonded to front surface and edges of particleboard. Edges shall be bonded with "EPT" Edge Protection Technology.

- a. Elevator interior finish system shall include: Stainless steel toe kick – 4.25" (108mm), stainless steel reveals - ¾" (19mm), stainless steel corners -

Installation Hotline • 866.EZINPRO

Inprocorp.com • 800.222.5556 • 262.679.9010

World Headquarters S80 W18766 Apollo Drive, Muskego, WI 53150 USA

ASCEND™
ELEVATOR PROTECTION SYSTEMS
A DIVISION OF INPRO®

Ascend™ Elevator Protection Systems

Suggested Specifications

1¾" (44mm), stainless steel friezes 6.0" (152mm)
b. Options shall include stainless steel handrails/wall guards and ceilings/ceiling lights/battery backup.

6. Vela: Provide elevator interior finish system that shall include 10 or 12 vertical upper and horizontal lower Palladium panels with a stainless steel handrail panels. Inpro® Panel System shall have .375" (9.5 mm) thick particleboard panels having a .040" thick PVC front and back surface. Panels shall be constructed of rigid vinyl sheet permanently bonded to front surface and edges of particleboard. Edges shall be bonded with "EPT" Edge Protection Technology.

a. Elevator interior finish system shall include: Stainless steel toe kick – 4.25" (108mm), Stainless steel reveals – ¾" (19mm), stainless steel corners – 1¾" (44mm), stainless steel friezes – 6.0" (152mm).

b. Options shall include stainless steel handrails/wall guards,) and stainless steel handrail panel – 10" (254mm) and ceilings/ceiling lights/battery backup.

7. Corvus: Provide elevator interior finish system that shall include 21 or 27 vertical Inpro® wall panels. Inpro® Panel System shall have .375" (9.5 mm) thick particleboard panels having a .040" thick PVC front and back surface. Panels shall be constructed of rigid vinyl sheet permanently bonded to front surface and edges of particleboard. Edges shall be bonded with "EPT" Edge Protection Technology.

a. Elevator interior finish system shall include: Stainless steel toe kick – 4.25" (108mm), stainless steel reveals – ¾" (19mm), stainless steel corners – 1¾" (44mm), stainless steel friezes 6.0" (152mm)

b. Options shall include stainless steel handrails/wall guards and ceilings/ceiling lights/battery backup.

8. Nova: Provide elevator interior finish system that shall include 7 or 9 vertical stainless steel formed edge panels. Inpro® Stainless Panel System shall have .375" (9.5 mm) thick particleboard panels having. Panels shall be constructed of 18 gauge stainless steel sheet permanently bonded to front surface and edges of particleboard.

a. Elevator interior finish system shall include: Stainless steel toe kick – 4.25" (108mm), stainless steel reveals – ¾" (19mm), stainless steel corners – 1¾" (44mm), stainless steel friezes 6.0" (152mm)

b. Options shall include stainless steel handrails/wall guards and ceilings/ceiling lights/battery backup.

B. Ascend™ Elevator Cab Ceiling Systems

1. Black welded steel frame w/stainless steel panels and LED lamps. Battery back-up is included.

2. Stainless Steel Pan ceiling with 1, 2, or 3 stainless steel panels and LED lamps. Battery backup is included.

3. Stainless Steel Island ceiling with 6 or 9

stainless steel panels and LED lamps. Battery backup is included.

C. Ascend™ Elevator Cab Handrails/Wall Guards

1. Flat, ¼" (6.35mm) x 2" (51mm).

Specify location: back wall, side walls, or all walls. Specify end style: returned ends, straight ends.

2. Flat, 3/8" (9.5mm) x 2" (51mm).

Specify location: back wall, side walls, or all walls. Specify end style: returned ends, straight ends.

3. Flat, 3/8" (9.5mm) x 3" (76mm).

Specify location: back wall, side walls, or all walls. Specify end style: returned ends, straight ends.

4. Flat, 3/8" (9.5mm) x 4" (102mm).

Specify location: back wall, side walls, or all walls. Specify end style: returned ends, straight ends.

5. Flat, 3/8" (9.5mm) x 6" (152mm).

Specify location: back wall, side walls, or all walls. Specify end style: returned ends, straight ends.

6. Extruded, 3" (75mm) x .5" (13mm) .

Specify location: back wall, side walls, or all walls. Specify end style: returned ends

7. Round, 1-1/2" (38mm) diameter.

Specify location: back wall, side walls, or all walls. Specify end style: returned ends, straight capped ends.

8. Round with bullet vault bracket, 1-1/2" (38mm) diameter.

Specify location: back wall, side walls, or all walls. Specify end style: returned ends, straight ends, rounded (bullet) ends.

9. Round with flat vault bracket, 1-1/2" (38mm) diameter.

Specify location: back wall, side walls, or all walls. Specify end style: returned ends, straight ends, rounded (bullet) ends.

10. Oval, 1.9" (48mm) x 1" (25mm).

Specify location: back wall, side walls, or all walls. Specify end style: returned ends, straight ends.

D. Ascend™ Elevator Cab Mounting Clips

1. Ascend™ components shall be installed with a unique clip system that allows fasteners and seams to be hidden. Reveal strip shall cover fasteners and prevent tampering.

2.03 MATERIALS

A. Palladium® Wall Panel System: Panels shall be made from .040" IPC Rigid Sheet factory bonded to particleboard. Particleboard shall have No Added Urea Formaldehyde.

B. Printed Wall Panels Square Edge Banding: Panels shall be made from .040" clear rigid PVC with printed image bonded to particle board with .0175" black PVC edge banding, and .040" IPC Rigid Sheet Backer. Particleboard shall have no added urea formaldehyde. PETG sheet shall be reverse printed by Inpro with customer supplied digital graphics. Sheet shall have a matte finish.

C. Vinyl: IPC Rigid Sheet shall be manufactured from chemical and stain resistant polyvinyl chloride with the addition of impact modifiers. No plasticizers shall be added (plasticizers may aid in

bacterial growth).

D. Stainless Steel: Stainless steel toe kicks, reveals, and corners shall be fabricated from type 304 stainless steel. Handrail panels, friezes, and ceiling panels shall be fabricated from type 430 steel. Toe kick shall be 16-gauge stainless steel. Frieze and handrail panel shall be 18-gauge stainless steel.

E. Aluminum: Aluminum attachment clips shall be fabricated from 6063-T5 extruded aluminum with a mill finish

F. Steel – Black welded steel frames shall be 1/8" (3.2mm) A36 Steel.

2.04 FINISHES

A. Color or pattern of Palladium® Panels to be selected by the architect from the Ascend™ finish selection. Surface shall have a velvet texture. Select patterns shall have a smooth texture.

B. Customer Supplied Digital Graphics: High definition digital files shall be reverse printed on clear PETG sheet and sealed with a protective backer. Customer to supply custom artwork, with copyright clearance. Adobe Illustrator (AI) or Encapsulated Postscript (EPS) artwork is preferred, but most raster file types (e.g. TIFF, JPEG) are acceptable. Raster files to be submitted at full scale, 300 dpi, in an uncompressed format.

C. Stainless Steel shall have a number 4 satin finish

D. Aluminum shall have a mill finish

E. Steel Ceiling Frame shall have a black powder coat finish.

PART 3 - EXECUTION

3.01 EXAMINATION

A. Examine areas and conditions in which the Ascend™ Elevator Protection System will be installed.

1. Complete all finishing operations, including painting, before beginning installation of panels.
B. Wall surface shall be dry and free from dirt, grease and loose paint.

3.02 PREPARATION

A. General: Prior to installation, clean substrate to remove dust, debris and loose particles.

3.03 INSTALLATION

A. General: Locate the Ascend™ Elevator Protection System as indicated on the approved detail drawing for the appropriate substrate and in compliance with the IPC installation instructions. Install level and plumb at the height indicated on the drawings.

3.04 CLEANING

A. At completion of the installation, clean surfaces in accordance with the IPC clean-up and maintenance instructions.

Installation Hotline • 866.EZINPRO

Inprocorp.com • 800.222.5556 • 262.679.9010

World Headquarters S80 W18766 Apollo Drive, Muskego, WI 53150 USA

ASCEND™
ELEVATOR PROTECTION SYSTEMS
A DIVISION OF INPRO®