

SPECIFICATIONS | ANTHOLOGY ABSTRACT

	CONSTRUCTION	LVT with micro-beveled edges
	STANDARD AVAILABLE SIZES (STYLE DEPENDENT)	4.5" x 36" (114 mm x 915 mm), 18" x 18" (457 mm x 457 mm), 18" x 36" (457 mm x 915 mm) Other sizes available - refer to brochure matrix for specific product sizes.
	OVERALL THICKNESS	0.098" (2.5 mm)
	WEAR LAYER THICKNESS	40 mil (1 mm)
	PIECES PER CARTON	40 pcs. of 4.5" x 36"; 20 pcs. of 18" x 18"; 10 pcs. of 18" x 36"
	COVERAGE PER CARTON	45 sq. ft. Depends on the product and product size
	WARRANTY	This product is backed by our Limited 20 Year Commercial Warranty and Limited 20 Year Quantum Guard® HP Wear Warranty.
	QUANTUM GUARD® HP	The highest performance commercial urethane finish in the industry. The patented aluminum oxide proprietary wear layer eliminates the need for polish, while enhancing durability, cleanability, appearance retention and slip retardance when compared to standard LVT floors - resulting in 70% annual savings in maintenance costs.
	QUICKSTIX™	LVT with pre-applied adhesive, reducing time and labor required to install the flooring. QuickStix™ floors can be used immediately after installation, even in extreme moisture areas.
	3RD PARTY CERTIFICATIONS	FloorScore, Industry wide 3rd party Type III EPD (Environmental Product Declaration)
	LEED	Mannington Commercial products may contribute to multiple LEED credits.
	US MANUFACTURING	Mannington is a fourth generation, family-owned company deeply committed to U.S. manufacturing. We make flooring in seven communities across the U.S., allowing us to provide the highest levels of service and quality in the industry, while supporting local economies and crafting quality, American-made products.
	RAPIDLY RENEWABLE CONTENT	Contains 4% rapidly renewable resource content.
	STATIC LOAD LIMIT	750 PSI
	SPECIFICATION (ASTM F1700)	Class III Type A & B
	HEAT STABILITY (ASTM F1514)	Passes
	STAIN & CHEMICAL RESISTANCE (ASTM F925)	Passes
	HUD/FHA REQUIREMENTS	Exceeds
	AMERICANS WITH DISABILITIES ACT GUIDELINES (ADAG)	Meets or exceeds ADA Guidelines
	COEFFICIENT OF FRICTION (COF)	≥ 0.5 Leather; 0.6 Rubber
	FLOORING RADIANT PANEL (ASTM E648)	≥ 0.45 watts/cm2, Passes (Class 1)
	N.B.S. SMOKE CHAMBER TEST (ASTM E662)	< 450-Passes
	INSTALLATION ADHESIVE	Porous & Non-Porous Substrates: Amtico High Pressure Sensitive, Full Spread / RH 90%, MVER 8, pH5-9; Amtico 373, Full Spread / RH 80%, MVER 5, pH 7-10; XpressStep for LVT Spray Adhesive / RH 90%, MVER 8, pH11; XpressStep Premium Spray Adhesive / RH 93%, MVER 10, pH12. Non-Porous Substrates or where higher performance is required: Amtico Universal, Full Spread, 2 Part Urethane / RH 80%, MVER 5, pH 7-10. Under Hospital Beds and Heavy Rolling Loads: Amtico Universal, Full Spread, 2 Part Urethane / RH 80%, MVER 5, pH 7-10; XpressStep for LVT Spray Adhesive / RH 90%, MVER 8, pH11; XpressStep Premium Spray Adhesive / RH 93%, MVER 10, pH12 / QuickStix™ pre-applied adhesive / 99% RH, MVER 18, pH12.