

PHYSICAL CONSTRUCTION:

CONSTRUCTION:	Tip Sheared Patterned Loop
FACE FIBER:	Ultron Type 6,6 Nylon, with Patented Mixed Denier / Mixed Cross Section Fiber Design
DYE METHOD:	Piece
GAUGE:	5/64
STITCHES PER INCH:	11
PILE THICKNESS:	.157 Inches
TUFTED YARN WEIGHT:	28 Ounces Per Square Yard
DENSITY:	Average Density = 6,420; Weight Density = 179,770
PRIMARY BACKING:	100% Synthetic
SECONDARY BACKING:	UltraBac RE with Minimum 10% Recycled Content and Lifetime Warranty Standard
STANDARD SIZE:	12' 6" Width
PATTERN REPEAT:	18 3/4" W x 22 1/2" L

ENVIRONMENTAL:

RECYCLED CONTENT:	Minimum 10% Post-Consumer Recycled Content by Total Product Weight*
MANUFACTURE LOCATION:	Calhoun, Georgia 30701 USA
NSF / ANSI-140 CERTIFICATION:	Platinum
CRI GREEN LABEL PLUS ID:	GLP0678

WARRANTIES:

WARRANTY:	Lifetime Limited Warranty, Covering Face Wear, Delamination, Tuft Bind, Unraveling, and Static Protection
STAIN RESISTANT WARRANTY:	XGUARD with 15 Year Limited Warranty Against Staining

PRODUCT TESTING:

RADIANT PANEL (ASTM E-648):	Class I (Direct Glue)
SMOKE CHAMBER (ASTM E-662):	Less than 450 (Flaming Mode)
METHENAMINE PILL TEST (ASTM D-2859):	Passes
ELECTROSTATIC PROPENSITY (AATCC 134):	Less than 3.0 KV

RECOMMENDED ADHESIVE:

MULTI-PURPOSE ADHESIVE:	Mannington Ultra Adhesive
CRI GREEN LABEL PLUS ID:	GLP70513
VOC LIMITS:	Meets SCAQMD Rule #1168
BOND WARRANTY:	10 Year Limited Warranty When Used With Mannington UltraBac RE Carpet

Specifications are subject to normal manufacturing variances. Specifications are subject to change without notice when technological advancements provide improved product performance.

* Most products contain a higher percentage of recycled content than the minimums listed above. Please contact Mannington Technical Services at 1-800-241-2262 for updated, specific recycled content percentages for each product.