Professional Testing Laboratory, Inc.

TEST REPORT

DATE: 04/12/2012 **TEST NUMBER**: 146901

CLIENT	Masland Carpets

TEST METHOD CONDUCTED	Surface Flammability of Carpets and Rugs (16 CFR Chapter II, Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D2859

DESCRIPTION OF TEST SAMPLE	
IDENTIFICATION	7476 Botanique
COLOR	74600 Barnsdale
ROLL	0072769401
CONSTRUCTION	Multi-Level Cut & Loop Pile
BACKING	Woven Synthetic

GENERAL PRINCIPLE

This test method is intended to measure the response of finished textile floor covering materials when exposed to an ignition source under controlled laboratory conditions. It is applicable to all types of textile floor coverings whether constructed from natural or man-made materials.

TEST CRITERION

The uncharred area of the test specimen must be greater than one inch in at least seven of the eight specimens tested in order to meet the acceptance criterion.

TEST RESULTS

	SPECIMEN NUMBER							
	1	**2**	**3**	**4**	**5**	**6**	**7**	**8**
Uncharred Area (Inches)	3.5	3.5	3.6	3.5	3.4	3.6	3.5	3.5

NOTE: This sample was tested on the face side.

This sample *PASSES* the Federal Flammability Standard DOC FF 1-70.

APPROVED BY: Gary Calvery

NVLAP®

714 Glenwood Place Dalton, GA 30721 Phone: 706-226-3283 Fax: 706-226-6787 email: protest@optilink.us