

## Construction specifications

Product	Tansu
Style #	7219
Fiber Content	Antron® Legacy nylon
Fiber Weight (tufted)	36 oz./Sq. Yd. (1220 g/m <sup>2</sup> )
Construction	Tip Sheared Loop Pattern
Pattern Repeat	.5" W x .5"L (1.27 cm x 1.27 cm)
Dye Method	Beck Dyed
Gauge	1/10
Width	12' (3.66)
Pile Height	.406" / .125"
Total Weight	82 oz./Sq. Yd. (2780 g/m <sup>2</sup> )

## Performance specifications

Flammability Rating:	Flooring Radiant Panel ASTM E-648 and/or NFPA 253. Greater than 0.45 watts / CM <sup>2</sup> Class 1. (EU) CFL S1
Smoke Density:	Passes NBS Smoke Chamber Test ASTM E-662
Colorfastness	4.0 or better
Static Rating:	Less than 3.0 kV
Warranty:	10 year warranty
Primary Backing	Woven Polypropylene
Secondary	Woven Polypropylene
DuraTech® Soil Resistant Treatment:	A commercially durable treatment provides extra protection against soiling.

Tufted fiber weight denotes specs prior to tip shearing. Tip Shearing removes a small amount of fiber, which will vary slightly by product and production run.

This product is certified GOLD by the NSF 140-2007 Sustainable Carpet Standard.



Tansu meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Carpet Testing Program. Certification # GLP#2950.

All Masland Designs are protected under the U. S. Copyright Act of 1976. Any unauthorized duplication or approximation of a Masland design constitutes copyright infringement in violation of Federal Law.