Architectural Remnants[™] Coastal Living[™] Patina Rustics[™] Premium | Premium Lustre | Premium





Armstrong offers design flexibility with the best visuals and overall performance in laminate flooring. Armstrong's moisture resistant HydraCore™ Plus core provides stability and lasting durability. Armstrong's wear resistant VisionGuard™ Commercial layer protects against spills, stains and fading. The back layer provides balance and moisture resistance. Whether you choose to create a mood of exotic flair or a warm home-like environment, you can count on rich color, texture and the realistic look of natural hardwood flooring – Armstrong has the broadest selection of wood looks for your space.

PR	ODUCT INFORMATION			
Construction		Laminate		
Product Line		Architectural Remnants Coastal Living Patina Rustics Premium Premium Lustre Premium		
International Product Specifications		EN 13329		
Overall Thickness		0.47 in. (12 mm) (nominal)		
Edge/End Detail		Micro-beveled edges and ends		
Installation		Lock&Fold®, floating or glue down		
Maintenance Options		Armstrong Hardwood & Laminate Floor Cleaner		
PA	CKAGING			
Plank Size		Contact Techline - www.armstrong.com/commflooringna/flooring-techline.html		
Square Feet per Carton		Contact Techline - www.armstrong.com/commflooringna/flooring-techline.html		
Carton Weight		Contact Techline – www.armstrong.com/commflooringna/flooring-techline.html		
Shipping Weight		Contact Techline - www.armstrong.com/commflooringna/flooring-techline.html		
PE	RFORMANCE	TEST METHOD	MINIMUM REQUIREMENT	PERFORMANCE VS. REQUIREMENT
	Thickness Swell	EN 13329	5.5%	Meets
	Light Stability	EN 438-2.16	No Change	Meets
1700	Stain Resistance	EN 438-2.15	Group 4; Excellent Resistance	Meets
ш	Impact Resistance	EN 13329	≥ IC 1	Meets
ASTM	Wear Resistance (Taber Abrasion)	EN 13329	IP Class 5; > 6,000	Meets
ğ	Slip Resistance	ASTM D 2047	> 0.50 static coefficient of friction	Meets
	Formaldehyde Emissions	ASTM E-1333-96	CARB Phase I or CARB Phase II Compliant	Meets
	Static Load Limit - Subjective Visual	ASTM F 970 ASTM F970 modified	0.0 in. @ 125 psi 0.0 in. @ 1500 psi	Meets
Supplementary	Fire Test Data - Flame Spread	ASTM E 648	0.45 watt/cm² or more Class I	Meets
	Fire Test Data - Smoke Evolution	Class I when tested in accordance to ASTM E 662 or NFPA 253	450 or less	Meets
	Sound Test: Impact Insulation Class (in room) 1" Gyp-crete over plywood subfloor/ceiling assembly	ASTM E 492 Classified by E 989	S-1836 Quiet Comfort Premium™: STC above 60; IIC over 6 in. concrete slab above 60*	Meets
	Sound Test: Sound Transmission Class (in room) 1" Gyp-crete over plywood subfloor/ceiling assembly	ASTM E 90 Classified by E 413	S-1836 Quiet Comfort Premium™: STC above 60; IIC over 6 in. concrete slab above 60*	Meets
	Low Emitting Materials	CARB Phase II	Meets Guidelines	Meets
WARRANTY				
15-Year (Premium Lustre and Premium only) and 10-Year Commercial Warranty when installed and maintained in accordance with Armstrong's recommended installation and maintenance procedures.				
LINKS				
Installation Instructions - http://www.armstrong.com/pdbupimages/2127188114.pdf				
Maintenance Information - http://www.armstrong.com/pdbupimages/197959.pdf				
View the Full Line - http://www.armstrong.com/commflooringna/products/commercial-laminate				
Email Techline - http://www.armstrong.com/commflooringna/contact_techline.jsp				





Architectural Remnants™ Coastal Living™ Patina Rustics™ Premium | Premium Lustre | Premium



COMMERCIAL FLOORING







Architectural Remnants

Woodland Reclaim







Structure Saw Mark Oak

Antique







Skip Planed L3106





L3081 L3082

Rustics™ Premium

X-Grain









American Chestnut L6604

Reclaimed









Premium



L8705





L0242













