

S-288 Premium Vinyl Sheet Flooring Adhesive



CAUTION

S-288 EYE AND SKIN IRRITANT

STIR WELL BEFORE USING.

For use with the following Installation Systems:

- Fiberglass-Reinforced Sheet Flooring
- ToughGuard II
- Alterna
- Residential LVT Planks
- Commercial Luxury Vinyl Tile Flooring

DESCRIPTION:

Type:	Water-based rubber resin
Color:	Creamy beige
Taggants:	Yes – green glitter
Trowel:	S-891 Notched Steel Trowel or S-892 Replaceable Blade Trowel; Fine notch – (1/32" deep, 1/16" wide, 5/64" apart), U-notch
Coverage:	250-300 sq. ft. /gallon (23-28 sq. m.)
Units:	1 gallon (3.78 L) and 4 gallons (15.14 L)
Open Time:	Porous substrates – Set-in-wet: Minimum 10-20 minutes Nonporous substrates – Dry-to-touch: 30 minutes or more
Working Time:	Up to 1 hour (working times may vary based on job conditions, substrates, temperature, and humidity)
Shelf Life:	2 years, unopened
Freeze/Thaw Stable:	Yes, to 10° F (-12° C)
VOC Content:	< 14 g/L; calculated and reported, SCAQMD 1168
Clean Up:	Wet – clean, white cloth with neutral detergent and water Dry – clean, white cloth and mineral spirits
Subfloors:	All grade levels of concrete, existing resilient floors, ceramic, terrazzo, marble, steel, stainless steel, aluminum, polymeric poured floors, and suspended wood

Advantages:

For Full Spread Installation Systems

Moisture and alkali resistant

Strong, early grab

Armstrong Guaranteed Installation System (AGIS)
Guarantee included as part of Armstrong Installation
System when installing Armstrong vinyl-back sheet
flooring and residential Luxury Vinyl Tile

Nonflammable, ammonia-free and low odor; contains low
or no organic solvents

Contains no reportable hazardous substance (per current
regulations)