

S-725 Wall Base Adhesive

⚠ CAUTION S-725 **EYE AND SKIN IRRITANT**

STIR WELL BEFORE USING.

For use with the following Installation System:

- WALL BASE, RISERS, and Vinyl TRANSITION STRIPS

DESCRIPTION:

Type:	Water-based/rubber-resin
Color:	Off-white
Taggants:	Yes – 50% yellow and 50% orange
Trowel:	1/16" deep, 1/16" wide, 3/32" apart), U-notch
Coverage:	2-1/2" WALL BASE: 375-425 lin. ft./gal (114-130 m. lin.) 4" WALL BASE: 300-350 lin. ft./gal (91-107 m. lin.) 6" WALL BASE: 200-250 lin. ft./gal (61-76 m. lin.) 7" RISER: 200-250 lin. ft./gal (61-76 m. lin.) 11-oz cartridge – 4": 1/8" bead – 18 lin. ft. (5.5 m. lin.) 30-oz cartridge – 4": 1/8" bead – 50 lin. ft. (15.2 m. lin.)
Units:	11-oz cartridge (311.8 grams) 30-oz cartridge (950.4 grams) quart (946 ml) gallon (3.78 L) 4 gallons (15.14 L)
Open Time:	None recommended
Working Time:	Up to 15 minutes
Shelf Life:	1 year, unopened
Freeze/Thaw Stable:	Yes, to 10° F (-12° C)
VOC Content:	Zero g/L; calculated and reported, SCAQMD 1168
Clean Up:	Wet – clean, white cloth with neutral detergent and water Dry – clean, white cloth and mineral spirits
Walls:	Structurally sound and dry wall surfaces

Advantages:	Moisture and alkali resistant
	Good wet strength
	Excellent bond integrity
	Versatile (use for rubber or vinyl WALL BASE)
	AGIS Guarantee
	Nonflammable