

S-750 Premium Tile Flooring Adhesive

⚠ CAUTION S-750 **EYE AND SKIN IRRITANT**

STIR WELL BEFORE USING.

For use with the following Installation Systems:

- Commercial Vinyl Composition Tile
- Residential Dry Back Vinyl Tile
- Primer for wood and concrete with self-adhering tile

DESCRIPTION:

Type:	Water-based/rubber resin
Color:	Cream
Taggants:	Yes – 50% yellow and 50% orange
Trowel:	S-891 Notched Steel Trowel or S-892 Replaceable Blade Trowel; fine notch (1/32" deep, 1/16" wide, 5/64" apart), U-notch To apply as a primer, use a brush or medium-nap roller
Coverage:	275–350 sq. ft. /gallon (26-33 sq. m.) Brush or roller (Primer): 350–400 sq. ft./gallon (33-37 sq. m.)
Units:	1 quart (946 mL), 1 gallon (3.78 L) and 4 gallons (15.14 L)
Open Time:	Until dry-to-touch: approximately 30 minutes or more
Working Time:	Up to 6 hours (working times may vary based on job conditions, substrates, temperature, and humidity)
Shelf Life:	1 year, unopened
Freeze/Thaw Stable:	No, keep from freezing
VOC Content:	5 g/L; calculated and reported, SCAQMD 1168
Clean Up:	Wet – clean, white cloth with neutral detergent and water Dry – clean, white cloth and mineral spirits
Subfloors:	All grade levels of concrete, existing resilient floors, ceramic, terrazzo, marble, polymeric poured floors, and suspended wood
Advantages:	Can be used over “cutback” adhesive residue Moisture and alkali resistant Strong, early grab AGIS Guarantee Nonflammable, ammonia-free and low odor Contains low or no organic solvents