

SCS Global Services does hereby certify that an independent assessment has been conducted on behalf of:

Armstrong Flooring, Inc.

630 Industry Rd., Somerset, KY; 1735 Washington St., Vicksburg, MS

For the following product(s):

See Addendum

The product(s) meet(s) all of the necessary qualifications to be certified for the following claim(s):

FloorScore®

Indoor Air Quality Certified to SCS-EC10.3-2014 v4.0

Conforms to the CDPH/EHLB Standard Method v1.2-2017 (California Section 01350), effective April 1, 2017, for the school classroom and private office parameters when modeled as Flooring.

Measured Concentration of Total Volatile Organic Compounds (TVOC): Less than/equal to 0.5 mg/m³ (in compliance with CDPH/EHLB Standard Method v1.2-2017)

Registration # SCS-FS-03647

Valid from: September 1, 2017 to August 31, 2018

SCS Global Services is currently the only certification body approved by the Resilient Floor Covering Institute (RFCI) to provide FloorScore® product certification; certified products are only listed on the SCS Green Products Guide, <http://www.scsglobalservices.com/certified-green-products-guide>.



ANSI Accredited Program
Product Certification
#0821



A handwritten signature in black ink that reads "Stanley Mathuram".

Stanley Mathuram, PE, Vice President
SCS Global Services
2000 Powell Street, Ste. 600, Emeryville, CA 94608 USA

Certification Addendum

Armstrong Flooring, Inc.

Certification: Registration # SCS-FS-03647 | Valid from: September 1, 2017 to August 31, 2018

SCS Global Services is currently the only certification body approved by the Resilient Floor Covering Institute (RFCI) to provide FloorScore® product certification; certified products are only listed on the SCS Green Products Guide, <http://www.scsglobalservices.com/certified-green-products-guide>.

Addendum **FloorScore®**

Indoor Air Quality Certified to SCS-EC10.3-2014 v4.0

Conforms to the CDPH/EHLB Standard Method v1.2-2017 (California Section 01350), effective April 1, 2017, for the school classroom and private office parameters when modeled as Flooring.

Measured Concentration of Total Volatile Organic Compounds (TVOC): Less than/equal to 0.5 mg/m³ (in compliance with CDPH/EHLB Standard Method v1.2-2017)

Products: **Engineered Hardwood:**

Armstrong Flooring:

Traditional Engineered 3/8": Beaumont Plank, Beckford Oak

Traditional Engineered 1/2": Artesian Hand Tooled; Artistic Timbers TimberBrushed; Fifth Avenue™ Plank – 3", 5", 7" mix; Metro Classics – Birch 3", 5"; Metro Classics – Pecan 3", 5"; Metro Classics – Maple 3", 5"; Metro Classics – Cherry 3", 5"; Metro Classics – Walnut 3", 5"; Rustic Accents; Woodland Relics™

Distressed Engineered 3/8": Blackwater Classics – Cherry; Blackwater Classics – Walnut; Heritage Classics – Oak 3", 5"; Heritage Classics – Hickory 5"

Hand Scraped Engineered 1/2": Rural Living – Hickory 5"; Rural Living – Maple 5"; Century Farms – Birch 5"; Century Farms – Hickory 5"; Century Farms – Maple 5"; Century Farms – Cherry 5"; Century Farms – Walnut 5"; American Scrape Walnut 5.75"; American Scrape Cherry 5.75"; American Scrape Maple 5.75"; American Scrape™ Hickory 5.75"; American Scrape™

Certification Addendum

Armstrong Flooring, Inc.

Certification: Registration # SCS-FS-03647 | Valid from: September 1, 2017 to August 31, 2018

SCS Global Services is currently the only certification body approved by the Resilient Floor Covering Institute (RFCI) to provide FloorScore® product certification; certified products are only listed on the SCS Green Products Guide, <http://www.scsglobalservices.com/certified-green-products-guide>.

Addendum **FloorScore®**

Indoor Air Quality Certified to SCS-EC10.3-2014 v4.0

Conforms to the CDPH/EHLB Standard Method v1.2-2017 (California Section 01350), effective April 1, 2017, for the school classroom and private office parameters when modeled as Flooring.

Measured Concentration of Total Volatile Organic Compounds (TVOC): Less than/equal to 0.5 mg/m³ (in compliance with CDPH/EHLB Standard Method v1.2-2017)

Products: Birch 5.75"; Prime Harvest™ Engineered Hickory

Hand Scraped Engineered 3/8": American Scrape Hickory 5"

Specialty Engineered 1/2": Artesian Classics™ - Birch; Artesian Classics™ - Cherry; Artesian Classics™ - Maple; Artesian Classics™ - Walnut

Performance Plus™: Performance Plus - Red Oak, Performance Plus - White Oak (Low/high gloss), Performance Plus - Birch (Low/high gloss), Performance Plus - Maple (Low/high gloss), Performance Plus - Hickory, Performance Plus - Cherry (Low/high gloss), Performance Plus - Walnut (Low/high gloss)

Prime Harvest: Engineered Oak 3", Engineered Oak 5", Hickory 3", Hickory 5"

Bruce Flooring: Brushed Impressions, Frontier Birch (1/2"), Farmington (3/4" Maple), Bristol Trail (3/4" Oak)

Traditional 3/8" Engineered: Colony Oak, Summerside Oak 2 1/4", Springdale Oak 3", Turlington Oak 3",5", Turlington Maple II 3",5", Turlington Am. Exotics Birch 3",5", Turlington Am. Exotics Hickory 3",5", Turlington Am. Exotics Maple 3",5",

Certification Addendum

Armstrong Flooring, Inc.

Certification: Registration # SCS-FS-03647 | Valid from: September 1, 2017 to August 31, 2018

SCS Global Services is currently the only certification body approved by the Resilient Floor Covering Institute (RFCI) to provide FloorScore® product certification; certified products are only listed on the SCS Green Products Guide, <http://www.scsglobalservices.com/certified-green-products-guide>.

Addendum **FloorScore®**

Indoor Air Quality Certified to SCS-EC10.3-2014 v4.0

Conforms to the CDPH/EHLB Standard Method v1.2-2017 (California Section 01350), effective April 1, 2017, for the school classroom and private office parameters when modeled as Flooring.

Measured Concentration of Total Volatile Organic Compounds (TVOC): Less than/equal to 0.5 mg/m³ (in compliance with CDPH/EHLB Standard Method v1.2-2017)

Products: Turlington Am. Exotics Cherry 3",5", Turlington Am. Exotics Walnut 3", 5", Turlington Lock & Fold Oak 3",5", Turlington Lock & Fold Hickory 3",5", Turlington Lock & Fold Maple 3",5", Turlington Lock & Fold Cherry 5", Turlington Lock & Fold Walnut 5", Turlington Signature Collection Oak, Turlington Signature Collection Birch

Distressed 3/8" Engineered: Cavendar Plank Oak 3", Baltic Plank Oak 5", Rockwell Plank Oak 7", Amer. Originals Oak 5", Amer. Originals Hickory 5", Amer. Originals Maple 3",5", Am. Vintage Cherry 5", Am. Vintage Walnut 5", Amer. Originals Lock N Fold Oak 5", Amer. Originals Lock N Fold Maple 5"

Handscraped 3/8" Engineered: Legacy Manor Oak 5", Legacy Manor Maple 5", Frontier Collection Hick 5"

Capella® Flooring: Birch Scrape (3/8"), Hickory Scrape, Hickory Wire Brushed,
Added June 7, 2018: Capella Smooth, Specialty Engineered 1/2": Artesian Collective