

SHEETROCK®

Patching Plaster

Ideal for interior plaster repairs

- Non-shrinking
- Slow setting
- Easy sanding
- May be drilled, textured and painted



Description

SHEETROCK Patching Plaster is a workable, easy-to-decorate material for repair of interior plaster walls and ceilings. It is ideal for restoration on lath work and older plaster walls.

Surface Preparation

Surface should be free of all foreign material, dust, dirt and grease. Use a screwdriver to open narrow cracks to at least $\frac{1}{4}$ " wide. Dampen surface using sponge.

Mixing

Use clean water and equipment. Mix approximately two parts powder into one part water. Stir thoroughly; do not overthin. Mix only as much material as you can use within 60 minutes.

Application

Pack patching plaster into crack or damaged area. Finish flush with surface.

For cracks over 1" wide or $\frac{1}{4}$ " deep, apply a first coat to within $\frac{1}{4}$ " of surface. Allow to set 30 minutes. Apply additional material until patch is flush with surface. Texture to match surrounding area. Allow patch to dry completely before decorating.

Sand area using fine-grade sandpaper. You may now decorate repaired area.

Decorating

Interior walls may be painted or wallpapered as desired.

Cleanup

Clean tools and containers with soap and water immediately after use.

Packaging

Available in 4 lb. box and 25 lb. bag.

WARNING

When mixed with water, this material hardens and then slowly becomes hot. DO NOT attempt to make a cast enclosing any part of the body using this material. Failure to follow these instructions may cause severe burns that may require surgical removal of affected tissue. Avoid eye contact or inhalation of dust. Wear eye protection. If eye contact occurs, flush thoroughly with water for 15 minutes. If irritation persists, consult physician. If dry sanding or if dusty, wear a NIOSH/MSHA-approved respirator. Dust can cause eye, nose, throat or respiratory irritation. Avoid creating dust by wet sanding. Long-term breathing of large amounts of mica can cause lung disease. Do not ingest. If there is any discomfort call physician. Product safety information: (800) 507-8899.

KEEP OUT OF REACH OF CHILDREN.

Trademarks: The following trademarks used herein are owned by United States Gypsum Company or a related company: SHEETROCK, USG.

Note: Products described here may not be available in all geographic markets. Consult your U.S. Gypsum Company sales office or representative for information.

Notice: We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered.

For product information: (800) USG-4YOU (874-4968).

United States Gypsum Company

125 South Franklin Street
P.O. Box 806278
Chicago, IL 60680-4124
A Subsidiary of USG Corporation