

CIRRUS® Second Look®

Scored Tegular
medium texture



Cirrus® Second Look® III panels with Suprafine® 9/16" suspension system (Pgs. 400-401)



See more photos at:
armstrongceilings.com/photogallery
SEARCH: cirrus

These medium-textured panels, with scored plank visual, provide the noise reduction and sound blocking of Total Acoustics® performance.

KEY SELECTION ATTRIBUTES

- Get total noise control and design flexibility with Total Acoustics® ceiling panels: NRC + CAC = Total Acoustics® performance
- Cirrus® panels are part of the Sustain™ portfolio and meet the most stringent sustainability compliance standards today
- Classic Cirrus texture
- Excellent score line painting for a clean visual
- USDA Certified Biobased Product – 94%

TYPICAL APPLICATIONS

- Offices – closed spaces for privacy and confidentiality; open spaces for focus, collaboration, and teaming
- Healthcare – assists in addressing HIPAA, HCAHPS, and FGI acoustical requirements
- Lobbies/reception areas
- Department stores/retail

FACE VIEW



Cirrus Second Look I panel –
Scoring creates nominal 12" x 12" squares



Cirrus Second Look II panel –
Scoring creates nominal 24" x 24" squares




Cirrus Second Look III panel –
Scoring creates nominal 6" x 48" linear planks

COLOR



White
(WH)

DETAILS (Other Suspension Systems compatible. Refer to listing on page 220)



1. Cirrus® Second Look III
2. Cirrus® Second Look III with Suprafine® 9/16" suspension system


CIRRUS® Second Look®

Scored Tegular
medium texture



DeclareSM
Living Building
Challenge Compliant

SUSTAINSM
High Performance
Sustainable
Ceiling Systems



Calculate LEED contribution at
armstrongceilings.com/greengenie

VISUAL SELECTION

Edge Profile	Susp. Dwg. Pgs. 407-411 armstrongceilings.com/catdwgs	Item No.	Dimensions (Inches)	
CIRRUS® Second Look® I				
15/16" Beveled Tegular	14	512	24 x 48 x 3/4"	
CIRRUS Second Look II				
9/16" Beveled Tegular	28	510	24 x 48 x 3/4"	
15/16" Beveled Tegular	14	513	24 x 48 x 3/4"	
CIRRUS Second Look III				
9/16" Beveled Tegular	28	511	24 x 48 x 3/4"	
15/16" Beveled Tegular	14	514	24 x 48 x 3/4"	

PERFORMANCE SELECTION

Dots represent high level of performance.

\$\$\$

UL Classified Acoustics	NRC + CAC	Total Acoustics ¹	Fire Performance	Light Reflect	Anti-Mold & Mildew	Sag Resist	Certified Low VOC Emissions	Durability	Recycled Content	Recycle Program	Warranty
0.65	35	GOOD	Class A	0.85	•	Std	•	Std	•	•	10-Yr
0.65	35	GOOD	Class A	0.85	•	Std	•	Std	•	•	10-Yr
0.65	35	GOOD	Class A	0.85	•	Std	•	Std	•	•	10-Yr
0.65	35	GOOD	Class A	0.85	•	Std	•	Std	•	•	10-Yr
0.65	35	GOOD	Class A	0.85	•	Std	•	Std	•	•	10-Yr

¹ Total Acoustics® ceiling panels have an ideal combination of noise reduction and sound-blocking performance in one product.
GOOD (NRC 0.60-0.65; CAC 35+) **BETTER** (NRC 0.70-0.75; CAC 35+) **BEST** (NRC 0.80+; CAC 35+)

SUSPENSION SYSTEMS



PHYSICAL DATA

Material

Wet-formed mineral fiber

Surface Finish

Factory-applied latex paint

Fire Performance

ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less (UL labeled).

ASTM E1264 Classification

Type III, Form 1, Pattern E I K
Fire Class A

Humidity/Sag Resistance

Standard performance ceiling panels are recommended where the building is enclosed and the HVAC is continuously functioning.

Mold/Mildew Protection

Ceiling panels with BioBlock® performance resist the growth of mold and mildew.

VOC Emissions

Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.1, 2010. This standard is the guideline for low emissions in LEED, CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Primary (Embodied) Energy

See all LCA information on our EPDs.

High Recycled Content

Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Insulation Value

R Factor – 1.9 (BTU units)
R Factor – 0.33 (Watts units)

Design Consideration

Do not mix Cirrus® Second Look® with standard Cirrus items in the same room.

Warranty

Details at armstrongceilings.com

Weight; Square Feet/Carton

1.09 lbs/SF; 48 SF/ctn

Minimum Order Quantity

1 carton

Metric Items Available

512M, 510M, 513M, 511M, 514M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.

TechLine / 1 877 276-7876
armstrongceilings.com/commercial
(search: cirrus)
BPCS-3013-417

LEED® is a registered trademark of the U.S. Green Building Council
Declare™ is a service mark of The International Living Future Institute
UL is a registered trademark of UL LLC. All other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates
© 2016-2017 AWI Licensing LLC Printed in the United States of America

Armstrong®
CEILING & WALL SOLUTIONS

236

MINERAL FIBER