

GEORGIAN™ & GEORGIAN™ HIGH WASHABILITY

Square Lay-in & Tegular
medium texture



Georgian™ Beveled Tegular panels with Prelude® 15/16" suspension system (Pgs. 391-392)

This medium-textured panel offers good acoustics and high washability options to meet USDA/FSIS guidelines.

KEY SELECTION ATTRIBUTES

- Unique spatter-painted visual
- Total Acoustics® options (Items 795, 796)
- High Washability items available
 - Meets USDA/FSIS guidelines for use in food processing establishments
- Durable – Washable Scrubbable Impact-resistant Scratch-resistant
- 30-Year Limited System Warranty against visible sag (excludes item 791 and other sizes), mold, and mildew

TYPICAL APPLICATIONS

- Schools/classrooms (Items 795, 796)
- Corridors/conference rooms
- Kitchen/food preparation areas (Items 793, 794)

COLOR



White
(WH)

DETAILS (Other Suspension Systems compatible. Refer to listing on page 264.)



1. Georgian™ Beveled Tegular
2. Georgian™ Beveled Tegular with Prelude® 15/16" suspension system
3. Georgian™ Beveled Tegular with Silhouette® 9/16" suspension system 1/4" Reveal

GEORGIAN™ & GEORGIAN™ HIGH WASHABILITY

Square Lay-in & Tegular medium texture

UP TO **56%** RECYCLED CONTENT






Calculate LEED contribution at armstrongceilings.com/greengenie

LEED®

energy management
construction waste mgmt
regional materials
design for flexibility
EPD
recyclable/extended producer resp.
biobased materials
recycled content
sourcing of raw materials
material ingredient reporting
low emitting materials
lighting quality
acoustics


LOCATION DEPENDENT

VISUAL SELECTION

Edge Profile	Susp. Dwg. Pgs. 407-411 armstrongceilings.com/catdwgs	Item No.	Dimensions (Inches)
GEORGIAN™			
15/16" Square Lay-in	1	764	24 x 24 x 5/8" □
	1	763	24 x 48 x 5/8" □
	1	898	24 x 48 x 3/4" □
	1	791	30 x 60 x 3/4" □
15/16" Beveled Tegular	15	1752	24 x 24 x 5/8" □
			
9/16" Beveled Tegular	29, 44, 48, 52, 56	1753	24 x 24 x 5/8" □
			
SCHOOL ZONE® GEORGIAN			
15/16" Square Lay-in	1	796	24 x 24 x 3/4" □
	1	795	24 x 48 x 3/4" □
SCHOOL ZONE® GEORGIAN Size Capabilities			
15/16" Square Lay-in	Made-to-Order Sizes (3-4 Wks)	Width	
		Length	
		3/4" Thick	
		12" - 30"	18" - 72"
GEORGIAN – High Washability Panels, Unperforated			
15/16" Square Lay-in	1	794	24 x 24 x 5/8" □
	1	793	24 x 48 x 5/8" □

¹ Total Acoustics® ceiling panels have an ideal combination of noise reduction and sound-blocking performance in one product.
GOOD (NRC 0.60-0.65; CAC 35+) **BETTER** (NRC 0.70-0.75; CAC 35+) **BEST** (NRC 0.80+; CAC 35+)

SUSPENSION SYSTEMS



PHYSICAL DATA

Material

Wet-formed mineral fiber

Surface Finish

Factory-applied latex paint

Fire Performance

ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less (UL labeled). Fire Guard™: A fire-resistive ceiling when used in applicable UL assemblies (Class A).

ASTM E1264 Classification

Type III, Form 2, Pattern C E
 Items 794, 793, 898 –
 Type IX, Form 2, Pattern G
 Fire Class A

Sag Resistance

HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not

including, standing water and outdoor applications. Excludes Item 791 and other size panels.

Mold/Mildew Protection

Ceiling panels with BioBlock® performance resist the growth of mold and mildew.

Acoustical Performance

CAC testing conducted using Silhouette® suspension system.

VOC Emissions

Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.1, 2010. This standard is the guideline for low emissions in LEED, CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

High Recycled Content

Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Insulation Value

R Factor - 1.6 (BTU units)
 R Factor - 0.28 (Watts units)

30-Year Performance Guarantee & Warranty

When installed with Armstrong® Suspension System. Details at armstrongceilings.com

Weight; Square Feet/Carton

763, 793 – 0.67 lbs/SF; 96 SF/ctn
 764, 794, 1752, 1753 – 0.72 lbs/SF; 64 SF/ctn
 791 – 0.76 lbs/SF; 75 SF/ctn
 898 – 1.13 lbs/SF; 64 SF/ctn
 796 – 1.31 lbs/SF; 48 SF/ctn
 795 – 1.38 lbs/SF; 64 SF/ctn

Minimum Order Quantity

1 carton, excludes made-to-order panels

Metric Items Available

1753M, 764M, 763M, 791M, 1752M, 796M, 795M, 794M, 793M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.

PERFORMANCE SELECTION

Dots represent high level of performance.

\$\$\$

UL Classified Acoustics	Total Acoustics ¹	Fire Performance	Light Reflect	Anti-Mold & Mildew	Sag Resist	Certified Low VOC Emissions	Wash	Scrub	Impact	Scratch	Recycled Content	Recycle Program	30-Yr Warranty
NRC + CAC	NRC + CAC	Fire	Light	Anti-Mold & Mildew	Sag	Certified Low VOC Emissions	Wash	Scrub	Impact	Scratch	Recycled Content	Recycle Program	30-Yr Warranty
0.55	33	–	Class A	0.86	•	•	•	–	–	•	•	•	•
0.55	33	–	Class A	0.86	•	•	•	–	–	•	•	•	•
0.55	35	–	Fire Guard™	0.86	•	•	•	–	–	•	•	•	•
0.55	33	–	Class A	0.86	•	Std	•	–	–	•	•	•	1-Yr
0.55	35	–	Class A	0.86	•	•	•	–	–	•	•	•	•
0.55	35	–	Class A	0.86	•	•	•	–	–	•	•	•	•
0.65	35	GOOD	Class A	0.86	•	•	•	–	–	•	•	•	•
0.65	35	GOOD	Class A	0.86	•	•	•	–	–	•	•	•	•
N/A	N/A	–	Class A	0.86	•	Std	•	–	–	•	•	•	1-Yr
N/A	33	–	Class A	0.88	•	•	•	•	•	•	•	•	•
N/A	33	–	Class A	0.88	•	•	•	•	•	•	•	•	•



MINERAL FIBER