



Personalize Your Design!

Mix and match different sizes, colors, and materials to reinvent your ceiling. More at:
armstrongceilings.com/designflex



Lyra® Vector® panels with Prelude® XL® 15/16" suspension system (Pgs. 458-459)

plus capabilities
to do more



armstrongceilings.com/capabilities
See more photos at:
armstrongceilings.com/photogallery

Smooth-textured acoustical panel is ideal for projects with limited plenum space: requires about 6" of clear space from the deck.

KEY SELECTION ATTRIBUTES



- DesignFlex™ options include tailor-made sizes and colors available to ship in 3 weeks
- 1/4" reveal between acoustical panels results in a monolithic appearance
- Downward accessible for minimal plenum height
- Outstanding acoustical performance for open plan areas, both Articulation Class (190) and NRC (0.90)
- Smooth, clean durable finish – Washable Scratch-resistant Soil-resistant
- Energy-saving high light-reflective finish
- Product can be recycled through the Armstrong Ceilings Recycling Program
- 30-Year Limited System Warranty against visible sag, mold, and mildew

COLOR



White
(WH)



Available in
any color!

DETAILS



1. Lyra® Vector® with Prelude® XL® 15/16" suspension system

VISUAL SELECTION


Edge Profile	Susp. Dwg. Pgs. 474-478 armstrongceilings.com/catdwgs	Item No.	Dimensions (Inches)
LYRA® Vector®			
1/4" Reveal with 15/16" Vector	73	8494	24 x 24 x 7/8"
	73	8495	24 x 48 x 7/8"
	73	8496	24 x 72 x 7/8"
	73	8497	24 x 96 x 7/8"
	73	8498	30 X 30 x 7/8"
	73	8499	48 x 48 x 7/8"

Size Capabilities

Width	Length
7/8" Thick	
4" – 5-1/2"	9" – 120"
6" – 11-1/2"	6" – 120"
12" – 30-1/2"	4" – 120"
31" – 48"	4" – 48"

¹ Total Acoustics® ceiling panels have an ideal combination of noise reduction and sound-blocking performance in one product.

SUSPENSION SYSTEMS



VECTOR – FIXTURE TRIMS

Item No.	Length	Color	Substrate
5790	12"	White	Extruded PVC
5791	24"	White	Extruded PVC
5792	30"	White	Extruded PVC
5793	48"	White	Extruded PVC

PHYSICAL DATA

Material
Fiberglass with acoustically transparent membrane

Surface Finish
Acoustically transparent membrane with factory-applied latex paint

Fire Performance
ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less (UL labeled.)

ASTM E1264 Classification
Type XII, Form 2, Pattern E
Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Mold/Mildew Protection
Ceiling panels with BioBlock® performance resist the growth of mold and mildew.

High Recycled Content
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Design Considerations
Use fixture trim kit around all lights, diffusers, and other ceiling penetrations to avoid exposed suspension system and panel edges.

Insulation Value
R Factor – 3.5 (BTU units)
R Factor – 0.62 (Watts units)

30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System. Details at armstrongceilings.com

Weight; Square Feet/Carton
8494 – 0.58 lbs/SF; 48 SF/ctn
8495, 8497 – 0.56 lbs/SF; 96 SF/ctn
8496 – 0.57 lbs/SF; 72 SF/ctn
8498 – 0.59 lbs/SF; 75 SF/ctn
8499 – 0.60 lbs/SF; 64 SF/ctn

Minimum Order Quantity
1 carton

PERFORMANCE SELECTION

Dots represent high level of performance.

UL Classified Acoustics	NRC	+	CAC	=	Total Acoustics ¹	Articulation Class	Fire Performance	Light Reflect	Mold & Mildew Protection	Sag Resist	Certified Low VOC Emissions	Wash	Scratch	Soil	Recycled Content	Recycle Program	30-Yr Warranty
0.90	N/A	–	190	Class A	0.88	•	•	•	–	•	•	•	•	•	•	•	•
0.90	N/A	–	190	Class A	0.88	•	•	•	–	•	•	•	•	•	•	•	•
0.90	N/A	–	190	Class A	0.88	•	•	•	–	•	•	•	•	•	•	•	•
0.90	N/A	–	190	Class A	0.88	•	•	•	–	•	•	•	•	•	•	•	•
0.90	N/A	–	190	Class A	0.88	•	•	•	–	•	•	•	•	•	•	•	•
0.90	N/A	–	190	Class A	0.88	•	•	•	–	•	•	•	•	•	•	•	•
N/A	N/A	N/A	Class A	0.88	•	•	•	–	•	•	•	•	•	•	•	•	•

ACCESSORIES (must be ordered separately)

Item No.		
441		Vector Border Clip (required for installations with the suspension system resting on the wall molding). Primarily used for corners and special cutouts.
442A		Vector Hold-Down Clip (required for installation)
7425 (24"), 7431 (30"), 7445 (48"), 7461 (60")		Stabilizer Bars
522		Mid-point Clip 48" x 48" Vector panels only
7870		Spring Border Clip (For installations with the panel resting on the wall molding)