



Optima® PB Ceiling Panels **Armstrong World Industries**

Final Assembly: Hilliard, OH, USA

Life Expectancy: 30 years

End of Life Options: Take Back Program (Armstrong Ceiling Recycling Program)

Ingredients:

Board: Man Made Mineral Fiber (Hilliard, OH),
Starch Acrylic Binder, Modified Vegetable Oil, Water Repellant; Scrim: Man Made Mineral Fiber, Polyvinyl Alcohol, Proprietary (0.2-0.75%)*; Adhesive: Polyvinyl Acetate, Plasticizer; Coating: Limestone, Dolomite, Calcium Carbonate, Titanium Dioxide, Polyvinyl Acetate, Aluminum Trihydrate, Diatomaceous Earth, Mica, Aluminum Hydroxide, Hydroxyethylcellulose, Quartz, Hydrous Alumino Silicate, Amorphous Silica, Sodium Hydroxide, Proprietary (0.01-0.1%)*, Methacrylic Acid, Proprietary (0.01-0.15%)*

*LBC Temp Exception I10-E4 Proprietary Ingredients <1%

Living Building Challenge Criteria:

ARM-0002

VOC Content: N/A

Declaration Status

EXP. 04/01/2017

VOC Emissions: CDPH Compliant

☐ LBC Red List Free

☒ LBC Compliant

☐ Declared

MANUFACTURER RESPONSIBLE FOR LABEL ACCURACY

INTERNATIONAL LIVING FUTURE INSTITUTE™ declareproducts.com