

PRELUDE® Plus XL® Fire Guard™

PRELUDE® XL® for Exterior Applications

Exposed Tee System



UP TO **30%** RECYCLED CONTENT

Calculate LEED contribution at armstrongceilings.com/greengenie

LEED

- energy management
- construction waste mgmt
- regional materials
- design for flexibility
- EPD
- recyclable/extended producer resp.
- biobased materials
- recycled content
- sourcing of raw materials
- material ingredient reporting
- low emitting materials
- lighting quality
- acoustics

LOCATION DEPENDENT

A 15/16" suspension system for severe environmental performance.



Prelude® Plus XL® suspension system

KEY SELECTION ATTRIBUTES

- **Seismic Rx®** Suspension System saves time and money; ICC-ES approach to installations (ESR-1308)
- Systems conform to ASTM C635 for Severe Environmental Performance
- Rotary-stitched during manufacture for torsional strength and stability
- 10-Year Limited Warranty; 30-Year Limited Warranty with **HumiGuard® Plus** or **HumiGuard® Max** products
- XL® staked-on end detail provides secure locked connection
- **PeakForm®** profile increases strength and stability
- **SuperLock™** main beam clip engineered for secure connection and fast, accurate alignment



PRELUDE® XL® For Exterior Applications

- Minimum G90 hot-dipped galvanized steel with prefinished G90 steel capping
- Suitable for wind uplift applications with appropriate bracing

PRELUDE® Plus XL® Fire Guard™

- Systems are minimum G60 hot-dipped galvanized steel with prefinished aluminum capping for enhanced corrosion resistance

TYPICAL APPLICATIONS

PRELUDE Plus XL Fire Guard


- Locker rooms
- Food preparation areas

PRELUDE XL For Exterior Applications


- Non-exposed exterior corridors
- Drive-thru areas
- Indoor parking garages
- Use with Woodworks Linear Solid Wood Panels for Exterior

COLORS

Fire Guard™



Exterior



VISUAL SELECTION

Face Profile	Item No. ♦	Description	Dimensions (Inches)	Hanger Spacing* Lbs./LFT		
Prelude® Plus XL® Fire Guard™ (Red Numbers are Fire Guard Items)				2 Ft.	4 Ft.	5 Ft.
15/16"	HD8201 _	12' HD Main Beam	144 x 15/16 x 1-11/16"	12.75	16.73	—
15/16"	XL8240 _	4' Cross Tee	48 x 15/16 x 1-1/2"	12.75	—	—
15/16"	XL8223 _	2' Cross Tee	24 x 15/16 x 1-1/2"	38.63	—	—
Molding						
7/8"	HD7801 _	10' Hemmed Angle Molding	120 x 7/8 x 7/8"	—	—	—
Prelude XL for Exterior Applications						
15/16"	7301G90A _	12' HD Main Beam	144 x 15/16 x 1-11/16"	—	16.50	6.92
15/16"	XL7341G90A _	4' Cross Tee	48 x 15/16 x 1-11/16"	—	16.59	—
15/16"	XL7321G90A _	2' Cross Tee	24 x 15/16 x 1-11/16"	—	74.38	—
Molding						
7/8"	HD7801G90 _	10' Hemmed Angle Molding	120 x 7/8 x 7/8"	—	—	—
Accessories						
2"	BACG90A	Wind Uplift Clip	N/A	—	—	—
	UHDC	Universal Hold-down Clip	N/A	—	—	—

* Simple Span

♦ Add 2-letter color suffix to item number when specifying or ordering. Available in White Steel and Tech Black (ex. HD7801G90A **B L**)

PERFORMANCE

Fire Guard	Seismic Category

Dots represent high level of performance.

•	•
•	•
•	•
—	—
—	•
—	•
—	—
—	—
—	—

PACKAGING

Pcs./ Ctn.	LFT/ Ctn.
20	240
60	240
60	120
30	300
20	240
60	240
60	120
30	300
250	—
1000	—

ASTM Class
HD - Heavy-duty
ID - Intermediate-duty
LD - Light-duty

DETAILS

For more information on Prelude Plus XL Fire Guard, see submittal BPCS-3156. Prelude XL for exterior applications and wind uplift chart see BPCS-3384.



PRELUDE XL Main Beam



PRELUDE XL Cross Tee

