

TUNDRA®

Square Lay-in & Tegular
medium texture



Tundra® panels with Suprafine® 9/16" suspension system (Pgs. 400-401)

Durable Tundra® panels have a medium-textured visual, and are impact- and scratch-resistant.

KEY SELECTION ATTRIBUTES

- Durable
 - Impact-resistant
 - Scratch-resistant
- 30-Year Limited System Warranty against visible sag, mold, and mildew

TYPICAL APPLICATIONS

- Offices
- Schools
- Corridors

COLOR



White
(WH)

DETAILS (Other Suspension Systems compatible. Refer to listing on page 310.)



1. Tundra® Beveled Tegular
2. Tundra with Suprafine® 9/16" suspension system

TUNDRA®

Square Lay-in & Tegular medium texture

UP TO **35%** RECYCLED CONTENT

Calculate LEED contribution at armstrongceilings.com/greengenie

LEED®

- energy management
- construction waste mgmt
- regional materials
- design for flexibility
- EPD
- recyclable/extended producer resp.
- biobased materials
- recycled content
- sourcing of raw materials
- material ingredient reporting
- low emitting materials
- lighting quality
- acoustics

LOCATION DEPENDENT

VISUAL SELECTION

Edge Profile	Susp. Dwg. Pgs. 407-411 armstrongceilings.com/catdwgs	Item No.	Dimensions (Inches)
TUNDRA®			
15/16" Square Lay-in	1	301	24 x 24 x 5/8" <input type="checkbox"/>
		302	24 x 48 x 5/8" <input type="checkbox"/>
15/16" Beveled Tegular	15	303	24 x 24 x 5/8" <input type="checkbox"/>
		305	24 x 48 x 5/8" <input type="checkbox"/>
9/16" Beveled Tegular	29, 44, 48, 52, 56	304	24 x 24 x 5/8" <input type="checkbox"/>
Size Capabilities		Width	Length
15/16" Square Lay-in	Made-to-Order Sizes (4-6 Wks)	5/8" Thick	
15/16" & 9/16" Beveled Tegular		24"	24" - 48"


PERFORMANCE SELECTION

Dots represent high level of performance.

UL Classified Acoustics		Total Acoustics ¹	Fire Performance	Light Reflect	Mold & Mildew Protection	Sag Resist	Certified Low VOC Emissions	Impact	Scratch	Recycled Content	Recycle Program	30-Yr Warranty
NRC	+ CAC	=			Bio-Block	Humi-Guard+		Durability				
0.50	33	-	Class A	0.87	•	•	-	•	•	Std	•	•
0.50	35	-	Class A	0.87	•	•	-	•	•	Std	•	•
0.50	33	-	Class A	0.87	•	•	-	•	•	Std	•	•
0.50	35	-	Class A	0.87	•	•	-	•	•	Std	•	•
0.50	33	-	Class A	0.87	•	•	-	•	•	Std	•	•
N/A	N/A	-	Class A	0.87	•	•	-	•	•	Std	•	•

¹Total Acoustics® ceiling panels have an ideal combination of noise reduction and sound-blocking performance in one product.

SUSPENSION SYSTEMS



PHYSICAL DATA

Material
Wet-formed, high-density mineral fiber

Surface Finish
Factory-applied latex paint with scuff-resistant spatter coat

Fire Performance
ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less (UL labeled).

ASTM E1264 Classification
Type III, Form 2, Pattern C E
Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Acoustical Testing
CAC testing conducted using Prelude® XL® suspension system for 15/16" edge detail and Silhouette® suspension system for 9/16" edge detail.

Mold/Mildew Protection
Ceiling panels with BioBlock® performance resist the growth of mold and mildew.

Insulation Value
R Factor - 1.7 (BTU units)
R Factor - 0.30 (Watts units)

30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System. Details at armstrongceilings.com

Weight; Square Feet/Carton
301, 302, 305 - 1.09 lbs/SF; 64 SF/ctn
303, 304 - 1.10 lbs/SF; 48 SF/ctn

Minimum Order Quantity
1 carton, excludes made-to-order panels.

Metric Items Available
302M, 303M, 305M, 304M - Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.