CREATE!™ ULTIMA®, ULTIMA® Health Zone™, OPTIMA®

Square Lay-in, Tegular & Vector® fine texture









Create!™ custom images are available on Ultima, Ultima® Health Zone™, and Optima® panels. Great acoustics have never been so colorful!

KEY SELECTION ATTRIBUTES

- · Get total noise control and design flexibility with Total Acoustics® ceiling panels: NRC + CAC = Total Acoustics® performance
- · Artistic designs have broad appeal and complement unique interior design
- · Mix and match designs with standard Ultima, Ultima Health Zone, and Optima
- Excellent sound absorption NRC 0.70 - 0.90
- · The high performance benefits of Ultima or Optima fine-textured ceilings:
- Washable, Soil-resistant (Ultima, Optima) Water-repellent (Ultima Health Zone)
- · Product is directional
- · Custom samples available
- · Can contribute to LEED® credits

TYPICAL APPLICATIONS

- · Classrooms · Libraries/media centers
- · Lobbies/reception areas
- · Retail
- · Restaurant
- · Patient Rooms

CREATE YOUR OWN UNIQUE, CUSTOM CEILING VISUAL USING COLOR AND ARTWORK

Original Artwork Guidelines:

- · Artwork must be vector-based
- · Acceptable file types:
- Adobe® Illustrator® .ai
- Encapsulated PostScript .eps
- Scalable Vector Graphics .svg
- · Acceptable Color Mode: CMYK

Original Digital Image Requirements:

- · Image must be 150 dpi at full print size
- · Acceptable file types:
- Joint Photographic Experts Group .jpg - Tagged Image File Format - .tiff

Solid Color Requirements:

- · Custom colors are available
- · RAL® classic colors available on suspension systems and perimeter trims



CREATE!™ ULTIMA®, ULTIMA® Health Zone™, OPTIMA®

Square Lay-in, Tegular & Vector® fine texture

THEMES - Available on ULTIMA®, ULTIMA® HEALTH ZONE™, OPTIMA® CREATE!™ Panels

Blooms



Single Panel Design 021



4-Panel Design
Design 022 (Add
A, B, C, or D for
individual panel



Single Panel Design 051



4-Panel DesignDesign 052 (Add
A, B, C, or D for
individual panel
order)

Stars



Single Panel Design 041



Single Panel Design 042



Single Panel Design 043



Bubbles

Single Panel Design 011



Single Panel Design 012



Single Panel Design 013

WOOD LOOKS - Available on ULTIMA HEALTH ZONE CREATE! Square Lay-in panels Due to printing limitations, shade may vary from actual product.











Walnut (WN

CALL, DON'T FALL - Available on ULTIMA HEALTH ZONE CREATE! Square Lay-in Panels

Reinforce safety in patient rooms by printing warning messages, in any language, on ceiling panels. Add your custom design or choose one of these.











More design options online at armstrongceilings.com/calldontfall

Custom CREATE![™] Designs

Choose from the standard colors shown on the front of Create! 6" x 6" submittal samples. Keep in mind, sheen varies slightly depending on base panel selection (Ultima, Ultima Health Zone, Optima). Custom colors available.



Optima® Create!™ Vector® panels with Prelude® XL® suspension system



Ultima® Create!™ Vector® panels in Oak Wood Looks with Prelude® XL® suspension system



Ultima® Create!™ Custom panels with Prelude® XL® suspension system



Ultima® Create!™ Custom panels with Prelude® XL® suspension system


VISUAL SELECTION

PERFORMANCE SELECTION Dots represent high level of performance.

\$\$\$\$

	NRC	+ CAC	II Post Total Post Acoustics	Fire Performance	Anti-Mold & Mildew	Sag Resist	Water Repel	Wash Wash	Soil	Recycled Content	Recycle Program	30-Yr Warranty
	੨		CAC		Bio- Block	Humi- Guard+		— Durability	202000			
4" 🗌 🤾	0.75	35	BETTER (III)	Class A	•	•	-	•	•	•	•	•
	0.90	26		Class A	•	•	_	•	•	•	•	•
4"	0.75	35 •	BETTER (III)	Class A	•	•	-	•	•	•	•	•
4" 🗌	0.70	33	-	Class A	•	•	-	•	•	•	•	•
B"	0.80	26	-	Class A	•	•	_	•	•	•	•	•
					Bio- Block+							
4"	0.70	38	BETTER (III)	Class A	•	•	•	•	•	•	•	•
4"	0.70	38	BETTER (III)	Class A	•	•	•	•	•	•	•	•
	variations run; ilings have	variations 1 Tota run; G00 illings have Bas	variations 1 Total Acoustics® GOOD (NRC 0.60 Based on image	variations 1 Total Acoustics® ceiling panel: run; GOOD (NRC 0.60-0.65; CAC 3: Based on image/color covera;	variations 1 Total Acoustics® ceiling panels have an irun; GOOD (NRC 0.60-0.65; CAC 35+) BETTE Based on image/color coverage, NRC me	variations run; GOOD (NRC 0.60-0.65; CAC 35+) BETTER (NRC 0.86) Based on image/color coverage, NRC may vary slig	variations rrun; GOOD (NRC 0.60-0.65; CAC 35+) BETTER (NRC 0.70-0.75; CA Based on image/color coverage, NRC may vary slightly.	variations rrun; llings have 1 Total Acoustics® ceiling panels have an ideal combination of noise redu GOOD (NRC 0.60-0.65; CAC 35+) BETTER (NRC 0.70-0.75; CAC 35+) I Based on image/color coverage, NRC may vary slightly.	variations rrun; GOOD (NRC 0.60-0.65; CAC 35+) BETTER (NRC 0.70-0.75; CAC 35+) BEST (NRC 0.80-0.75; CAC 35+) BEST (NRC 0.70-0.75; CAC 35+) BEST (NRC 0.70-0	variations rrun; GOOD (NRC 0.60-0.65; CAC 35+) BETTER (NRC 0.70-0.75; CAC 35+) BEST (NRC 0.80+; CAC Based on image/color coverage, NRC may vary slightly.	variations rrun; GOOD (NRC 0.60-0.65; CAC 35+) BETTER (NRC 0.70-0.75; CAC 35+) BEST (NRC 0.80+; CAC 35+) Based on image/color coverage, NRC may vary slightly.	variations run; GOOD (NRC 0.60-0.65; CAC 35+) BETTER (NRC 0.70-0.75; CAC 35+) BEST (NRC 0.80+; CAC 35+) Based on image/color coverage, NRC may vary slightly.

SUSPENSION SYSTEMS AND EDGE DETAILS



Prelude® XL®

(White suspension required for Vector)



Tegular Panel and Silhouette® XL® 1/4" Reveal



Tegular Panel and Silhouette® XL® 1/8" Reveal



Lay-in Panel and Prelude® XL® or 360° Painted Grid





RAL® Colors Available on Suspension Systems and Perimeter Trims

PHYSICAL DATA

Ultima®/Ultima® Health Zone: Wet-formed mineral fiber Optima: Fiberglass with DuraBrite® acoustically transparent membrane with CAC-backing

Surface Finish

Factory-applied latex paint with UV printing

Fire Performance

ASTM E84 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less.

ASTM E1264 Classification
Ultima/Ultima Health Zone: Type III, Form 2, Pattern E Optima: Type XII, Form 2, Pattern E Fire Class A

Humidity/Sag Resistance HumiGuard® Plus ceiling panels are recommended for

TechLine / 1 877 276 7876

armstrongceilings.com/commercial (search: create)

areas subject to high humidity, up to, but not including, standing water and outdoor applications

Mold/Mildew Protection
Ceiling panels with BioBlock® performance resist the growth of mold and mildew. Health Zone ceiling panels with BioBlock® Plus performance also resist odor and action equality bacterial growth. stain causing bacterial growth.

Acoustical Performance

CAC testing conducted using Silhouette® suspension system.

High Recycled Content

Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Insulation Value

Ultima/Ultima Health Zone: R Factor – 1.6 (BTU units) R Factor – 0.28 (Watts units) Optima: R Factor – 4.0 (BTU units) R Factor – 0.70 (Watts units)

30-Year Performance Guarantee & Warranty When installed with Armstrong® Suspension System. 1-year limited warranty on color. Details at armstrongceilings.com

Weight; Square Feet/Carton

Ultima/Ultima Health Zone: 1.05 lbs/SF; 16 SF/ctn Optima: 0.55 lbs/SF; 16 SF/ctn

Minimum Order Quantity:



LEED® is a registered trademark of the U.S. Green Building Council Adobe® Illustrator® is a registered trademark of Adobe Systems Incorporated. RAL® is a registered trademark of RAL gGmbH. All other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates BPCS-4949-118 © 2018 AWI Licensing LLC Printed in the United States of America