

ULTIMA® Health Zone™ ULTIMA® Health Zone™ High NRC

Square Lay-in
fine texture



Ultima® Health Zone™ Square Lay-in panels with Prelude® 15/16" suspension system (Pgs. 391-392)

Smooth-textured Ultima® Health Zone™ panels meet USDA/FSIS guidelines for use in food preparation areas, kitchens, and Clean Room assemblies, is water-repellent, and provides excellent sound absorption and blocking, addressing HIPAA requirements.

KEY SELECTION ATTRIBUTES

- Get total noise control and floor plan versatility with Total Acoustics® ceiling panels: NRC + CAC = Total Acoustics Performance
- Ultima® panels are part of the Sustain® portfolio and meet the most stringent sustainability compliance standards today
- Clean Rooms up to ISO Class 5 (Class 100) (items 1935 & 1938)
- Exceeds FGI Guidelines for acoustics and cleanability in general healthcare spaces
- Meets USDA/FSIS guidelines for use in food processing areas
- Long-lasting water-repellency; Washable and Scrubbable
- USDA Certified Biobased Product – 88%
- Smooth, clean, durable finish – Impact-, Scratch-, and Soil-resistant; safe for use with disinfectants
- Excellent sound absorption
- 30-Year Limited System Warranty against visible sag, mold and mildew, and bacterial growth

TYPICAL APPLICATIONS

Clean Rooms (item 1935)
Healthcare



- Patient rooms
- Treatment rooms
- Nurses' stations
- Emergency rooms
- Corridors
- Lavatories and restrooms
- Kitchen/food prep areas

COLOR



White
(WH)

DETAILS



1. Ultima® Health Zone™ Square Lay-in
2. Ultima® Health Zone™ High NRC Square Lay-in panels with Clean Room™ 15/16" suspension system

ULTIMA® Health Zone™ ULTIMA® Health Zone™ High NRC

Square Lay-in
fine texture

Declare™
Living Building
Challenge Compliant



SUSTAIN™
High Performance
Sustainable
Ceiling Systems

UP TO **76%** RECYCLED CONTENT

Calculate LEED contribution at armstrongceilings.com/greengenie

LEED®

energy management
construction waste mgmt
regional materials
design for flexibility
EPD
recyclable/extended producer resp.
biobased materials
recycled content
sourcing of raw materials
material ingredient reporting
low emitting materials
lighting quality
acoustics

VISUAL SELECTION

Edge Profile	Susp. Dwg. Pgs. 407-411	Item No.	Dimensions (Inches)
--------------	-------------------------	----------	---------------------

ULTIMA® Health Zone™ High NRC

15/16" Square Lay-in	1, 6	1445	24 x 24 x 1"	<input type="checkbox"/>
	1, 6	1448*	24 x 48 x 1"	<input type="checkbox"/>

ULTIMA Health Zone

15/16" Square Lay-in	1, 6	1935	24 x 24 x 3/4"	<input type="checkbox"/>
	1, 6	1938*	24 x 48 x 3/4"	<input type="checkbox"/>

Size Capabilities

Width	Length
7/8" Thick	
4" – 5-1/2"	12" – 72"
6" – 11-1/2"	6" – 72"
12" – 24-1/2"	4" – 72"
25" – 48"	4" – 30"

¹ Total Acoustics® ceiling panels have an ideal combination of noise reduction and sound-blocking performance in one product.

GOOD (NRC 0.60-0.65; CAC 35+) **BETTER** (NRC 0.70-0.75; CAC 35+) **BEST** (NRC 0.80+; CAC 35+)


* Item does not have painted edges

PERFORMANCE SELECTION

Dots represent high level of performance.

UL Classified Acoustics	Total Acoustics ¹	Fire Performance	Light Reflect	Mold & Mildew Protection	Sag Resist	Certified Low VOC Emissions	Water Repel	Wash	Scrub	Impact	Scratch	Soil	Recycled Content	Recycle Program	30-Yr Warranty
NRC + CAC =															
0.80 • 35	BEST	Class A	0.86 •	•	•	•	•	•	•	•	•	•	•	•	•
0.80 • 35	BEST	Class A	0.86 •	•	•	•	•	•	•	•	•	•	•	•	•
0.70 • 38	BETTER	Class A	0.86 •	•	•	•	•	•	•	•	•	•	•	•	•
0.70 • 38	BETTER	Class A	0.86 •	•	•	•	•	•	•	•	•	•	•	•	•
N/A N/A	—	Class A	0.86 •	•	•	•	•	•	•	•	•	•	•	•	•

SUSPENSION SYSTEMS



PHYSICAL DATA

Material

Wet-formed mineral fiber with DuraBrite® acoustically transparent water-repellent membrane

Surface Finish

DuraBrite with factory-applied latex paint

Fire Performance

ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less (UL labeled).

ASTM E1264 Classification

Type IV, Form 2, Pattern E
Fire Class A

Humidity/Sag Resistance

HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Mold/Mildew & Bacterial Protection

Health Zone™ ceiling panels with BioBlock® Plus performance resist the growth of mold and mildew, and resist odor- and stain-causing bacterial growth.

VOC Emissions

Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.1, 2010. This standard is the guideline for low emissions in LEED, CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Acoustical Performance

CAC testing conducted using Prelude® XL® suspension system.

Primary (Embodied) Energy

See all LCA information on our EPDs.

High Recycled Content

Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Insulation Value

R Factor – 2.2 (BTU units)
R Factor – 0.39 (Watts units)

30-Year Performance Guarantee & Warranty

When installed with Armstrong® Suspension System. Details at armstrongceilings.com

Cleaning Recommendations

To clean panel, use a clean, white cloth with water or a mild detergent, and wipe surface. To disinfect panel, lightly spray surface and wipe clean with a clean, white cloth. Acceptable colorless disinfectants include:

- Sodium hypochlorite
- Hydrogen peroxide
- Quaternary ammonium

Weight; Square Feet/Carton

1935, 1938 – 1.08 lbs/SF; 48 SF/ctn
1448, 1445 – 1.0 lbs/SF; 40 SF/ctn

Minimum Order Quantity

1 carton

TechLine / 1 877 276 7876
armstrongceilings.com/commercial
(search: ultima)

BPCS-4066-318

LEED® is a registered trademark of the U.S. Green Building Council
Declare™ is a service mark of The International Living Future Institute
UL is a registered trademark of UL LLC. All other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates
© 2018 AWI Licensing LLC Printed in the United States of America

Armstrong®
CEILING & WALL SOLUTIONS

322

MINERAL FIBER