

# CLEAN ROOM™ Aluminum

## 15/16" and 1-1/2" Exposed Tee System



Calculate LEED contribution at [armstrongceilings.com/greengenie](http://armstrongceilings.com/greengenie)

LOCATION DEPENDENT



### KEY SELECTION ATTRIBUTES

- Suitable for use in Class 5 (Class 100 clean rooms as defined by ISO Standard 14644-1 (Federal Standard 209E) when used with Clean Room™ FL, Clean Room VL, Health Zone™ Ultima®, and Health Zone Optima®
- Aluminum construction for maximum corrosion resistance and non-magnetic environments.
- Clear non-ferrous hold down clip to ensure a good seal available (not required for clean room performance)
- Unique, factory-applied gaskets for better seal between panel and suspension system
- 10-year limited warranty; 30-year limited warranty with HumiGuard® Plus products

### TYPICAL APPLICATIONS

- MRI suites (co-extruded aluminum only)
- Hospitals
- Food processing facilities
- High-tech manufacturing
- Pharmaceutical facilities

### VISUAL SELECTION

### PERFORMANCE

### PACKAGING

Item No.	Face Profile	Description	Route Spacing	Dimensions (Inches)	Hanger Spacing* Lbs./Lin. Ft.			Fire Guard™	Seismic Category	Pcs./ Ctn.	Lin. Ft./ Ctn.
<b>15/16 Clean Room Co-Extruded Aluminum (Gasketed)</b>					<b>2 Ft.</b>	<b>4 Ft.</b>	<b>5 Ft.</b>	Dots represent high level of performance.			
EA7900	15/16"	12' ID Main Beam	12" O.C.	144 x 15/16 x 2"	—	12.25	—	—	—	20	240
EA7940	15/16"	4' Cross Tee	24" O.C.	48 x 15/16 x 2"	—	15.32	—	—	—	60	240
EA7920	15/16"	2' Cross Tee	—	24 x 15/16 x 2"	66.62	—	—	—	—	60	120
	15/16"	<b>Other Sizes</b> Main beams L: 36" - 144" / Cross tees L: 6" - 144" / Route spacing 3" from ends, 6" thereafter								Varies	Varies
EA7812		12' Hemmed Angle Molding		144 x 15/16 x 15/16"						30	360
<b>1-1/2 Clean Room Co-Extruded Aluminum (Gasketed)</b>											
EA7903	1-1/2"	12' HD Main Beam	12" O.C.	144 x 1-1/2 x 2"	—	16.7	8.4	—	•	12	144
EA7947	1-1/2"	4' Cross Tee	24" O.C.	48 x 1-1/2 x 2"	—	17.66	—	—	—	36	144
EA7927	1-1/2"	2' Cross Tee	—	24 x 1-1/2 x 2"	60.55	—	—	—	—	36	72
EA7813		12' Hemmed Angle Molding		144 x 15/16 x 15/16"						30	360

\* Simple Span

### ACCESSORIES

**BERC2 – 2" Beam End Retaining Clip** – Allows you to create a code compliant Seismic D, E, F ceiling installation while eliminating the need to use 2" wall molding or spreader bars.


ALBERC2 (aluminum) – 200 pcs

☐ BERC2 (Steel) – 200 pcs

☐ FZBERC2 (Steel) – 50 pcs

☐ ALBERC2 (Aluminum) – 200 pcs

☐ FZALBERC2 (Aluminum) – 50 pcs




**CHDC – Clear Hold Down Clip** –

Attaches to top bulb of the suspension system to hold 1/16" to 5/8" lay-in panel in place; helps to prevent ceiling panel fluttering at entryways.

☐ CHDC – 50 pcs

☐ FZCHDC – 50 pcs

Clean Room (CHDC)  
Hold Down Clip



# CLEAN ROOM™ Aluminum

## 15/16" and 1-1/2" Exposed Tee System

### MAXIMUM FIXTURE WEIGHT

Item No.	Configuration		Fixture*		Planning Module		Hanger Spacing		Maximum Weight	
	A	B	A	B	A	B	A	B	A	B
<b>Main Beam to Main Beam</b>										
<input type="checkbox"/> EA7903			24" x 48"		48" x 48"		48"		100.0 lbs.	
			24" x 48"	12" x 48"	48" x 48"	48" x 48"	48"	48"	70.0 lbs.	100.0 lbs.
			12" x 48"		48" x 48"		48"		69.0 lbs.	
Main beams tested as follows: EA7903 tested at 16.74 lbs./lin. ft. to 1/360 of 4' span.										
<b>Cross Tee to Cross Tee</b>										
<input type="checkbox"/> EA7947			24" x 48"	24" x 24"	48" x 48"	48" x 48"	48"	48"	100.0 lbs.	100.0 lbs.
48" cross tees tested as follows: EA7947 tested at 18.4 lbs./lin. ft. to 1/360 of 4' span.										

**Main Beam** ↑ **Hanger Wire** (•)  
 \* Fixtures weighing more than 56 lbs. should be independently supported. Fixture weight is based on single fixture only. For end-to-end fixtures or other configurations not shown, consult your Armstrong representative.  
 NOTE: The above data is based on 48" hanger wire spacing, board weight of 1 lb./sq. ft., maximum deflection of tees not to exceed 1/360 of the span, and suspension system installed in accordance with ASTM C 636.

### COLOR SELECTION

White




### LIGHT FIXTURES

NOTE: Specify light fixtures designed to install with 2" web height suspension systems. Compatible light fixtures:


MANUFACTURER	ITEM #
Lithonia	CLRM-150 SRT-2x4_F MP4270
Guth	KLEENSEAL KRT 200
Morlite	CRGHEPA24 Series

### DETAILS


15/16"  
Aluminum  
Main Beam  
and Cross Tee




Clean Room  
Angle Molding  
for use with  
15/16"  
Clean Room  
Suspension  
System



1-1/2"  
Aluminum  
Main Beam  
and Cross Tee



Clean Room  
Angle Molding  
for use  
with 1-1/2"  
Clean Room  
Suspension  
System



### SEISMIC PERFORMANCE

**Main Beams**  
EA7903, EA7900

**Minimum Lbs. To Pull Out Compression/Tension**  
294.6

**Cross Tees**  
\*EA7947, EA7927, EA7940, EA7920

**Minimum Lbs. To Pull Out Compression/Tension**  
492.4

#### ICC Reports

For areas under ICC jurisdiction, see ICC evaluation report number 1308 for allowable values and/or conditions of use concerning the suspension system components listed on this page. The report is subject to reexamination, revisions, and possible cancellation.

\* Note: Requires use of #6 Phillips self-tapping screw through cross tee end detail.

### PHYSICAL DATA

#### Material

1-1/2" Co-Extruded Aluminum with PVC face – Gasketed

15/16" Co-Extruded Aluminum with aluminum-capped face – Gasketed

#### Surface Finish

Textured PVC for 1-1/2"

Baked polyester for 15/16"

White aluminum – Capped face

Manufactured and tested in accordance with ASTM C635

#### Cross Tee/Main Beam Interface

Co-Extruded Aluminum Clean Room – Flush Fit

#### End Detail for 1-1/2"

Main Beam: Staked-on clip

Cross Tee: Integral hook

#### End Detail for 15/16"

Main Beam: Integral

Cross Tee: Staked-on clip

TechLine / 1 877 ARMSTRONG  
armstrongceilings.com/commceilings  
(search: suspensionsystem)  
BPCS-3070-1116

LEED® is a registered trademark of the U.S. Green Building Council  
All other trademarks used herein are the property of AWI Licensing LLC  
and/or its affiliates © 2016 AWI Licensing LLC  
Printed in the United States of America

**Armstrong®**  
CEILING SOLUTIONS