

SHEETROCK® Brand Sand Finish Paint Additive

Preparation	Surface must be structurally sound, dry, clean, and free of scaly paint, wallpaper, wax, dust, and dirt.
Mixing	<p>Add approximately 8 oz. (0.22 kg) of additive to one gal. (3.78 L) of latex- or oil-based paint to create a medium texture finish on walls, ceilings, or wood surfaces. If a heavier or lighter texture is desired, more or less additive may be used. When using dark paint colors, mix 2-3 hours before painting, and allow to stand.</p> <p>Note: When attempting a heavier-than-average finish, test a small area before starting the job. The use of too much additive may cause cracking when paint is dry.</p>
Application	Apply paint or varnish according to manufacturer's directions, using brush or roller. If desired, a sponge, whisk broom, or other tool may be used on wet paint to further modify the texture.
Cleanup	Clean all brushes, rollers, and equipment immediately, referring to the instructions provided by the paint or varnish manufacturer.

Trademarks

The following trademarks used herein are owned by United States Gypsum Company or a related company: SHEETROCK.

Note

Products described here may not be available in all geographic markets. Consult your U.S. Gypsum Company sales office or representative for information.

Notice

We shall not be liable for incidental or consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than their intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from the date it was or reasonably should have been discovered.

SAFETY FIRST!

Follow good safety practices. Read material safety data sheets and related literature on products before specification and/or installation.

