METALWORKS™ Concealed

smooth texture



Large-size panels with concealed suspension are 100% accessible.

KEY SELECTION ATTRIBUTES

- Narrow 1/4" reveal offers clean, monolithic look
- · Hook-on panels provide safe and secure downward accessibility
- · Create continuous look or use with clouds and perimeter trim
- Lightweight panels install with standard 15/16" suspension system
- · Complete standard system from one manufacturer



Silver Grey (SG)



Gun Metal Grey (MY)

PERFORATION OPTIONS (1:2 scale shown)









WITH INFILL PANEL

METALWORKS™ Concealed

Item

METALWORKS™ Concealed

No. ◆

6664_ _ _ _ _

6665_ _ _ _ _

6666_ _ _ _ _

6667_ _ _ _ _

6668_ _ _ _ _

smooth texture

Edge

Profile

1/4" Reveal

VISUAL SELECTION

Perforations

M1: M10

M1; M10

M1 · M10

Dimensions (Inches)

24 x 96 x 5/8"

48 x 48 x 5/8"

48 x 96 x 5/8"


24 x 120 x 5/8" M1; M10

WxLxH

Dots represent high PERFORMANCE level of performance.

Light Reflect	Wash	Scrub	Impact	Soil
		mm	® ^`	.∩.
(White Only)	Durability —			
0.77 (M1)	•	•	•	•
0.77 (M1)	•	•	•	•
0.77 (M1)				
0.77 (M1)				
U.11 (WII)	•	•	•	•

ACOUSTICAL INFORMATION



Maximum NRC and CAC achieved with acoustical infill options. For additional Infill options, refer to Pg. 140.

† With BioAcoustic™ infill item 5479. NRC of 0.90 with fiberglass infill 8200100, NRC 0.80 as sold.



48 x 120 x 5/8" M1; M10

ACCESSORIES

Item No. ◆	Description	Dimensions (Inches)	Color	Pieces/Carton
6656M1	MetalWorks Concealed Trim	6" x 120"	WH, SG, MY	6
7842A	Slip-on Molding	1/2 x 120 x 5/8"	WH, SG, MY	40
FXTBC	T-bar Connector Clip	_	-	10
FX4SPLICE	Splice Plate with Set Screws	-	-	10
8200100	Fiberglass Infill Panel	24 x 24 x 1"	Black (Gloss)	12
5823	BioAcoustic™ Infill Panel	24 x 24 x 5/8"	Black	12
5479	BioAcoustic™ Infill Panel	24 x 24 x 5/8"	Beige	12
7239	Adjustable Trim Clip	_	N/A	50

0.77 (M1)


NOTE: Adjustable Trim Clip used with standard Axiom or MetalWorks Trim systems.

SUSPENSION SYSTEM

15/16" Heavy-duty Prelude® XL® Suspension System (See Pgs. 365-366 for components.)

5986	T-Bar Hook†	Nominal 4 x 2 x 3"	50
90190A242	#10 Pan Head Sheet Metal Screw	1/2"	100
6091	Safety Cable	24" x 3/32"	50
SH12	Support Hanger	144" x 2"	12

† For 24" x 96", 48" x 48", and 48" x 96" panels, install 4 hooks per panel; for 24" x 120" and 48" x 120" panels install 6 hooks per panel. NOTE: Refer to installation instructions at armstrongceilings.com/installation for a better understanding of suspension requirements



PHYSICAL DATA

Material

Aluminum composite – 0.57" thick

Surface Finish

Factory-applied powder-coated finish (post-coated)

Acoustical Performance

MetalWorks Concealed perforated panels provide outstanding acoustical correction. NRC 0.95 achieved with acoustical infill item 5823. See CS-4172 for more information on infill panels.

Fire Performance

ASTM E84 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed 50 or less

Installation Considerations
Please refer to installation instructions LA-297890 before installing MetalWorks Concealed panels.

Seismic Restraint

MetalWorks Concealed panels have been engineered, tested, and approved for application in all seismic areas when installed per Armstrong installation instructions.

Warranty

Details at armstrongceilings.com

Weight 0.97 lbs/SF (Bulk packaged)



LEED® is a registered trademark of the U.S. Green Building Council Revit® is a registered trademark of Autodesk, Inc. All other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2018 AWI Licensing LLC Printed in the United States of America



[◆] When specifying or ordering, include the appropriate perforation and color suffix with the item number (e.g., 6664 M 1 M Y).