

# METALWORKS™

## Accent & Acoustical Canopies

25% RECYCLED CONTENT

Calculate LEED contribution at [armstrongceilings.com/greengenie](http://armstrongceilings.com/greengenie)

LEED®



LOCATION DEPENDENT



MetalWorks™ Canopies in White

**COLORS** Due to printing limitations, shade may vary from actual product.



### VISUAL SELECTION

Item Number*	Shape	Dimensions (Inches)
<b>METALWORKS Canopies</b>		
5376_ _ _ _	Hill	74-1/2 x 46-1/2 x 1-1/2"
5377_ _ _ _	Valley	74-1/2 x 46-1/2 x 1-1/2"

\* When specifying or ordering, include the appropriate 2-digit perforation code and 2-digit color suffix (e.g. 5376 M 3 W H) with the item number.


Standard items are 5376M3WH, 5376M10WH, 5377M3WH, and 5377M10WH. All other items are subject to extended lead times. Flat canopies are available as custom. For details, contact TechLine at 1 877 ARMSTRONG.

### PERFORMANCE

Dots represent high level of performance.

Light Reflect	Wash	Scrub	Impact	Soil
(White Only)	Durability			
0.90	•	•	•	•
0.90	•	•	•	•

### PERFORATION OPTIONS



### ACCESSORIES

Item Number	Description
7006	Escutcheon Kit – Used when hanging canopy below an existing ceiling. Two kits needed per MetalWorks canopy.

Carton contains: Pre-curved MetalWorks canopy, suspension hardware, and 6 ft. 6 in. cables (4 cables per panel).

### PHYSICAL DATA

**Material**  
Aluminum composite

**Panel Arc**  
Hill or Valley – 9°

**Surface Finish and Edge Detail**  
Factory-applied post-production powder-coated finish;  
Light reflectance 0.75 – White unperforated only;  
Curved (hill/valley) – edge detail width:  
45° angle, edge detail length: 90° angle

**Fire Performance**  
Flame Spread Index 25 or less. Smoke Developed Index 50 or less.

MetalWorks canopies, as with other architectural features located in the ceiling plane, may obstruct or skew the existing or planned fire sprinkler water distribution pattern, or possibly delay the activation of the fire

sprinkler or fire detection system. Designers and installers are advised to consult a fire protection engineer, NFPA 13, and their local codes for guidance on the proper installation techniques where fire detection or suppression systems are present.

**ASTM E1264 Classification**  
Fire Class – Class A  
Unperforated – Type XX, Pattern G  
Perforated – Type XX, Pattern C

**Acoustical Performance**  
M3 Extra Microperforated – 36 Sabin per canopy with included acoustical fiberglass infill; or 1.15 Sabin/SF

**Design Considerations**  
MetalWorks canopies are not approved for exterior application. The MetalWorks canopies cable hanging system must not hang from any commercial ceiling suspension system. The canopy must not be used to support any other material. Please note that

the White finish on this product may vary slightly from Armstrong Global White.

**Installation Consideration**  
MetalWorks Canopies require two people to handle and install a panel safely. See installation instructions on web site for details.

**Seismic Restraint**  
Refer to ASCE 7-10, Section 13.5 Architectural Components, for seismic requirements. Section 13.5, item 2 refers to 13.2.3 Consequential Damage.

**Suspension System**  
Hardware and cables are included in each kit.

**Warranty**  
Details at [armstrongceilings.com/warranty](http://armstrongceilings.com/warranty)

**Weight**  
Hill or Valley 62.4 lbs; one canopy per carton

TechLine™ / 1 877 ARMSTRONG  
[armstrongceilings.com/metalworks](http://armstrongceilings.com/metalworks)  
(search: metalworks canopies) BPCS-5086-815

LEED® is a registered trademark of the U.S. Green Building Council  
RAL is a registered trademark of RAL gGmbH. All other trademarks used herein are the property of AWI Licensing Company and/or its affiliates  
© 2015 AWI Licensing Company Printed in the United States of America

**Armstrong®**  
CEILING SOLUTIONS

36

CLOUDS & CANOPIES