# **DRYWALL GRID SYSTEM**

## **Clips and Accessories**

### **VISUAL SELECTION**

Item Number	Description	
□ DWACS 100 pcs/bucket □ FZDWACS 50 pcs/bucket	DWACS – Drywall Attachment Clip – Facilitates transition from drywall to acoustical ceiling; locks under bulb of grid section to prevent upward movement and provide secure attachment surface on one side of exposed grid	NOTE: For use with 15/16" face dimension suspension system.
□ DW30CAG - 30° □ DW45CAG - 45° □ DW60CAG - 60° □ DW90CAG - 90° 250 pcs/bucket	Drywall Angle Clip — Used to create positive and secure angles for drywall and ceiling installations on either main beams or cross tees; attachment to be made with 7/16" pan head screw	
☐ FZDW30CAG — 30° ☐ FZDW45CAG — 45° ☐ FZDW60CAG — 60° ☐ FZDW90CAG — 90° 50 pcs/bucket		DW30C – 30°  DW45C – 45°  DW60C – 60°  Main Beam  Drywall  Furring  Tees  Drywall  Drywall  Drywall  Drywall  Drywall  Drywall  Drywall  Drywall  Drywall  Drywall
RC2AG 250 pcs/bucket FZRC2AG 50 pcs/bucket	RC2 – Radius Clip is used for drywall applications which form curved installations; attaches to the cavity side of web of the main beam with four 7/16" pan head screws. Install	DW90C – 90°  Angle Clip Item DW90C  OOO  OOO  OOO  OOO  OOO  OOO  OOO
RC1 200 pcs/bucket  FZRC1 50 pcs/bucket	at all knockout locations.  RC1 – Splice Clip is used as a main beam splice or partition top trim splice	
□ <b>TT10</b> 30 pcs/bucket	TT10 - 10' Partition Top Trim - Used to finish off the top of a drywall partition for a continuous drywall/acoustic ceiling interface	Item TT10  Item RC1 Splice Clip
GSC9 (1" to 4") GSC12 (4" to 8") GSC16 (8" to 14") 100 pcs/bucket	Adjustable Grid Spacer Clip — Used to space two parallel main beams for light fixtures, air diffusers, etc.; allows for 1/4" adjustments with three different clips	lînûnînân
☐ FZGSC9 (1" to 4") ☐ FZGSC12 (4" to 8") ☐ FZGSC16 (8" to 14") 50 pcs/bucket		
.ocking □ DW58LT – 5/8" Gypsum □ DW50LT – 1/2" Gypsum 125 pcs/bucket	Drywall Transition Clip with Locking Tabs -Facilitates transition from drywall to acoustical ceiling; one-sided hold down clip; eliminates need for drywall bead. Locking tabs provide secure location for DGS cross	
FZDW58LT - 5/8" Gypsum FZDW50LT - 1/2" Gypsum 50 pcs/bucket	tees.	
Non-locking □ DW58AG - 5/8" Gypsum □ DW50AG - 1/2" Gypsum 125 pcs/bucket		



## **DRYWALL GRID SYSTEM**

### **Clips and Accessories**

#### **VISUAL SELECTION**

Item Number	Description		
<ul> <li>□ EHDC50 (for 1/2" ceiling panels and drywall)</li> <li>□ EHDC58 (for 5/8" ceiling panels and drywall)</li> <li>□ EHDC75 (for 3/4" ceiling panels and drywall)</li> <li>125 pcs/bucket</li> <li>□ FZEHDC50 (for 1/2" ceiling panels and drywall)</li> <li>□ FZEHDC58 (for 5/8" ceiling panels and drywall)</li> <li>□ FZEHDC75 (for 3/4" ceiling panels and drywall)</li> <li>50 pcs/bucket</li> </ul>	External Hold Down Clip locks under bulb of grid section to prevent upward movement and provide secure attachment surface. Keeps acoustical and drywall ceiling components in place during wind uplift and in high security areas.	EHDC50	
DLCCAG 250 pcs/bucket  FZDLCCAG 50 pcs/bucket	DLCC – Direct Load Ceiling Clip is used to hang suspension system below existing 15/16" grid face, transferring weight directly to hanger wire; may be used to preserve the fire rating of an existing ceiling and to support heavy accessories	0	
□ DDC 250 pcs/bucket □ FZDDC 50 pcs/bucket	DDC — Double Drywall Clip is used to hang suspension system below existing 1-1/2" grid face, transferring weight directly to hanger wire; may be used to preserve the fire rating of an existing ceiling and to support heavy accessories; allows for double layer of 5/8" gypsum board		
DWC 250 pcs/bucket	DWC – Drywall Clip allows for a "second" ceiling to be installed below a drywall ceiling; attaches through installed drywall to supporting structure	(0) (0)	
□ MBACAG 70 pcs/bucket □ FZMBAC 50 pcs/bucket	MBAC – Main Beam Adapter Clip attaches to web of suspension system section; provides larger surface for screw attachments; used as a hold down clip for thin material (metal or plastic lay-in panels); fastens drywall track to underside of exposed suspension system with lay-in panels, leaving suspension system face free of screw holes		
□ XTAC 100 pcs/bucket □ FZXTAC 50 pcs/bucket	XTAC - Cross Tee Adapter Clip is used to attach field cut cross tees to main beams	0 0 0	
QSUTC 150 pcs/bucket  FZQSUTC 50 pcs/bucket	QSUTCA — QuikStix™ Uptight Clip saves time in tight plenum areas and is adjustable to uneven surfaces		
□ IIC 36 pcs/bucket	Impact Isolation Clip for use with HD8906IIC drywall grid main beam. Provides up to 8 points of IIC improvement to ensure your project meets IBC requirements.  IIC Clip must be used with HD8906IIC Drywall Grid Main Beam		
□ WS12 1000 pcs/bucket □ FZWS12 50 pcs/bucket	Hanger Wire Splice – Splices two pieces of 12 guage wire pieces for extra long wire drops or renovation work		

The FastShip™ Clips and Accessories Program offers over 90 clip and accessory items that are available for overnight or ground delivery direct to the jobsite in full-size or 50 piece cartons.



