


AC11-23X8S2OUC

V0

GEA COB LED Uplight recessed



Description

Floor recessed for indoor and outdoor use.


For uplighting. Electronic components are in a sealed internal compartment, completely separate from the compartment where the connection terminals are located. The unit will withstand a static weight of 1,800 Kg and the occasional transit of slow-moving vehicles. Includes 2 anti-glare accessories. Includes 2 reflectors. Includes flush-mounting box. Suitable for installation in marine environments. Includes 2 cable outlets to facilitate chain mounting. Maximum light surface temperature below 40°C. Adjustable light source. Structure material: Stainless steel AISI316, High purity aluminium. Structure finish: Polished, Black. Diffuser material: Glass. Diffuser finish: Tempered. UV protection. Warranty: 2 Years.

Finish

Polished
Black
Tempered

Material

Stainless steel AISI316
High purity aluminium
Glass



TECHNICAL CHARACTERISTICS

Light source

Light source: LED CREE
Output (W): 23W
Total power consumption (W): 27.6
Color temperature: Neutral white - 4000K
CRI: 80
Real Lumen: 2347
Nominal Lumen: 2993
Qty Leds: 1
Lm/Real W: 85
Life Time: 60.000h L80B20
Bin / Grup: 40H
MacAdam steps: 2 steps
UGR: -
Photobiological risk: RG1

GEAR

Voltage / Frequency:
100-240V/50-60Hz
Power Factor: 0.93
Flickering: 0.027

Luminaire

Temperature on the surface: 40.00
Double cable exit: Yes
Drainage: Yes
Recessed: Si
Public Areas: 1800
Maintenance: Producto sin barniz. Se puede utilizar estropajo abrasivo
Seaside: Yes
Cable meters included: -
Uv Protection: Yes
Warranty: 2 Years

Logistics

Energy Efficiency: LED A++
EAN Code: 8435526801466
Net Weight (Kg): 3.275
Weight in Kg (packaged): 3.459
Packing: 235 x 235 x 195
Masterbox: 4

The photograph may not match the reference exactly. Please read the product description to identify the finish.

