


05-E012-14-CM

V0

KÖSSEL Wall fixture



Description

Wall fixture

For frontal lighting and downlighting. Includes filters to emulate warm light. Specially designed to conceal all mounting screws. Includes easily interchangeable decorative front panels in various finishes. Suitable for installation in marine environments. Includes 2 cable outlets to facilitate chain mounting. Structure material: Polycarbonate + ABS. Structure finish: White. Diffuser material: Polycarbonate. Diffuser finish: Transparent. UV protection. Warranty: 2 Years.

Finish
White
Transparent

Material
Polycarbonate + ABS
Polycarbonate



TECHNICAL CHARACTERISTICS


Light source
Light source: LED EDISON
Output (W): 6.4 W
Total power consumption (W): 7 W
Color temperature: Neutral white - 4000K
CRI: 80
Real Lumen: 295
Nominal Lumen: 825
Qty Leds: 18
Lm/Real W: 42
Life Time: 59.000h L70B30
Bin / Grup: 403
MacAdam steps: 3 STEPS
UGR: 16
Photobiological risk: RG0

GEAR
Brand: EAGLERISE
Gear included: Yes, electronic
Voltage / Frequency: 100-240V/50-60Hz
Power Factor: 0.87
Flickering: 28.1%

Luminaire
Double cable exit: Yes
Drainage: No
Seaside: Yes
Uv Protection: Yes
Warranty: 2 Years

Logistics
Energy Efficiency: LED A++
EAN Code: 8435381495923
Net Weight (Kg): 0.500
Weight in Kg (packaged): 1.126
Packing: - x - x -
Masterbox: 12

The photograph may not match the reference exactly. Please read the product description to identify the finish.



PLANTILLA DE INSTALACIÓN
INSTALLATION TEMPLATE

