

Jot Modular

Product Specifications

Collection Name	GroupThink		
Style Number	I0295		
Product Type	Modular		
Construction	Multi-level Pattern Loop		
Fiber Type	Solution Q Extreme® Nylon		
Dye Method	100% Solution Dyed		
	English	Metric	
Gauge	1/12	47.24 per 10 cm	
Stitches Per Inch	10	39.37 per 10 cm	
Tufted Pile Height	3/32" low - 5/32" high	2.38mm - 3.97mm	
Tufted Yarn Weight	22 oz.	745.93 g/m²	
Finished Pile Thickness		.104	2.64 mm
Total Thickness		0.250	6.35 mm
Product Size	24" x 24"	60.96 cm x 60.96 cm	
Average Density	7615	14.18 kilotex	
Installation Pattern Repeat	none		
Primary Backing	Non-Woven Synthetic		
Secondary Backing	EcoWorx® Tile		
GSA Approved Product	Yes		


Performance Specifications

Traffic Class	Severe (TARR)
Antimicrobial Assessment	Passes (AATCC-174) (When installed using Shaw 5036 adhesive)
Methenamine Pill Test	Passes (DOCFF-1-70)
Radiant Panel	Class I (ASTM E-648)
NBS Smoke	<450 (ASTM E-662) (ASTM-E-662)
Electrostatic Propensity	Less than 3.5Kv (AATCC-134)
CRI Green Label Plus	Certified GLP9968
ADA Compliance	This product meets the guidelines as set forth in the Americans with Disabilities Act for minimum static coefficient of friction of 0.6 for accessible routes.

Warranty Information

Lifetime Commercial Limited

Installation Methods



transforming performance.



Environmental Specifications

Recyclability	100% recyclable
---------------	-----------------

Materials

Ingredients

does not contain PVC, phthalates, or PBD/PBDE

Recycled Content

Total Recycled Content (by weight)	38 %
Pre-Consumer	38 %
Post-Consumer	0 %
Bio-Based/Rapidly Renewable Content (By Weight)	0 %
Packaging	100% Recyclable
Country of Origin (manufacturer)	USA

Meets or exceeds all local and national regulations in country of manufacture.
Manufactured in an ISO9001 & ISO14001 certified facility or equivalent.
Recycled content is calculated using system allocation, mass balance, and direct insertion.
The actual recycled content in this product will likely vary. For more information email info@shawgreenedge.com.

Third Party Certifications

MBDC Cradle to Cradle	Silver Certified
NSF 140	gold certified
CRI Green Label Plus	Certified GLP9968
USGBC LEED	contributes

Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate specification changes without notice. This carpet is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another carpet design is also strictly prohibited. Visit patcraft.com/testing for more information.

transforming performance.